MILITARY SPECIFICATION

STATIC TUBE - SELF ALIGNING
M - 74 TRAINER

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of static tube entitled Static Tube - Self Aligning used on the M - 74 Nike Hercules Trainer.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8846004	- Static Tube - Self Aligning
8846373	- Nose Section Assembly - Packaging Drawing

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

3.2 Assembly. The static tube shall comply with all requirements specified on the drawing (dwg) 8846004, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Finish. The static tube shall have a surface showing a maximum porosity of 0.031 diameter by 0.031 deep in any outside surface. The total area of pores in a square inch of surface shall not exceed 1/2 square inch.

3.5 Swivel of Nose Cone Assembly. The nose cone assembly shall swivel as specified when tested as specified in 4.4.1.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8846004) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I
First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Swivel of nose cone assembly (see 3.5)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Static Tube - Self Aligning Assembly (see dwg 8846004).

Categories — Characteristics — Method of Inspection

Critical: None defined.

Major:

101. Crack in any component.....Visual
102. Evidence of poor workmanship (see 3.6).....Visual
103. Any operation missing.....Visual
104. Portion of any component broken away.....Visual
105. Large insert in collar assembly not concentric.....Visual
106. Porosity in excess of permissible (see 3.4).....Visual
107. Vanes loose or missing.....Visual
108. Nose cone assembly connot be swiveled.....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

109. Markings misleading, unidentifiable or mislocated.....Visual
110. Static probe point damaged.....Visual
111. Orientation spring pin missing.....Visual
112. Nose collar assembly screw missing.....Visual
113. Preformed packing missing.....Visual
114. Objective evidence relating to material missing or improper (see 3.1).....Visual

Minor: None defined.

4.3.2.1.2 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation and packaging not in accordance with dwg 8846373	Visual
102.	Packaging not in accordance with applicable dwg or specification (see 5.2)	Visual
103.	Marking not in accordance with dwg 8846373	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Swivel of nose cone assembly	Major

This test is not considered destructive and samples so tested shall be returned to the production lot.

4.3.3.1 Swivel, nose cone assembly. Each static tube assembly in the lot shall be tested as accordance with 4.4.1. If any item fails to comply with 3.5, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

4.3.4.1 Major and Minor characteristics and tests. Inspection and testing shall be performed with the acceptance test equipment, operating instructions and calibration instructions prepared by the contractor. The contractor shall obtain approval of such designs, operating instructions and special calibration instructions as specified in 6.3 prior to use on the contract.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Swivel of nose cone assembly. The nose cone assembly shall be free to swivel about the mast up to the point where the inside of the probe assembly touches the mast.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The static tube shall be packaged in accordance with dwg 8846373 using the specified moisture barrier.

5.1.2 Level C. The static tube shall be packaged in accordance with dwg 8846373 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Levels A and C. The static tube shall be packed in accordance with the following.

5.2.1.2 Shipment with trainer. When shipped as a component of the trainer, the Static Tube - Self Aligning shall be installed in accordance with dwg 8846373.

5.2.1.3 Spares. When shipped as spares, the Static Tube - Self Aligning shall be packed in accordance with the minimum package and pack which will afford adequate protection against corrosion, deterioration, and physical damage during the shipment from supply source to the first receiving activity for immediate use. Shipping containers shall be snugly packed and constructed so as to insure acceptance by a common carrier or air express for safe transportation to the point of destination. Containers shall conform to the requirements of the Consolidated Freight Classification rules in effect at the time of shipment, except that fiberboard, when used, shall have a minimum Mullen test of 275 pounds. Containers shall be able to withstand storage, rehandling, and reshipment without the necessity of repacking.

5.3 Marking. Marking shall be in accordance with dwg 8846373.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2128 Rev 1 dated 6 February 1964.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1135-A197

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:03Z
Check the source to verify that this is the current version before use.