MILITARY SPECIFICATION

WELDING MACHINE, RESISTANCE, SPOT-TYPE

PORTABLE

This specification is approved for use by the Armament Research and Development Engineering Center (Tool and Equipment Engineering Division, Standardization and Specification Engineering Branch), Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of manually operated, portable, resistance spot-welding machine.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

W-C-596	-	Connector, Electrical, Power, General Specification for.
W-C-596/66	-	Connector, Plug, Electrical, General Purpose, General Grade, Grounding 2 Pole, 3 Wire, 20 Amperes, 250 Volts, 50/60 Hertz.
W-C-596/169	-	Connector, Plug, Electrical, General Purpose, Grounding, 2 Pole, 3 Wire, 30 Amperes, 250 Volts, 50/60 Hertz.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Engineering Center, ATTN: SMCAR-EST-S, Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3432
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-152	-	Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment.
MIL-V-173	-	Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment).
MIL-W-45562	-	Welding and Soldering Equipment, Supplies, and Accessories, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28	-	Screw-Thread Standards for Federal Services.

MILITARY

DoD-STD-2000-1	-	General Purpose Soldering Requirements for Electrical and Electronic Equipment
MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	-	Identification Marking of US Military Property
MIL-STD-889	-	Dissimilar Metals
MIL-STD-1190	-	Minimum Guidelines for Level C Preservation, Packing and Marking

* 2.1.2 Other Government drawings and publications. The following other Government drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

US DEPARTMENT OF LABOR

29 CFR, Chapter XVII, Part 1910 - Occupational Safety and Health Standards

(Copies of specifications, standards, handbooks, other Government drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B5.10 - Machine Tapers

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E380 - Standard for Metric Practice

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

NATIONAL ELECTICAL MANUFACTURERS' ASSOCIATION (NEMA)

NEMA ICS 1 - General Standards for Industrial Control and Systems.

(Applications for copies should be addressed to the National Electrical Manufacturers' Association, 2101 L Street, NW, Washington, DA 20037.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 70 - National Electrical Code.
NFPA 79 - Electrical Standard for Metalworking Machine Tools Plastics Machinery.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specification, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3 REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish one or more complete welding machines for first article inspection (see 4.3 and 6.2.1).

* 3.2 Design. The welding machine shall be new and of the manufacturer's current design meeting the performance requirements specified herein. The machine shall be a resistance spot welding type that is portable, manually operated, and suitable for spot welding gage sheet metal constructions such as cabinets and tool boxes. The welding machine shall incorporate a control to permit adjustment of welding time. The control shall have a timing adjustment range of 0.1 second to 1.5 seconds, with a repeatable accuracy of $\pm$0.05 second. The control may be either a remote control device or be an integral part of the welding machine.

3.2.1 Safety and health requirements. Safety devices shall be provided for all parts presenting safety hazards. Guards shall be removable to provide easy access to guarded parts. The welding machine shall comply with the general safety and health requirements promulgated under 29 CFR, Chapter XVII, Part 1910 that are applicable to the machine itself. Exceptions and additional requirements for safety and health shall be as specified in the contract (see 6.2.1 and 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

3.2.2 Measurement system. The US Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of the welding machine. In this specification, all measurements, dimension sizes and capacities are given in the US system. These measurements may be converted to the SI system by using the conversion factors and methods specified in ASTM E380.

3.3 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the welding equipment industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.3.1 Reclaimed materials. The contractor is encouraged to use reclaimed materials for fabricating new parts without jeopardizing the chemical and physical properties, design integrity, and intent of the materials originally selected or specified. The reclaimed materials shall have reprocessed, remanufactured, or recycled in a manner that shall restore them to the same chemical composition and physical properties as the materials originally selected for use. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment.

3.4 Construction. The welding machine shall be furnished as a complete unit so that, when connected to the proper power source, it can be used for any operation for which designed.

* 3.4.1 Castings and forgings. All castings and forgings shall be free from defects, scale, and mismatching. No process such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part.

3.4.2 Welding, brazing, and soldering. Welding, brazing, and soldering shall be of a quality which shall sustain all requirements of the welded, brazed, or soldered parts. These operations shall not be employed as repair measures for defective parts.

* 3.4.3 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness. When subject to removal or adjustment, these parts shall not be swaged, peened, staked or otherwise permanently deformed.

* 3.4.4 Electrical connections. Connections of conductors and terminal parts shall be of the screw, pressure, or solder type. When soldered connections are used, the conductors and terminal parts shall be mechanically secured before soldering. Only rosin base fluxes shall be used in soldering operations. Connections to screw-type terminals shall be mechanically secured with means to prevent loss of tightness. Soldering shall conform to DoD-STD-2000-4.

3.4.5 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

3.4.6 Lubrication. All bearings (except sealed-for-life type), mating gears, and sliding parts shall be provided with standard means for lubrication. Oil holes, grease fittings, and filler caps shall be accessible without requiring disassembly of functional parts. Lubrication reservoirs, if applicable, shall have means for checking levels (see 6.5).

* 3.4.7 Interchangeability. All parts of the welder shall be manufactured to definite standards and tolerances. All respective parts of the welder shall be interchangeable without requiring modification of the replaced part or its mating components. All spare and repair parts subject to possible future replacement shall be assigned a manufacturer's part number and shall be identified in the repair parts manual. All replacement, repair and spare parts shall provide the same or better form, fit, function, and performance as the respective parts initially installed in the welder. When industry or Government standards are applicable, all replacement parts shall conform to the standards.

3.4.8 Parts. All parts used in construction of the welding machine shall be new. Those parts subject to wear, breakage, or distortion shall be accessible for adjustment, repair, and replacement without modification, distortion, or damage to the machine or any machine part.

3.4.9 Surfaces. Surfaces of all castings, forgings, molded parts, stampings, and welded parts shall be clean and free of sand, dirt, fins, sprues, scale, flux and other harmful or extraneous materials.

3.5 Performance and product characteristics.

3.5.1 Performance. The welding machine shall spot weld two 14 gage (0.0747 inch) 1020, cold rolled, mild steel sheets, two 16 gage (0.0598 inch) 304 stainless steel sheets, and two 18 gage (0.0516 inch) galvanized steel sheets. All spot welds shall have sufficient fusion to withstand attempts at separation by peeling without weld spot failure or separation. All gages shall be manufacturers standard gage for steel sheets.

3.5.2 Continuous duty. The welding machine shall spot weld two 14 gage (0.0747 inch) 1020, cold rolled, mild steel sheets a minimum of ten welds per minute for a period of three minutes. The temperature of the welding machine components and electrodes shall not exceed the manufacturer's design limits for this type machine.

3.5.3 Capacity. The welding machine shall have a rated output capacity at a 50 percent duty cycle of not less than 2.5 kilovolt-ampere (kVA).

* 3.5.4 High voltage requirement. The entire electrical system of the welding machine shall withstand, without damage, malfunction, breakdown, arcing, surface or air discharge, at least 2500 volts root mean square (RMS), 60 Hertz of electrical energy, at room standard ambient temperature. The electrical energy shall be applied instantaneously at full voltage of at least 2500 volts, and shall be maintained for at least 15 seconds. Each circuit shall be isolated from other circuits and all circuits shall be isolated from electrical ground. Solid state control components may be damaged as a result of high voltage and is no cause for rejection. Damage to solid state control components may be avoided by wiring around or by-passing them, terminal to terminal. No arcing or discharge from solid state control components is acceptable.

3.6 Components. The welding machine shall consist of, but not limited to, the components specified in 3.6.1 thru 3.6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

* 3.6.1 Transformer. Unless otherwise specified (see 6.2.1), the welding machine shall operate from a power source of 208/230 volts, 60 Hz, single phase current. The transformer shall be of suitable design to provide the necessary current to meet the requirements specified herein. The transformer shall be not less than 2.5 kVA rated capacity as specified in 3.5.3.

* 3.6.2 Pressure holding mechanism. The pressure holding mechanism shall be hand operated and shall consist, essentially, of a toggle or cam action mechanism holding two electrodes in such a position that, when the handle is depressed, sufficient pressure and current will spot weld the adjoining metal. The pressure holding mechanism shall assure that a clamping or welding squeeze force of at least 450 pounds is generated when welding with short welder arms of five inch throat depth. When the holding mechanism is an integral part of the transformer, the weight shall not exceed 35 pounds. When the holding mechanism is separate from the transformer, it shall be connected by not less than ten feet of flexible electric welding cable of the proper capacity, temperature, and voltage rating for the intended use.

* 3.6.3 Electrodes (spot-welder arms). Electrodes with tips shall be furnished for use with the welding machine. The electrodes shall hold the workpieces together at the point of contact until the weld has been accomplished. The required tips shall have a standard thread of Morse taper, conforming to FED-STD-H28 or ANSI B5.10, respectively. One each of the following electrodes shall be furnished with each machine:

90 Degree Electrodes - no effect
- 5 inch throat depth
- 12 inch throat depth
- 18 inch throat depth

90 Degree Electrodes - 7 to 8 inch offset
- 10 inch throat depth
- 16 inch throat depth

45 Degree Electrodes - no effect
- 5 inch throat depth
- 12 inch throat depth
- 18 inch throat depth

3.6.4 Electrical components. Electrical components of the welding machine, including starters, relays, switches, wiring, and their enclosures shall conform to, and shall be located in accordance with, NEMA ICS 1 and NFPA 79, as applicable. There shall be no component used in any application where the requirements exceed the manufacturer's rating for the part.

3.6.5 Power supply cord. Unless otherwise specified (see 6.2.1), each welding machine shall be furnished with not less than eight feet of three conductor, flexible electrical cord, National Electrical Code type SO, STO, or SJO, heavy duty, conforming to NFPA 70. Unless otherwise specified (see 6.2.1), the cord shall be provided with a three prong grounding plug conforming to either W-C-596/66 or W-C-596/169.

3.7 Fungus control. Components of electrical circuitry that are hermetically sealed or inherently resistant to fungus growth and moisture need not be treated. Components of electrical circuitry that are not inherently resistant to fungus growth or moisture shall be treated in accordance with MIL-T-152 and MIL-V-173.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

3.8 Painting. Unless otherwise specified (see 6.2.1), painting and finishing shall be in accordance with the best commercial practice in the industry. Before painting, all surfaces shall be clean and be free of all foreign matter detrimental to painting. At least one coat of primer (or a phosphate or chromate base) and one coat of enamel, or equivalent, i.e., epoxy enamel, shall be applied.

3.9 Product identification. The welding machine shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2.1), shall include the National Stock Number.

3.10 Workmanship. Standards of workmanship shall assure that the welding machine shall have the stability, strength, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that the products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2.1), first article inspection shall consist of examination in 4.5 and all tests under 4.6 Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Unless otherwise specified (see 6.2.1), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of (a) through (f) below. Failure of any spot welder to pass an examination or test shall be cause for rejection of that spot welder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

a. Product examination (see 4.5).

b. Pressure holding mechanism test (see 4.6.1).

c. Welder control timing test (see 4.6.2).

d. Performance test (see 4.6.3).

e. High voltage requirement test (see 4.6.6).

f. Packaging inspection (see 4.7).

* 4.4.1 Sampling. When required (see 6.2.1), sampling for quality conformance inspection shall be performed in accordance with MIL-STD-105 using inspection levels and acceptable quality levels (AQL) as listed:

Inspection or Test	Inspection Level	AQL
a. Product examination (4.5)	II	1.0
b. Pressure holding mechanism test (4.6.1)	II	1.0
c. Welder control timing test (4.6.2)	II	1.0
d. Performance test (4.6.3)	II	1.0
e. High voltage requirement test (4.6.6)	II	4.0
f. Packaging inspection (4.7)	S-4	4.0

* 4.5 Product examination. Visually and manually examine the spot welder to determine conformance with the requirements of 3.2 through 3.4.9 and 3.6 through 3.10. Visual examination shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from defects. Manual examination shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the welder and its components have passed the examinations prescribed for them by the contractor's inspection system shall be cause for rejection. In addition, failure of the contractor to provide objective and tolerances so that no replacement part will degrade the form, fit or function of the end item (see 3.4.7), shall be cause for rejection.

4.6 Tests.

* 4.6.1 Pressure holding mechanism test. Place a pressure indicating device between the two electrodes during hand operation to determine the clamping or welding squeeze generated by the pressure holding mechanism. Short welder arms of 5 inch throat depth shall be used. The pressure indicating device shall be a force transducer or any other device of sufficient size that will accurately measure a welding squeeze of at least 450 pounds. Failure of the pressure holding mechanism to generate a clamping or welding squeeze force of at least 450 pounds shall be cause for rejection (see 3.6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

* 4.6.2 Welder control timing test. The welding time of the welding machine shall be measured with a test timing device with an accuracy of ±.005 second. Adjust the welder control to the shortest time possible and record the welding time. Repeat and record the welding time of this setting a total of five times. Adjust the welder control to the longest possible time and record the welding time. Repeat and record the welding time of this setting a total of five times. Adjust the welder control to the mid-range of time and record five repetitive time readings at this same setting. Failure of the welder control to produce a minimum adjustment time of 0.1 second or less, produce a maximum adjusted time of 1.5 seconds or more, or produce repeatability of ±0.05 seconds or less (see 3.2) at any of the three constant settings shall be cause for rejection.

* 4.6.3 Performance test. The welding machine shall be used to spot weld not less than four welds each on 1020, cold rolled, mild steel, on type 304 stainless steel, and on galvanized steel sheets as specified in 3.5.1. After spot welding the metal sheets, a peel test shall be performed. This test shall be accomplished by separating the welded components by driving a chisel between them in an unwelded area or by peeling one sheet back against the weld until failure occurs around the periphery of the weld or the part (sheet) fails. Consistent failure of the base metal outside of the weld area will be considered evidence that the welds are satisfactory.

* 4.6.4 Continuous duty test. The welding machine shall be used to spot weld two 1020, cold rolled, mild steel sheets, each 14 gage thick (see 3.5.2) at a minimum rate of ten welds per minute for a period of 3 minutes. Upon completion of this test, there shall be no evidence of overheating beyond the manufacturer's design limits (see 3.5.2) or of damage to any component of the machine.

* 4.6.5 Capacity test. The capacity of the welding machine shall be determined as follows:

a. Using two pieces of 14 gage (0.0747 inch) 1020 cold rolled mild steel, spot weld at a cycle rate of 5 cycles per minute at 6 seconds on and 6 seconds off.

b. At the end of 1 minute and with the initiating switch engaged, measure secondary circuit voltage at the electrodes and measure the operating amperage.

Failure of the welding machine to provide an output of at least 2.5 kVA shall be cause for rejection (see 3.5.3).

* 4.6.6 High voltage requirement test. A test voltage of at least 2500 volts, rms, 60 hZ, shall be applied instantaneously between mutually insulated circuits and between insulated circuits and ground. The voltage shall be supplied by a transformer having a volt-ampere capacity of at least 500. The voltage shall be applied to an uninsulated point between each circuit and/or designation above. The voltage shall be maintained for at least 15 seconds to each circuit (see 3.5.4). Damage to any part or circuit evidenced by malfunction, breakdown, arcing or other surface or air discharge shall be cause for rejection.

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5 PACKAGING

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

5.1 Military preservation, packing, and marking. When specified (see 6.2.1), requirements for Level A preservation and for Levels A and B packing and marking shall be in accordance with MIL-W-45562.

* 5.2 Level C preservation, packing, and marking. When specified (see 6.2.1), preservation, packing, and marking shall be in accordance with MIL-STD-1190.

6 NOTES

* 6.1 Intended use. The welding machine described by this specification is used primarily by field military units to fabricate sheet metal constructions unrelated to automotive use and to repair weld cabinets and sheet metal items.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. First article when required (see 3.1).

c. Exceptions and additional safety/health requirements when required (see 3.2.1 and 6.4).

d. Power source (transformer) if different (see 3.6.1).

e. Power supply cord and plug if different (see 3.6.5).

f. Painting and finishing if different (see 3.8).

g. Product identification if different (see 3.9).

h. First article inspection if different (see 4.3).

i. Quality conformance inspection if different (see 4.4).

j. Sampling for quality conformance inspection when required (see 4.4.1).

k. Level of preservation, packing and marking if different (see 5.1 and 5.2).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.4 Safety and health requirements. In order that equipment integrated into the user's operational environmental will comply with 29 CFR, Chapter XII, Part 1910, limitations and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc., as applicable, specific requirements concerning such points of operation, and other health and safety requirements, should be specified by the user.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

6.5 Standard lubricants. The machine designer should specify and use to the maximum extent possible those lubricants (see 3.4.6), that are presently in the Department of Defense supply system. MIL-HDBK-113, MIL-HDBK-267, and MIL-STD-838 may be used as selection guides.

* 6.6 Subject term (key word) listing.

Continuous duty
Electrodes
Manually operated
Spot-welding
Transformer
Throat depth

6.7 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only the the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodian:
Army - AL

Review activities:
Army - MI
DLA - GS

Preparing activity:
Army - AL

Project No. 3432-A133

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:58Z
Check the source to verify that this is the current version before use.