SS-A-666d
May 7, 1968
SUPERSEDING
Int. Fed. Spec. SS-A-00666c(GSA-FSS)
October 3, 1968 and
Fed. Spec. SS-A-666b
October 16, 1968

FEDERAL SPECIFICATION

ASPHALT, PETROLEUM (BUILT-UP ROOFING, WATERPROOFING, AND DAMPPROOFING)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers petroleum asphalt for use as hot-cement and mopping coat in the construction of built-up roof coverings, in dampproofing, and in the construction of a membrane system of waterproofing.

1.2 Classification.

1.2.1 Asphalt shall be of the following types, as specified (see 6.2):

Type I - For roofs with inclines not exceeding 1 inch per foot.
II - For roofs with inclines between 1/2 and 3 inches per foot.
III - For roofs with inclines between 1/2 and 6 inches per foot.
IV - For roofs with relatively steep slopes and generally in areas with relatively high temperatures.
V - Waterproofing, dampproofing, below ground level, at moderate temperature.
VI - Waterproofing, dampproofing, above ground level, temperatures up to 125°F.
VII - Waterproofing, dampproofing, above ground level, vertical surfaces, above 125°F.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-D-705 - Drum: Metal Shipping, Steel, (Over 12 and Under 55 Gallon).
PPP-D-711 - Drum: Metal, Shipping, Steel, Lightweight (55 Gallon).
PPP-D-723 - Drums, Fiber.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

Military Standard:

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

D312 - Specification for Asphalt for Use in Constructing Built-Up Roof Coverings.
D449 - Specification for Asphalt for Dampproofing and Waterproofing.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, Pa. 19103.)

American Trucking Associations, Inc:

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Association, Inc., 1616 P St., N.W., Washington, D.C. 20036.)

Uniform Classification Committee:

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 W. Jackson Blvd., Chicago, Ill. 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Types I, II, III, and IV. Each of these types shall meet the applicable requirements of ASTM D312.

3.2 Types V, VI, and VII. Each of these types shall meet the applicable requirements of ASTM D449.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling and testing. Sampling and testing, for types I, II, III, and IV shall be in accordance with ASTM D312; for types V, VI, and VII sampling and testing shall be in accordance with ASTM D449.

4.3 Inspection of preparation for delivery. The packing and marking of the asphalt shall be inspected to determine conformance to the applicable requirements of section 5.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.1.1 Levels A and B. The asphalt shall be packed in quantities as specified (see 6.2), in a close-fitting fiber drum conforming to PPI-D-711, type I or II, grade C, as applicable.

contract. [illegible] conformance does not authorize submission of known

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:13Z
Check the source to verify that this is the current version before use.

5.1.1.1 Types I and II. Unless otherwise specified, the asphalt shall be packed in quantities as specified (see 6.2), in a close-fitting metal drum conforming to PPP-D-705, and PPP-D-711, type I, as applicable.

5.1.2 Level C. The asphalt shall be packed to insure carrier acceptance and safe delivery to destination at lowest rates. Containers and packing shall comply with Uniform Freight Classification Rules.

5.2 Marking.

5.2.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The suggested use for each type is not absolute, and overlapping of fields of use may occur between adjoining types, depending upon the kind and occupancy of the building involved; the kind of roof employed; the presence, absence, or thickness of any insulation; the specific material and construction used in the roofing membrane itself; and the temperatures and other climatic conditions to which the roofing may be subjected in service.

Type I - Suitable for use on roofs with inclines up to 1 inch per foot.
Type II - Suitable for use on roofs with inclines from 1/2 up to 3 inches per foot.
Type III - Suitable for use on inclines from 1/2 to 6 inches per foot.
Type IV - Suitable for use on roofs with relatively steep slopes and generally in areas with relatively high temperatures.
Type V - Suitable for use below ground level moderate temperature conditions both during the process of installation and service.
Type VI - Suitable for use above ground level where not exposed to temperatures exceeding 125°F. (52°C.)
Type VII - Suitable for use above ground level, where exposed on vertical surfaces in direct sunlight or at a temperature above 125°F. (52°C.).

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of asphalt required (see 1.2.1).
(c) Selection of applicable level of packing required (see 5.1).

6.3 Asphalt for dampproofing and waterproofing, types V, VI, and VII in this specification correspond respectively to types A, B, and C in ASTM D449.

MILITARY CUSTODIANS:

Army - ME
Navy - YD
Air Force - 84

User activities:

Army - None
Navy - CG, MC
Air Force - None

Review Activities:

Army - ME
Navy - YD
Air Force - 84

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:13Z
Check the source to verify that this is the current version before use.