SS–B–671c
June 2, 1965
SUPERSEDING
Int. Fed. Spec. SS–B–00671b(GSA–FSS)
September 9, 1963, and
Fed. Spec. SS–B–671a
August 20, 1937

FEDERAL SPECIFICATION

BRICK, PAVING

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers paving brick of vitrified clay or shale.

1.2 Classification.

1.2.1 *Types and sizes.* Paving brick shall be of the following types and sizes as specified (see 6.2):

	Depth inches	*Width inches*	*Length inches*
Type I—Repressed lug brick	4	3½	8½
Type II—Vertical fiber lug brick	2½	4	8½
	3	4	8½
	3½	4	8½
Type III—Wire-cut lug brick	4	3½	8½

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. There are no Federal specifications or standards applicable to this specification.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Stand-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

ards from established distribution points in their agencies.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following publication forms a part of this specification to the extent specified herein Unless otherwise indicated the issue in effect on date of invitation for bids shall apply.

American Society for Testing and Materials Specification:

C7—Specification for Paving Brick.

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

3. REQUIREMENTS

3.1 Each type and size of brick shall meet the requirements of ASTM C7.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. The lot size and sample brick required for visual examination, dimensional characteristics, and test shall be in accordance with ASTM C7.

4.3 Test. Brick shall be tested in accordance with ASTM C7.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Unless otherwise specified, commercial packages are acceptable under this specification.

5.2 Packing. Unless otherwise specified, the subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate to the point of delivery.

5.3 Marking. Unless otherwise specified, shipping containers shall be marked with the name of the material, class, size and shape, and quantity contained therein as defined by the contract or order under which shipment is made, the name of the contractor and the number of the contract or order, and the gross weight.

6. NOTES

6.1 Intended use. Paving bricks covered by this specification are intended for use in the construction of pavements and floors.

6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.

(*b*) Type and size of brick desired (1.2.1).

(*c*) Packaging, packing, and marking if different from (5.1, 5.2, and 5.3).

6.3 Transportation description. The transportation descriptions and minimum weights applicable to this commodity are:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

Rail:

Brick, paving, not otherwise indexed by name.

Carload minimum weight 60,000 pounds.

Motor:

Brick, paving, not otherwise indexed by name.

Truckload minimum weight 60,000 pounds, subject to Rule 115, National Motor Freight Classification.

MILITARY INTERESTS:

Army—MO

Navy—Docks

Air Force—69

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.