SS-L-351B
April 23, 1973
SUPERSEDING
Int. Fed. Spec. SS-L-00351A
August, 1960 and
Fed. Spec. SS-L-351
October 14, 1930

FEDERAL SPECIFICATION

LIME: HYDRATED (FOR) STRUCTURAL PURPOSES

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers hydrated lime which is suitable for use in the scratch, brown and finish coats of plaster, for stucco, for mortar, and as an addition to portland-cement concrete.

1.2 Classification.

1.2.1 Types. This specification covers two types of hydrated lime:

Type F - Finishing hydrated lime, for use mainly in the finish coats of plaster, but may be used for any structural purpose.
Type M - For use for any structural purpose except the finish coats of plaster.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

UU-S-48 - Sacks, Shipping, Paper.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

C25 - Chemical Analysis of Limestone, Quicklime, and Hydrated Lime.
C50 - Sampling, Inspection, Packing, and Marking of Lime and Limestone Products.
C110 - Physical Testing of Quicklime and Hydrated Lime.
C206 - Special Finishing Hydrated Lime.
C207 - Hydrated Lime for Masonry Purposes.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

National Motor Freight Traffic Association Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material. Hydrated lime sold under this specification shall be a fine, white powder produced by the action of water on quicklime. It consists essentially of calcium hydroxide naturally associated with more or less magnesuim hydroxide.

3.2 Type F. Type F - Finishing hydrated lime shall be in accordance with ASTM C206 except for inspection, rejection, retesting, packing and marking (see 4.4.1 and 4.4.2).

3.3 Type M. Type M - Masons hydrated lime shall be in accordance with Type S, ASTM C207 except for inspection, rejection, retesting, packing and marking (see 4.4.1 and 4.4.2).

3.4 Workmanship.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection of materials and components. In accordance with 4.1, the supplier is responsible for insuring that materials used were manufactured, examined, and tested to the extent specified, in accordance with the requirements of referenced subsidiary specifications and standards, if any.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of each type of hydrated lime offered for delivery at the same time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

4.2.2 Sampling for visual examination. Sampling shall be in accordance with MIL-STD-105, Inspection Level S-3. The acceptable quality level (AQL) shall be 4.0 percent defective.

4.2.3 Sampling for chemical and physical tests. Samples obtained for visual examination shall be in accordance with methods specified in ASTM C50 and shall be used for testing.

4.3 Visual examination. Examine hydrated lime in accordance with table I.

TABLE I. Classification of defects

Defects
Lumps in lime.
Lime not dry.
Extraneous particules in lime.
Damage or defect not affecting function or serviceability.

4.4 Test methods.

4.4.1 Chemical analysis. Applicable chemical tests shall be in accordance with ASTM C25 (see 3.2 and 3.3).

4.4.2 Physical properties. Applicable physical property tests shall be in accordance with ASTM C110 (see 3.2 and 3.3).

4.5 Inspection of preparation for delivery. An inspection shall be made to determine that the packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps.
Contents	Quantity per container is more or less than required.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.1.1 Level A. Hydrated lime in quantities of 50 pounds shall be packed in bags conforming to UU-S-48, 8-8X, MB1.

5.1.2 Level B. Hydrated lime in quantities of 50 pounds shall be packed in bags conforming to UU-S-48, 4-4X, MB1.

5.1.3 Level C. Hydrated lime shall be packed to insure protection during shipment and safe delivery to destination in compliance with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.2 Marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with 5.2.1 or 5.2.2, as specified (see 6.2).

5.2.1 Military agencies. All marking shall be in accordance with MIL-STD-129.

5.2.2 Civil agencies. All marking shall be in accordance with Fed. Std. No. 123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use.

6.1.1 Type F. Finishing hydrated lime is intended for use in the scratch, brown, and finish coats of plaster, for stucco, for mortar, and as an addition to portland-cement concrete. It also constitutes an excellent masons lime.

6.1.2 Type M. Masons hydrated lime is intended for use in mortar, in the scratch and brown coats of plaster, for stucco, and for addition to portland-cement concrete. Frequently a good masons lime does not qualify as a satisfactory finishing lime.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type (see 1.2).
(c) Level of packaging, and level of packing required (see 5.1).
(d) Whether marking shall be as required for civil or military agencies (see 5.2).

Military Interest:

None

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activities:

COMMERCE - NBS
GSA - PCD
HEW - FEC
INTERIOR - BPA

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price - cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.