SS-P-371E
August 28, 1968
SUPERSEDING
Int. Fed. Spec. SS-P-00371D (GSA-FSS)
December 21, 1967 and
Fed. Spec. SS-P-371C
June 10, 1963

FEDERAL SPECIFICATION

PIPE, CONCRETE (NONREINFORCED, SEWER, STORM DRAIN, AND CULVERT)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers nonreinforced pipe used for the conveyance of sewage, industrial wastes, and storm water. This pipe is also used for the construction of culverts. For the purpose of this specification, the term pipe includes specials.

1.2 Classification.

1.2.1 Type. Pipe shall be of the following types, as specified (see 6.1):

Type I - Bell-and-spigot.
Type II - Tongue-and-groove.
Type III - Modified tongue-and-groove.

1.2.2 Class. Pipe shall be of the following classes, as specified (see 6.1):

Class 1 - Standard strength.
Class 2 - Extra strength.

1.2.3 Size. The sizes (internal diameter) shall be as follows for the three types and both classes of pipe (see 6.1):

4-inch	10-inch	18-inch
6-inch	12-inch	21-inch
8-inch	15-inch	24-inch

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 5630

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads, 40 Inch X 80 Inch, 4-Way Partial and 4-Way Pallets.

(Copies of specifications standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bids shall apply.

American Society for Testing and Materials (ASTM) Standards:

C 14 - Specification for Concrete Sewer, Storm Drain, and Culvert Pipe.
C 443 - Specification for Joints for Circular Concrete Sewer and Culvert Pipe, Using Flexible Watertight Rubber Gaskets.
C 497 - Method of Test for Determining Physical Properties of Concrete Pipe or Tile.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, Pa. 19103.)

Uniform Classification Committee:

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

National Classification Board:

National Motor Freight Classification Rules.

(Application for copies should be addressed to the National Classification Board., 1616 P Street, N. W., Washington, D. C. 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Each type and class of pipe shall meet the requirements of ASTM C 14, except for marking (see 4.3.1 and 4.3.2).

3.2 Rubber coupling gaskets. Rings shall conform to ASTM C 443 (see 4.3.3). When specified (see 6.1), a coupling ring shall be furnished with each section of pipe.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. Samples for visual examination, dimensional characteristics, and tests shall be in accordance with ASTM C 14 for pipe, and ASTM C 443 for gaskets.

4.3 Test methods.

4.3.1 Strength and absorption. Test for strength and absorption in accordance with ASTM C 497 (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

4.3.2 Permeability or hydrostatic test. Test for permeability, or as an alternate, the hydrostatic test in accordance with ASTM C 497 (see 3.1 and 6.1).

4.3.3 Gasket rings. Conduct test in accordance with ASTM C 443 (see 3.2).

4.4 Inspection of preparation for delivery. The packing and marking of pipe shall be inspected to determine conformance to the applicable requirements of section 5.

5. PREPARATION FOR DELIVERY

5.1 Packing.

5.1.1 Level A. Due to the availability of overseas production plants for concrete pipe, overseas shipment is not anticipated.

5.1.2 Level B and C. Concrete pipe shall be shipped loose and nested in accordance with Section No. 1 of the Association of American Railroads General Rules Governing the loading of Commodities on open top cars for rail shipment or in accordance with the National Mortor Freight Classification or Applicable exceptions thereto. When specified, concrete pipe may be shipped on pallets in accordance with MIL-STD-147.

5.2 Marking.

5.2.1 Civil agencies. In addition to any special marking specified in the contract or order, marking for shipment shall be in accordance with Fed. Std. No. 123.

5.2.2 Military agencies. In addition to any special marking required in the contract or order, marking for shipment shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and class of pipe (see 1.2.1 and 1.2.2).
(c) Size of pipe (see 1.2.3).
(d) Whether gaskets are required (see 3.2).
(e) Permeability test, or hydrostatic test (see 4.3.2).
(f) Selection of applicable level of packing required (see 5.1).

MILITARY INTERESTS:

Custodians:

Army - ME
AF - 84

User interest:

CE

Order for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price ents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.