SS-P-551C
December 22, 1971
SUPERSEDING
Fed. Spec. SS-P-551B

FEDERAL SPECIFICATION

PENCIL POINTER (ABRASIVE PAPER)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers pencil pointers for general office use.

1.2 Classification.

1.2.1 Types. Pencil pointers covered by this specification shall be of the following types, as specified (see 6.1).

Type I - Emery.
Type II - Flint.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of solicitation for offers or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.
PPP-F-320 - Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index; which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge from the Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established points in their agencies.)

Military Specifications:

MIL-C-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of solicitation for offers or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Preproduction sample. At the option of the contracting officer (see 6.1), before production is commenced, a sample pencil pointer covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Material.

3.2.1 Type I. Type I pencil pointers shall be made from medium grit closed coat emery paper.

3.2.2 Type II. Type II pencil pointers shall be made from fine grit closed coat flint paper.

3.2.3 Holders. Holders for Types I and II pointers shall be made of wood, or at the option of the manufacturers the holders may be made from solid fiberboard. The holders shall conform to workmanship requirements (see 3.4).

3.3 Construction.

3.3.1 Pencil pointers. Type I and II pointers shall be furnished in pads of 12 sheets of abrasive paper glued to a machine finished wooden holder or a holder made from solid fiberboard.

3.3.1.1 Pads. Types I and II pads shall consist of 12 individual sheets, not less than 1-1/4 inches wide by not less than 4 inches long, sufficiently glued along their edges to form a pad from which successive sheets may be removed without destroying the underlying sheets.

3.3.1.2 Holders. Types I and II holders shall conform to the following minimum dimensions:

Length	7 inches
Width	1-1/4 inches
Thickness	1/8 inch

The holders shall be smoothly finished in all edges and surfaces. The holders shall be shaped for use as a handle, for a minimum length of 2-1/2 inches from one end; and shall be drilled with a hole not less than 1/4 inch in diameter. The center of the holder shall be located 1 inch $\pm$ 1/4 inch from the shaped end.

3.3.1.3 Assembly. For wood holders, the non-abrasive surface of the pad shall be glued to good wrapping paper and the pad completely wrapped. The wrapped pad shall then be securely glued to the unshaped portion of the wood holder, with the non-abrasive surface toward the holder. The sides and end of the glued pads shall be parallel to and equidistant from the sides and end of the unshaped portion of the holder. If solid fiberboard is used for the holder, the grit paper shall be glued to the fiberboard. The grit paper shall be glued entirely along one edge, and along the opposite edge to approximately one inch from the end of the unshaped portion of the holder. Completed assembly of all pencil pointers shall result in the abrasive surfaces of all sheets in the pad facing away from the holder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. Wooden or solid fiberboard holders shall be machined to a smooth finish and shall be free from defects which affect their appearance or which might impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

4.2 Preproduction sample inspection. When required by the contracting officer, a preproduction sample shall be examined in accordance with 4.4.

4.3 Component and material inspection. In accordance with 4.1, the supplier is responsible for insuring that components and materials used are manufactured, tested and inspected to insure conformance with the requirements of this specification.

4.4 End item inspection. Examination of the end item shall be in accordance with the classification of defects, inspection level and acceptable quality level set forth below. The lot size for the purpose of determining the sample size shall be all pencil pointers of the same type submitted for inspection and delivery at one time. The sample unit for this inspection shall be one pencil pointer.

4.4.1 Visual examination. Visual examination of the end item shall be in accordance with the classification of defects in table I. Sampling shall be in accordance with MIL-STD-105. The inspection level shall be II with an Acceptable Quality Level (AQL) of 6.5 defects per hundred units.

TABLE I. Visual examination

Examine	Defects
Design	Not as specified.
Dimensions	Not as specified.
Sheet Count	Less than 12 sheets per pad.
Material	
Holder	Not wood or solid fiberboard.
Abrasive Paper Pads	
Type I	Not closed coat emery paper.
Type II	Not closed coat flint paper.
Assembly	Pad not fastened to holder so that abrasive surfaces of all sheets in the pad face away from holder.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.1).

5.1.1 Level A. The pencil pointers shall be packaged in close-fitting boxes conforming to PPP-B-566, PPP-B-665, or PPP-B-676. The boxes shall be closed in accordance with the closure requirements of the box specification. Each box shall be waterproofed in accordance with MIL-P-116, Method IC-2.

5.1.2 Level B. Twelve pencil pointers, of one type only, shall be packaged as specified in 5.1.1, except that waterproofing of boxes shall not be required.

5.1.3 Level C. The pencil pointers shall be packaged in accordance with the manufacturer's standard practice, providing that this insures protection for the pencil pointers during shipment and provides for safe delivery to their destination. When fiberboard is utilized, it shall conform to PPP-F-320.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 Level A. The pencil pointers shall be packed in a close-fitting fiberboard box conforming to PPP-B-636, class weather resistant. Each box shall be closed and sealed in accordance with the appendix to the box specification.

5.2.2 Level B. Twenty-four packages of 12 pencil pointers each shall be packed in a close-fitting fiberboard box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The pencil pointers, packaged as specified in 5.1.3, shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification rules and the National Motor Freight Classification rules. When fiberboard is utilized, it shall conform to PPP-F-320.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 4.3.2 as specified (see 6.1).

5.3.1 Civil agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following in procurement documents:

(a) Title, number, and date of this specification.
(b) When preproduction sample is required (3.1).
(c) Type required.
(d) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

☆U. S. GOVERNMENT PRINTING OFFICE : 1972 O - 482-192 (3277)

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.