SS-S-445A
June 13, 1974
SUPERSEDING
Fed. Spec. SS-S-445
August 12, 1966

FEDERAL SPECIFICATION

SLAG, STONE, AND GRAVEL, CRUSHED (FOR BITUMINOUS PAVING MIXTURES)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers crushed slag, stone, and gravel, used in the construction and maintenance of various types of highways.

1.2 Classification. The material shall be of the following types, classes, and sizes as specified (see 6.2).

1.2.1 Types and classes:

Type I - Slag.

Class A - For bituminous paving mixtures.
Class B - For dry-bound or waterbound macadam base courses.
Class C - For single bituminous surface treatment.
Class D - For bituminous-macadam base and surface courses.

Type II - Stone.

Class A - For bituminous paving mixtures.
Class B - For dry-bound or waterbound macadam base courses.
Class C - For single bituminous surface treatment.
Class D - For bituminous-macadam base and surface courses.

Type III - Gravel.

Class A - For bituminous paving mixture.
Class B - For dry-bound or waterbound macadam base courses.
Class C - For single bituminous surface treatment.

1.2.2 Sizes. Sizes for slag, stone and gravel shall be in accordance with ASTM D 448 as specified (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

FSC 5610

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications: The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

D 75 - Sampling Aggregates, Method of.
D 448 - Standard Sizes of Coarse Aggregate for Highway Construction.
D 692 - Coarse Aggregate for Bituminous Paving Mixtures.
D 693 - Crushed Stone, Crushed Slag, and Crushed Gravel for Bituminous Macadam Base and Surface Course of Pavements.
D 694 - Crushed Stone, Crushed Slag and Crushed Gravel for Dry-Bound or Water-Bound Macadam Base Courses.
D 1139 - Crushed Stone, Crushed Slag and Gravel for Single or Multiple Bituminous Surface Treatments.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Type I, II and III, Class A. Crushed slag, stone and gravel used as coarse aggregate for bituminous paving mixtures shall conform to requirements to ASTM D 692, when tested in accordance with 4.4.2.

3.1.2 Types I, II and III, Class B. Crushed slag, stone and gravel used for dry-bound or water-bound macadam course shall conform to the requirements of ASTM D 694, when tested in accordance with 4.4.3.

3.1.3 Types I, II and III, Class C. Crushed slag, crushed stone and gravel used for single or multiple bituminous surface treatments shall conform to the requirements of ASTM D 1139, when tested in accordance with 4.4.4.

3.1.4 Types I and II, Class D. Crushed slag and stone used for bituminous macadam base and surface course of pavements shall conform to the requirements of ASTM D 693, when tested in accordance with 4.4.5.

3.2 Grading size. Crushed slag, stone or gravel shall be as uniform in size as practicable when tested in accordance with 4.4.6 and conform to grading shown in ASTM D 448 for the specified nominal size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of 250 tons of all of the same type, class, and size offered for delivery at the same time.

4.2.2 Visual examination and tests. Sampling for examination and tests shall be in accordance with ASTM D 75.

4.3 Visual examination. Examination of the end item shall be in accordance with table I. The Acceptable Quality Level (AQL's) in MIL-STD-105 shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

TABLE I. Classification of defects, end item

End item	Major	Minor
Type and class not as specified.....	X	
Dirt or other objectionable matter present.....	X	
Not free of an excess of thin or elongated pieces.....	X	
Not free of soft or disintegrated pieces.....		X

4.4 Tests.

4.4.1 Acceptance. The AQL shall be 6.5 percent defective in accordance with MIL-STD-105.

4.4.2 Types I, II, and III, class A. Tests for these types and class shall be as referenced in ASTM D 692 (see 3.1.1).

4.4.3 Types I, II, and III, class B. Tests for these types and class shall be as referenced in ASTM D 694 (see 3.1.2).

4.4.4 Types I, II, and III, class C. Tests for these types and class shall be as referenced in ASTM D 1139 (see 3.1.3).

4.4.5 Types I and II, class D. Tests for these types and class shall be as referenced in ASTM D 693 (see 3.1.4).

5. PREPARATION FOR DELIVERY

5.1 The product shall be prepared for shipment and loaded on rail, truck or other approved means of transportation, to insure safe delivery at destination in accordance with the Uniform Freight Classification Rules or National Motor Freight Classification Rules.

6. NOTES

6.1 Intended use.

6.1.1 Types I, II and III, Class A. Crushed slag, stone and gravel are suitable for use as coarse aggregate in bituminous paving mixtures.

6.1.2 Types I, II and III, Class B. Crushed slag, stone and gravel are suitable for use in the construction of dry bound or waterbound macadam courses.

6.1.3 Types I, II and III, Class C. Crushed slag, stone and gravel are suitable for use as aggregate in single or multiple bituminous surface treatment.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:13Z
Check the source to verify that this is the currentversion before use.

6.1.4 Types I and II, Class D. Crushed slag and stone are suitable for use in the construction of bituminous macadam base and surface courses.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and class (see 1.2.1).
(c) Size required (see 1.2.2).
(d) Size of lot, if different (see 4.2.1).

Military Coordinating Activity:

Navy - YD

User activity:

Army - ME, CE

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activities:

AGRICULTURE - AFS
COMMERCE - NBS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:13Z
Check the source to verify that this is the current version before use.