MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, LOGIC FUNCTION RESISTORS

1. SCOPE

1.1 This specification covers the detail requirements for one type of circuit card assembly. The requirements of this specification together with the general requirements of MIL-C-60898 comprise the complete requirements for the Logic Function Resistors Circuit Card Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-C-60898	Circuit Card Assemblies, General Specification for

DRAWINGS

U. S. Army, Frankford Arsenal

F10554163	Electronic Component Assembly, Logic Function Resistors

PACKAGING DATA SHEET

10554163	Packaging of Circuit Card Assembly, Logic Function Resistors

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 4931

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Fabrication. The assembly shall be manufactured in accordance with Drawing F10554163 and drawings pretaining thereto.

3.2 General specification. The assembly shall meet the requirements of MIL-C-60898.

3.3 Environmental service conditions. See MIL-L-60898.

3.3.1 Resistance value at temperature extremes. For the conditions of 3.3.2 of MIL-C-60898, there shall be a resistance of 1 kilohm, (± 10 percent) between pin 13 and the following pins: 9, 10, 11, 12, 16, 17, 18, 19, 20, 21, 22, 23, 26, and 27. There shall be a resistance of 75 kilohms, (± 12 percent) between pin 2 and pin 4.

3.4 Electrical Performance

3.4.1 Resistance value. There shall be resistance of 1 kilohm, (± 5 percent) between pin 13 and the following pins: 9, 10, 11, 12, 16, 17, 18, 19, 20, 21, 22, 23, 26, and 27. There shall be a resistance of 75 kilohms, (± 5 percent) between pin 2 and pin 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 General. The quality assurance provisions of MIL-C-60898 shall apply to the assembly covered by this detail specification.

4.2 First article inspection. As specified in MIL-C-60898.

4.3 Control test sample. As specified In MIL-C-60898.

4.4 Functional tests. The following characteristics shall be 100 percent tested in accordance with MIL-C-60898.

	Characteristic	Requirement	Procedure
100	Resistance value	3.4.1	4.5.2.1

4.4.1 Inspection equipment. As specified in MIL-C-60898 and below in 4.4.1.1.

4.4.1.1 Test equipment. In conjunction with 4.4.1, the following test equipment shall be utilized in the performance of the applicable tests as specified in 4.5.

Item	Description
1. OHMMETER	Capable of measuring d-c resistance to ± 0.-5 percent accuracy and resolution at O to 100 kilohms.

4.5 Test methods and procedures

4.5.1 Environmental. As specified in MIL-C-60898 except the requirements of 3.3. 1 herein shall be verified during temperature extremes.

4.5.2 Electrical test

4.5.2.1 Resistance value. Connect the OHMMETER (item 1 of 4.4.1.1) between pin 13 and the following pins: 9, 10, 11, 12, 16, 17, 18, 19, 20, 21, 22, 23, 26, 27; then between pin 2 and pin 4. The resistance values shall conform to 3.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with Packaging Data Sheet 10554163.

6, NOTES

6,1 The notes specified in MIL-C-60898 are applicable to this specification.

Custodian:

Army - MU

Preparing Activity:

Army - MU

project No. 4931-A040

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS. This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

YES NO *(If "yes", in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.