INCH-POUND

MIL-C-70618A (AR)
AMENDMENT 1

1 December 1992

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, GUNFIRE SIMULATOR: 12725086

This amendment forms a part of MIL-C-70618A (AR), dated 17 October 1988, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

3.3.4.1: Delete "...60 to 75 seconds..." and replace with "...60 to 120 seconds..." (2 places)

PAGE 7

3.4.3: Delete "3.4.3 in it's entirety and substitute the following:

"3.4.3 Vibration. The CCA shall meet the requirements of 3.3 after being subjected to MIL-STD-810, Method 514, Procedure I-3.3.1 for one hour of random vibration along the vertical axis. Testing shall be conducted in a fixture which duplicates the CCA mounting configuration when installed in the GUFS end application device."

PAGE 14

4.7.3.3: Delete "4.7.3.3 in it's entirety and substitute the following:

"4.7.3.3 Vibration. The device shall be tested in accordance with MIL-STD-810, Method 514, Procedure I-3.3.1, using figure 514.4-1 for one hour of random vibration along the vertical axis. After completion of the vibration test, the device shall be functionally tested three times as specified in 4.7.1 herein to determine compliance with 3.4.3."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 6920-A115)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.