INCH-POUND

MIL-C-63990C (AR)
AMENDMENT 1
15 August 1994

MILITARY SPECIFICATION

CARTRIDGE; 5.56mm, TRACER, M856

This Amendment forms a part of Military Specification MIL-C-63990C, dated 15 February 1994, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Under drawings add the following:

"9349659 - Jacket
9357840 - Jacket, Pointed With Filler, Point"

PAGE 8

4.4.1 Add the following:

"Jacket, Pointed	9357839	25
Jacket, Pointed With Filler, Point	9357840	25"

PAGE 9

Table I delete "Sheet 1 of 4" and substitute "Sheet 1 of 6"

Delete "wall thickness variation (2 locations) " and substitute "wall thickness variation"

PAGE 10

Table I delete "Sheet 2 of 4" and substitute "Sheet 2 of 6"

Add Sheet 3 of 6 included as Page 3 (10a)

Add sheet 4 of 6 included as page 4 (10b)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Jacket, Pointed	3 OF 6	9357839
			NEXT HIGHER ASSEMBLY 9342866

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Wall thickness over cylindrical length of jacket (.024)	25, 0-1	3.2	SMTE
	Wall thickness at tapered portion of jacket (.016 min.)	25, 0-1	3.2	SMTE
	Evidence of poor workmanship	25, 0-1	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Jacket, Pointed With Filler, Point	4 OF 6	9357840
			NEXT HIGHER ASSEMBLY 9342866

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Length, tracer cavity (.430)	25, 0-1	3.2	SMTE
	Evidence of poor workmanship	25, 0-1	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.