INCH-POUND

MIL-P-63397A (AR)
AMENDMENT 3
21 July 1994
SUPERSEDING
AMENDMENT 2
03 April 1992

MILITARY SPECIFICATION

PROJECTILE, 155MM: INERT PXR 6325 (M549 SIM) METAL PARTS, ASSEMBLY

This amendment forms a part of Military Specification MIL-P-63397A (AR), dated 11 January 1985, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 SPECIFICATIONS, MILITARY

Delete:

"MIL-S-10520 - Steel, Forging, For Projectile Stock
MIL-S-11310 - Steel Bars, Carbon, Hot Rolled, In Cold Shaping Including Cold Extrusion"

And substitute:

"MIL-S-70703 - Strand Cast Steel, Carbon & Alloy, For Projectile Applications"

PAGE 2

2.1.1 Drawings: Delete drawing "9236063 - Projectile, 155MM: Inert PXR 6325 (M549 SIM)" in its entirety.

Delete drawing "9362569 - Packing and Marking...Projectile, 155MM" in its entirety and substitute the following:

"8837839 - Pallet for Projectile, 155MM, HE & GB, Hollow Base Type"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

PAGE 3

3.2, line 7: Delete "MIL-S-10520 or MIL-S-11310" and substitute "MIL-S-70703".

3.3 Delete in its entirety and substitute the following:

"3.3 Heat treatment. Heat treatment applied to any component part shall be uniform throughout and shall be so conducted as to produce in each component the mechanical properties specified on the applicable drawings."

3.3.2 Delete in its entirety.

PAGE 4

3.5.2, lines 4 and 5: Delete "there shall be no evidence of arc cratering at any location on the base metal when it is machined to 5.850 inch diameter." and substitute the following:

"There shall be no evidence of arc cratering at any location of the base metal when it is machined to 5.800 inches diameter."

3.5.4, lines 7 and 8: Delete "All indications including those in the starting weld zone must be removed when machined to the 5.850 inch diameters." and substitute the following:

"All indications including those in the starting weld zone must be removed when machined to the 5.800 inch diameters."

PAGE 6

4.3.1, line 8: To metal Parts Assembly for, 155MM, Drawing No. 9236061; delete Quantity of: "5" and substitute Quantity to "15".

4.3.1, line 9: Delete the following in its entirety:

"Projectile, 155MM: Inert PXR 6325 (M549 SIM); 9236063; 10".

PAGE 7

Table I - First article inspection: Add the following to Metal Parts Assembly for, 155MM; Inert PXR 6325 (M549 SIM):
"Proving ground test 10 - 3.7 4.4.3.5/4.5.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

Delete the following in its entirety:

"Projectile, 155MM; Inert PXR 6325
(M549 SIM)
(Dwg. 9236063)
Proving ground test 10 - 3.7 4.5.4".

PAGE 8

4.4.1 Delete paragraphs 4.4.1.b, 4.4.1.c and 4.4.1.d in their entirety and substitute the following:

"c. Miscellaneous lots. Small lots (such as bodies manufactured from abnormally small heats of steel or bodies that have become separated from previously delivered lots, etc.) may at the discretion of the supplier be grouped into miscellaneous heat treatment lots. Such lots shall be identified by a miscellaneous lot code number and processed in accordance with (a) above. The miscellaneous lot thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

d. Projectile lots. When it has been determined that bodies of a heat treated lot have complied with the mechanical properties requirement of the applicable drawing, they may be grouped for further processing."

PAGE 14

4.4.2.3: Delete Major defect "103, Salt spray test, Note a, 3.1, 4.4.3.4.1, 4.5.3" in its entirety.

4.4.2.3: Add Minor defect "210, Salt spray test, Note a, 3.1, 4.4.3.5.1, 4.5.3"

(Note, salt spray test is changed from a Major to a Minor defect.)

PAGE 15

4.4.2.4 Block, Drawing Number: Delete "9362569" and substitute "8837839".

4.4.2.4 Major 103, delete: "or staple".

4.4.2.4 Minor 203, delete: "or staple".

PAGE 16

4.4.3 Delete in its entirety and substitute the following:
"4.4.3 Testing."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4.3.2.1.1: Delete in its entirety and substitute the following:

"4.4.3.2.1.1 Heat treatment lots. In order to determine uniformity of heat treatment, each body in the heat treatment lot (as defined by 4.4.1a) after heat treatment, but prior to final machining shall be subjected to a hardness test with a Brinell Hardness Tester or any other method approved by the procuring activity. Hardness impressions shall be made on the outside surfaces at the band seat location or at any other area on the body deemed necessary for process control and used as the basis for selecting the tension test samples of 4.4.3.2.2.1."

4.4.3.2.1.2 Delete paragraph 4.4.3.2.1.2 in its entirety.

4.4.3.2.1.3 Delete paragraph 4.4.3.2.1.3 in its entirety and substitute the following:

"4.4.3.2.1.3 Miscellaneous lots. Miscellaneous heat treatment lots shall be subjected to a hardness test in accordance with 4.4.3.2.1.1."

PAGE 17

4.4.3.2.2.2 Delete paragraph 4.4.3.2.2.2 in its entirety.

4.4.3.2.2.3 Delete paragraph 4.4.3.2.2.3 in its entirety and substitute the following:

"4.4.3.2.2.3 Miscellaneous lots. Samples for tension test of miscellaneous heat treatment lots shall be selected in accordance with 4.4.3.2.2.1. Failure of any tension test specimen to comply with the yield strength or elongation requirements of the applicable drawings shall be cause for rejection of the lot. Tension tests shall be performed on each miscellaneous heat of steel before being grouped into a miscellaneous lot."

PAGE 19

4.4.3.3.3.3, lines 3 and 4: Delete "The band seat shall be machined to a minimum diameter of 5.850 inches." and substitute the following:

"The band seat shall be machined to a minimum diameter of 5.800 inches."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

PAGE 21

4.5.1.1 a, line 2: Delete the words "grinding to a sufficient depth" and substitute the following: "grinding a flat to a sufficient depth".

4.5.1.1 d, line 5: Delete "300kg" and substitute "3000kg".

4.5.1.2, line 2: Delete the following: "or stress relief".

4.5.1.2, line 16: Delete "Persent" and substitute "Percent."

PAGE 22

4.5.4, lines 4 and 5: Delete "shall be loaded and assembled as specified on Dwg. 9236063 and fired" and substitute the following:

"shall be inert loaded as specified on the applicable projectile loading drawing, to one weight zone that falls within the weight specified, on loading drawing. The loaded projectile shall then be dummy fuzed and fired."

4.5.4, line 6: Delete "M185 or M199 series cannon using a PXR-6297 proof charge" and substitute "M284 or M199 series cannon using a PXR-6297A1 stick proof charge".

PAGE 23

5.1, 5.2 Delete "9362569" and substitute "8837839".

6.3 Delete lines 3 and 4: Delete "US Army Armament Munitions and Chemical Center, ATTN: DRSMC-QAR-I (D), Dover, New Jersey 07801" and substitute the following: "US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-QAR-I, Picatinny Arsenal, New Jersey 07806-5000."

6.6, line 10: Change "sequecne" to "sequence".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AD19)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.