This documentation process conversion measures necessary to comply with this revision shall be completed by 29 January 2000.

INCH-POUND

MIL-PRF-19500/157M
12 November 1999
SUPERSEDING
MIL-PRF-19500/157L
1 July 1998

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE-REFERENCE TYPES
1N941B, 1N941B-1, 1N943B, 1N943B-1, 1N944B, 1N944B-1, 1N945B, 1N945B-1,
1N946B, 1N946B-1, 1N941BUR-1, 1N943BUR-1, 1N944BUR-1,
1N945BUR-1, AND 1N946BUR-1 JAN, JANTX, JANTXV, JANJ, AND JANS;
RADIATION HARDENED (TOTAL DOSE ONLY)
JANTXVM, D, L, R, F, G, H, AND JANSM, D, L, R, F, G, AND H

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for 11.70 volts ± 5 percent, silicon, voltage-reference diodes. Five levels of product assurance are provided for each encapsulated device type as specified in MIL-PRF-19500. Seven levels of radiation hardened (total dose only) product assurance are provided for each encapsulated device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (similar to DO-7 and DO-35) and figure 2 (similar to DO-213AA).

1.3 Maximum ratings. Unless otherwise specified, maximum ratings (T_A = +25°C).

P_T	T_{STG} and T_{op}	I_{ZM} 1/	Power derating above T_A = +25°C
mW	°C	mA dc	mW/°C
500	-55 to +175	39	3.33

1/ To guarantee voltage stability, it is necessary to maintain the proper I_Z = 7.5 mA dc.

1.4 Primary electrical characteristics. Unless otherwise specified, primary electrical characteristics at T_A = +25°C.

Type	ΔV_Z (voltage - temperature stability I_Z = 7.5 mA dc	Z_Z I_Z = 7.5 mA dc	V_Z I_Z = 7.5 mA dc		I_R V_R = 8.0 V
			Min	Max	
	mV dc	ohms	volts	volts	µA
1N941B, 1N941B-1, 1N941BUR-1	239.0	30	11.12	12.28	15.0
1N943B, 1N943B-1, 1N943BUR-1	47.0	30	11.12	12.28	15.0
1N944B, 1N944B-1, 1N944BUR-1	24.0	30	11.12	12.28	15.0
1N945B, 1N945B-1, 1N945BUR-1	12.0	30	11.12	12.28	15.0
1N946B, 1N946B-1, 1N946BUR-1	4.7	30	11.12	12.28	15.0

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Supply Center Columbus, ATTN: DSCC-VAC, 3990 East Broad St., Columbus, OH 43216-5000, by using the addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

DEPARTMENT OF DEFENSE

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Defense Automated Printing Service, 700 Robbins Avenue, Building 4D (DPM-DODSSP), Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. Devices furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified products list before contract award (see 4.2 and 6.6).

3.2 Associated specification. The individual item requirements shall be in accordance with MIL-PRF-19500 and as specified herein.

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be specified in MIL-PRF-19500 and figures 1, and 2 herein.

3.4.1 Lead finish. Unless otherwise specified, lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein.

3.5 Diode construction. These devices shall be constructed in a manner and using material which enable the diodes to meet the applicable requirements of MIL-PRF-19500 and this document.

3.5.1 Dash-one construction. Shall be as specified in MIL-PRF-19500.

3.5.2 JANS construction. Construction shall be dash-one, category I or II metallurgical bond in accordance with MIL-PRF-19500.


3.6 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.6.1 Marking of "UR" version devices. For "UR" version devices only, all marking (except polarity) may be omitted from the body, but shall be retained on the initial container.

3.7 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4 and table I herein.

3.8 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
BD	.060	.107	1.52	2.72	3
BL	.120	.300	3.05	7.62	3
LD	.018	.023	0.46	0.58	
LL	1.000	1.500	25.40	38.10	
LL_1	- - -	0.050	- - -	1.27	4

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Package contour optional within BD and length BL. Heat slugs, if any, shall be included within this cylinder but shall not be subject to minimum limit of BD.
4. Within this zone, lead diameter may vary to allow for lead finishes and irregularities, other than heat slugs.

FIGURE 1. Physical dimensions, 1N941B, 1N943B, through 1N946B, 1N941B-1, 1N943B-1, through 1N946B-1 (similar to DO-35 and DO-7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
BD	.063	.067	1.60	1.70
ECT	.016	.022	0.41	0.56
BL	.130	.146	3.30	3.70
S	.001 min		0.03 min	

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 2. Physical dimensions, 1N941BUR-1, 1N943BUR-1 through 1N946BUR-1 (similar to DO-213AA).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4).

4.1.1 Sampling inspection. Sampling inspection shall be in accordance with MIL-PRF-19500 and as specified herein, except that lot accumulation period shall be 3 months in lieu of 6 weeks.

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 Group E inspection. Group E inspection shall be conducted in accordance with MIL-PRF-19500, and paragraph 4.4.5 herein.

4.2.2 JANJ devices. For JANJ level, 3.3.1 through 3.3.1.3 of MIL-PRF-19500 shall apply, except as modified herein. Supplier imposed requirements as well as alternate screens, procedures, and/or controls shall be documented in the QM plan and must be submitted to the Qualifying Activity for approval. When alternate screens procedures, and/or process controls are used in lieu of the JANJ screens herein equivalency shall be proven and documented in the QM Plan. Radiation characterization may be submitted in the QM plan at the option of the manufacturer, however, paragraph 3.3.1.1 of MIL-PRF-19500 is not required. Die lot controls and rework requirements shall be in accordance with MIL-PRF-19500 paragraphs 3.13 and D.3.13.2.1 for JANS level. Lot formation and conformance Inspection requirements for JANJ shall be those used for JANTXV devices as a minimum.

4.2.3 JANJ Qualification. For JANJ qualification, 4.4.2.1 herein shall be performed as required by the Qualifying Activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

4.3 Screening (JANS, JANJ, JANTXV and JANTX levels only). Screening shall be in accordance with MIL-PRF-19500 (Appendix E, table IV), and as specified herein. Specified electrical measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see appendix E, table IV of MIL-PRF-19500)	JANS Level	JANJ Level	JANTXV and JANTX Level
1a 1b	Required Required	Not Required Required	Not Required Required (JANTXV only)
2	Not Required	Not Required	Not Required
3a 3b 3c	Required Not Applicable Not Applicable	Required Not Applicable Not Applicable	Required Not Applicable Not Applicable
4	Not Applicable	Not Applicable	Not Applicable
5	Not Applicable	Not Applicable	Not Applicable
6	Not Applicable	Not Applicable	Not Applicable
7a 7b	Not Applicable Required	Not Applicable Required	Not Applicable Required
8	Required	Not Required	Not Required
9	Not Applicable	Not Applicable	Not Applicable
10	Not Applicable	Not Applicable	Not Applicable
11	Required V_Z, Z_Z	Required V_Z, Z_Z	Required V_Z, Z_Z
12	Required See 4.3.1	Required T = 240 hours See 4.3.1	Required See 4.3.1
13	Required Subgroups 2 and 3 of table I herein, $\Delta Z_Z \leq \pm 15$ percent of initial reading. At T_A = +25°C, $\Delta V_Z \leq \pm$ 0.008 V dc from initial value for 1N941B, 1N941B-1, 1N941BUR-1, 1N943B, 1N943B-1, 1N943BUR-1. $\Delta V_Z \leq \pm$ 0.006 V dc from initial value for 1N944B, 1N944B-1, 1N944BUR-1, 1N945B, 1N945B-1, and 1N945BUR-1. $\Delta V_Z \leq \pm$ 0.003 V dc from initial value for 1N946B, 1N946B-1, and 1N946BUR-1.	Required Subgroups 2 and 3 of table I herein, $\Delta Z_Z \leq \pm 15$ percent of initial reading. At T_A = +25°C, $\Delta V_Z \leq \pm$ 0.008 V dc from initial value for 1N941B, 1N941B-1, 1N941BUR-1, 1N943B, 1N943B-1, 1N943BUR-1. $\Delta V_Z \leq \pm$ 0.006 V dc from initial value for 1N944B, 1N944B-1, 1N944BUR-1, 1N945B, 1N945B-1, and 1N945BUR-1. $\Delta V_Z \leq \pm$ 0.003 V dc from initial value for 1N946B, 1N946B-1, and 1N946BUR-1.	Required Subgroup 2 of table I herein, $\Delta Z_Z \leq \pm 15$ percent of initial reading. At T_A = +25°C, $\Delta V_Z \leq \pm$ 0.008 V dc from initial value for 1N941B, 1N941B-1, 1N941BUR-1, 1N943B, 1N943B-1, 1N943BUR-1. $\Delta V_Z \leq \pm$ 0.006 V dc from initial value for 1N944B, 1N944B-1, 1N944BUR-1, 1N945B, 1N945B-1, and 1N945BUR-1. $\Delta V_Z \leq \pm$ 0.003 V dc from initial value for 1N946B, 1N946B-1, and 1N946BUR-1.
14a 14b	Not Applicable Optional 1/	Not Applicable Optional 1/	Not Applicable Optional 1/
15	Required	Required Attributes Data only Film or Non-Film Techniques may be utilized	Not Required
16	Required	Required	Not Required
17	Not Required	Required Subgroup 2 of table I herein Verify polarity	Not Required

1/ Per MIL-PRF-19500

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows:

I_Z = 7.5 mA dc, +0.75 mA dc, -0 mA dc, T_A = 150°C +5°C, -0°C.

To better utilize burn-in equipment, higher values of I_Z shall be permitted provided the junction temperature does not exceed +175°C.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with appendix E, table V of MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIa (JANS) and table VIb (JAN, JANTX, JANTXV, and JANJ) of MIL-PRF-19500. Electrical measurements (endpoints) shall be in accordance with the applicable steps of table I, subgroup 2 herein.

4.4.2.1 Group B inspection, table VIa (JANS) of MIL-PRF-19500. For purposes of JANS inspection, a single device type shall be defined as devices from a single wafer lot (for each die type used in the construction). The conformance inspection sample shall be selected from the part category with the lowest ΔV_Z rating in the inspection lot.

Subgroup	Method	Conditions
B1	2066	
B2	2026 1022	
B3	1056 4066 1071 2075	Test Condition A, 25 Cycles Not applicable Test condition E.
B4	1037	I_Z = 19.5 mA dc at T_A = +25°C; t_{on} = t_{off} = 30 seconds minimum for 4,000 cycles. Forced air cooling allow during off cycle.
B5	1027	I_{ZM} = 39 mA dc for 96 hours. T_A = +75°C or adjusted as required, to give an average lot T_J = +200°C.
B6		Not applicable

4.4.2.2 Group B inspection, appendix E, table VIb (JAN, JANTX, JANTXV, and JANJ) of MIL-PRF-19500.

Subgroup	Method	Conditions
B1	2026 1022	
B2	1056 4066 1071	Test Condition A, 25 Cycles Not applicable Test condition E
B3	1027	(See 4.3.1)
B4	2075	
B5		Not applicable
B6		Not applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table VII of MIL-PRF-19500. Electrical measurements (end points) shall be in accordance with the applicable steps of table I, subgroup 2 herein.

4.4.3.1 Group C inspection, appendix E, table VII of MIL-PRF-19500.

Subgroup	Method	Conditions
C1	2066	
C2	1056 2036 1071 1021	Lead fatigue: Test condition E; tension: test condition A; 4 pounds weight, t = 15 ±3 seconds; (lead fatigue and tension tests are not applicable to surface mount "UR" version devices). Condition E Omit initial conditioning
C3		Not applicable
C4	1041	
C5		Not applicable
C6	1026	I_Z = 7.5 mA dc, T_A = +100°C.(see 4.5.2)
C7		Not applicable

4.4.4 Group D inspection. Group D inspection shall be conducted in accordance with appendix E, table VIII of MIL-PRF-19500. MIL-PRF-19500, appendix F is not required when homogeneous product of radiation hard assembly (in accordance with applicable 36D form) is submitted and successfully passes group D sampling of total dose at an outside facility compliant to MIL-STD-750, method 1019. Submitted lots for group D sample inspection must be constructed using one homogeneous wafer lot for the zener and one wafer lot for the compensating die, as also described in the submitted 36D forms.

4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup tests in appendix E, table IX of MIL-PRF-19500. Electrical measurements (end-points) requirements shall be in accordance with the applicable steps of table I, subgroup 2 herein.

4.4.5.1 Group E inspection, appendix E, table IX of MIL-PRF-19500.

Subgroup	Method	Conditions	Sample Plan
E1	1051	500 cycles	22 devices, c = 0.
E2	1038	Condition B, 1,000 hours (see 4.3.1)	22 devices, c = 0.
E3		Not applicable	
E4		Not applicable	
E5		Not applicable	
E6		Not applicable	

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables as follows.

4.5.1 Voltage-temperature stability. The breakdown voltage of each diode type shall be measured and recorded at each of the specified temperatures. The lowest measured voltage shall be subtracted from the highest measured voltage for each diode. The difference value obtained shall not exceed the specified ΔV_Z per diode type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

4.5.2 Reference voltage time stability. The breakdown voltage shall be measured prior to life testing, at 340 hours, and at the conclusion of the life test as shown in table below. The 340-hour reading shall be compared with the 0-hour reading and the 1,000-hour reading compared with the 340-hour reading. The change in breakdown voltage shall not exceed the limits specified. The test temperature for breakdown voltage shall be the same as specified ambient life test temperature.

Inspection	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Reference-voltage time stability		T_A = +100°C ± 2°C (see 4.5.2 and 4.5.3) I_Z = 7.5 ± 0.01 mA dc	ΔV_Z			
1N941B, 1N941B-1, 1N941BUR-1		(0 to 340 hours)			7	mV dc
1N943B, 1N943B-1, 1N943BUR-1					7	mV dc
1N944B, 1N944B-1, 1N944BUR-1					6	mV dc
1N945B, 1N945B-1, 1N945BUR-1					5	mV dc
1N946B, 1N946B-1, 1N946BUR-1					4	mV dc
1N941B, 1N941B-1, 1N941BUR-1		(340 to 1,000 hours)			4	mV dc
1N943B, 1N943B-1, 1N943BUR-1					4	mV dc
1N944B, 1N944B-1, 1N944BUR-1					3	mV dc
1N945B, 1N945B-1, 1N945BUR-1					3	mV dc
1N946B, 1N946B-1, 1N946BUR-1					2	mV dc

4.5.3 Reference voltage. The test current shall be applied until thermal equilibrium is attained (15 seconds maximum) prior to reading the reference voltage. For this test, the diode shall be suspended by its leads with mounting clips whose inside edge is located between .375 inch (9.53 mm) and .500 inch (12.70 mm) from the body and the mounting clips shall be maintained at the specified temperature. This measurement may be performed after a shorter time following application of the test current than that which provides thermal equilibrium if correlation to stabilized readings can be established to the satisfaction of the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Reference voltage (see 4.5.3)	4022	I_Z = 7.5 ±0.01 mA dc	V_Z	11.12	12.28	V dc
Small-signal breakdown impedance	4051	I_Z = 7.5 ±0.1 mA dc, I_{sig} = 0.75 mA ac	Z_Z		30	Ω
Subgroup 3						
Voltage-temperature stability (see 4.5.1 and 4.5.3)		I_Z = 7.5 ± 0.01 mA dc, T_A = -55°C, ± 0°C, +25°C, +75°C, +150°C ± 2°C	ΔV_Z			
1N941B, 1N941B-1, 1N941BUR-1					239.0	mV dc
1N943B, 1N943B-1, 1N943BUR-1					47.0	mV dc
1N944B, 1N944B-1, 1N944BUR-1					24.0	mV dc
1N945B, 1N945B-1, 1N945BUR-1					12.0	mV dc
1N946B, 1N946B-1, 1N946BUR-1					4.7	mV dc
Subgroups 4, 5, and 6						
Not applicable						
Subgroup 7						
Reverse current leakage	4016	DC Method; V_R = 8.0 V dc	I_R		15	µA

1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection.

Inspection 1/	MIL-STD-750		Symbol	Pre-irradiation limits		Post-irradiation limits		ΔV_{Z1} pre-post irradiation change		Unit
	Method	Conditions		M, D, R, L, F, G, and H		M, D, R, L, F, G, and H				
				Min	Max	Min	Max	Min	Max	
Subgroup 1										
Not applicable										
Subgroup 2		T_C = +25°C								
Steady-state total dose irradiation	1019	I_Z = 7.5 ± 0.01 mA dc, condition A								
Reference voltage (see 4.5.3)	4022	I_Z = 7.5 ± 0.01 mA dc	V_Z	11.12	12.28	11.12	12.28			V dc
Small-signal breakdown impedance	4051	I_Z = 7.5 ± 0.01 mA dc I_{sig} = 0.75 ac	Z_Z		30		30			ohms
Reverse current leakage	4016	DC method; V_R = 8.0 V dc	I_R		15.0		15.0			µA
Voltage stability (4.5.3)	4022	I_Z = 7.5 ± 0.01 mA dc, T_A = +25°C, ± 2°C	ΔV_Z							
1N941B, 1N941B-1 1N941BUR-1									± 5.0	mV
1N943B, 1N943B-1 1N943BUR-1									± 4.0	mV
1N944B, 1N944B-1 1N944BUR-1									± 3.0	mV
1N945B, 1N945B-1 1N945BUR-1									± 2.0	mV
1N946B, 1N946B-1 1N946BUR-1									± 1.5	mV

1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Departments' or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Issue of DODISS to be cited in the solicitation.

b. Lead finish as specified (see 3.4.1).

c. Product assurance level and type designator.

6.3 Substitution of radiation hardened devices. See MIL-PRF-19500.

6.4 Substitution of devices. Device types within this series with higher type numbers (lower ΔV_Z voltage-temperature stability) are a direct oneway substitution for lower type numbers (higher ΔV_Z voltage-temperature stability).

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

6.6 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List QML 19500 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center Columbus, ATTN: DSCC-VQE, 3990 East Broad Street, Columbus, OH 43216-5000.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, SM
Navy - AS, CG, MC
Air Force - 19, 80, 99

Preparing activity:
DLA - CC

(Project 5961-2093)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-19500/157M	2. DOCUMENT DATE

3. **DOCUMENT TITLE** SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE-REFERENCE TYPES 1N941B, 1N943B, 1N944B, 1N945B, 1N946B, 1N941B-1, 1N943B-1, 1N944B-1, 1N945B-1, 1N946B-1, 1N941BUR-1, 1N943BUR-1, 1N944BUR-1, 1N945BUR-1, AND 1N946BUR-1, JAN, JANTX, JANTXV, JANJ, AND JANS; RADIATION HARDENED (TOTAL DOSE ONLY) JANTXVM, D, L, R, F, G, H, AND JANSM, D, L, R, F, G, AND H

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) COMMERCIAL DSN FAX EMAIL	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. Point of Contact Alan Barone	b. TELEPHONE Commercial: 614-692-0510 DSN: 850-0510 FAX: 614-692-6939 EMAIL: alan_barone@dscc.dla.mil
c. ADDRESS Defense Supply Center Columbus ATTN: DSCC-VAC Columbus, OH 43216-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman, Suite 2533, Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-6888

DD Form 1426, Feb 1999 (EG) Previous editions are obsolete WHS/DIOR, Feb 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.