The documentation and process conversion measures necessary to comply with this amendment shall be completed by 24 May 2000.

INCH-POUND

MIL-PRF-19500/157M
AMENDMENT 1
24 February, 2000

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE-REFERENCE
TYPES, 1N941B, 1N941B-1, 1N943B, 1N943B-1, 1N944B, 1N944B-1, 1N945B, 1N945B-1,
1N946B, 1N946B-1, 1N941BUR-1, 1N943BUR-1, 1N944BUR-1,
1N945BUR-1, AND 1N946BUR-1 JAN, JANTX, JANTXV, JANJ, AND JANS;
RADIATION HARDENED (TOTAL DOSE ONLY)
JANTXVM, D, L, R, F, G, H, AND JANSM, D, L, R, F, G, AND H

This amendment forms a part of MIL-PRF-19500/157M, dated 12 November 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

4.4.3.1, subgroup C2, conditions column, delete and substitute:

"C2 1056

2036	Lead tension: Test condition A; 4 pounds weight, t = 15 ±3 seconds. Lead fatigue: Test condition E (lead tension and fatigue tests are not applicable to surface mount “UR” version device).
1071	Condition E.
1021	Omit initial conditioning. "

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, SM
Navy - AS, CG, MC
Air Force - 19, 80, 99

Preparing activity:
DLA - CC

(Project 5961-2270-01)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:25Z
Check the source to verify that this is the current version before use.