The documentation and process conversion measures necessary to comply with this amendment shall be completed by 24 May 2000.

INCH-POUND

MIL-PRF-19500/158M
AMENDMENT 1
24 February, 2000

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE-REFERENCE
TYPES 1N3154-1,through 1N3157-1, AND 1N3154UR-1, through 1N3157UR-1
JAN, JANTX, JANTXV, JANJ, AND JANS; RADIATION HARDENED (TOTAL DOSE ONLY)
JANTXVM, D, L, R, F, G, H, AND JANSM, D, L, R, F, G, H

This amendment forms a part of MIL-PRF-19500/158M, dated 19 November 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

4.4.3.1, subgroup C2, conditions column, delete and substitute:

"C2	1056	
	2036	Lead tension: Test condition Test condition A; 4 pounds weight, t = 15 ±3 seconds. Lead fatigue: Test condition E (lead tension and fatigue tests are not applicable to surface mount "UR" version device).
	1071	Condition E.
	1021	Omit initial conditioning. "

4.4.3.1. C6, delete in conditions column "Conditions for " B-1, and BUR-1" versions of:" only.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, SM
Navy - AS, CG, MC
Air Force - 19, 80, 99

Preparing activity:
DLA - CC

(Project 5961-2270-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:26Z
Check the source to verify that this is the current version before use.