INCH-POUND
MIL-R-26F
AMENDMENT 2
3 October 1994
SUPERSEDING
AMENDMENT 1
26 April 1994

MILITARY SPECIFICATION

RESISTORS, FIXED, WIRE-WOUND (POWER TYPE)
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-R-26F, dated 16 November 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

TABLE I, Group IV, delete "Shock, medium impact" and substitute "Shock, specified pulse".

PAGE 11

* 4.5.1.3.1, delete and substitute:

"4.5.1.3.1 Sampling plan. A sample of 13 parts shall then be randomly selected, if one or more defects are found, the lot shall be rescreened and defects removed. A new sample of 13 parts shall then be randomly selected, if one or more defects are found in the second sample, the lot shall be rejected and shall not be supplied to this specification."

* TABLE V, delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:20Z
Check the source to verify that this is the current version before use.

TABLE VI, delete and substitute:

"TABLE VI. Group C inspection. 1/

Inspection	Number of sample units to be inspected	Requirement paragraph	Method paragraph	Number of defects allowed
Monthly				
Resistance-temperature characteristics	10	3.11	4.6.7	1
Dielectric withstanding voltage		3.12	4.6.8	
Insulation resistance		3.13	4.6.9	
High-temperature exposure		3.14	4.6.10	
Moisture resistance 2/		3.15	4.6.11	
Low-temperature storage		3.16	4.6.12	
Mechanical strength		3.17	4.6.13	
Quarterly Subgroup 1				
Terminal strength	10	3.10	4.6.6	1
Subgroup 2				
Life	10	3.20	4.6.16	1
Semiannually (Applicable to axial-lead resistors only)				
Shock, specified pulse	10	3.18	4.6.14	1
Vibration, high frequency		3.19	4.6.15	

1/ If the manufacturer can demonstrate that the tests from this table have been performed for five consecutive times with zero failures, the frequency of these tests, with the approval of the qualifying activity, can be performed on an annual basis. If the design, material, construction, or processing of the part is changed, or if there are any quality problems or failures, the qualifying activity may require resumption of the original test frequency.

2/ The ten samples shall be evenly divided into two groups of five each, and one group shall be subjected to polarization, and the other group to loading."

PAGE 14

4.6.1a., delete and substitute:

"a. Measuring apparatus: Different type of measuring test equipment (multimeters, bridges, or equivalent) are permitted to be used on the initial and final readings of this test, provided the equipment is the same style, model, or if it can be shown that the performance of the equipment is equivalent or better."

PAGE 18

4.6.14, line two, delete "205" and substitute "213".

* 4.6.14c., delete and substitute:

"c. Test condition letter I."

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:20Z
Check the source to verify that this is the current version before use.

* TABLE IX, delete and substitute:

"TABLE IX. Performance characteristics - Continued.

Style		RW55	RW56	RW67	RW68	RW69	RW70	RW74	RW78	RW79	RW80	RW81
Maximum resistance Temperature characteristic in parts/million/°C PPM (Ref to 25°C)	20 ≤ R ohms	±260	±260	±260	±260	±260						
	20 > R ohms	±400	±400	±400	±400	±400						
	20 ≤ R ohms						±20	±20	±30	±30	±30	±30
	10 ≤ R < 20 ohms						±30	±30	±50	±50	±50	±50
	1 ≤ R < 10 ohms						±50	±50	±90	±90	±90	±90
	.499 ≤ R < 1 ohm						+400 -100	+400 -100	+400 -100	+400 -100	+400 -100	+400 -100
	.1 ≤ R < .499 ohm						+650 -100	+650 -100	+650 -100	+650 -100	+650 -100	+650 -100
Maximum ambient temperature at rated wattage (see 3.1)		25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C	25°C
Maximum ambient temperature at zero wattage derating (see 3.1)		350°C	350°C	350°C	350°C	350°C	275°C	275°C	275°C	275°C	275°C	275°C
Power rating in watts		7	14	6.5	11	3	1	5	10	3	2	1
Maximum percent change in resistance 1/	Thermal shock (see 3.7)	2	2	2	2	2	.2	.2	.2	.2	.2	.2
	Short time overload (see 3.8)	2	2	2	2	2	.2	.2	.2	.2	.2	.2
	Terminal strength (see 3.10)	1	1	1	1	1	.1	.1	.1	.1	.1	.1
	Dielectric withstanding voltage (see 3.12)	.1	.1	.1	.1	.1	.1	.1	.1	.1	.1	.1
	High temperature exposure (see 3.14)	2	2	2	2	2	.5	.5	.5	.5	.5	.5
	Moisture resistance (see 3.15)	2	2	2	2	2	.2	.2	.2	.2	.2	.2
	Low temperature storage (see 3.16)	2	2	2	2	2	.2	.2	.2	.2	.2	.2
	Shock-medium impact (see 3.18)	.2	.2	.2	.2	.2	.1	.1	.1	.1	.1	.1
	Vibration, high frequency (see 3.19)	.2	.2	.2	.2	.2	.1	.1	.1	.1	.1	.1
	Life (see 3.20)	3	3	3	3	3	.5	.5	.5	.5	.5	.5
	Resistance tolerance ±percent	see 3.1	see 3.1	see 3.1	see 3.1	see 3.1	±.1 .5 1.0	±.1 .5 1.0	±.1 .5 1.0	±.1 .5 1.0	±.1 .5 1.0	±.1 .5 1.0

1/ Total resistance change shall be considered as ±(_____ percent +0.05 ohm).

2/ Not to be used for new design. For replacement purposes only."

Source: https://assist.dla.mil -- Downloaded: 20260-15T17:20Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, AV, ME, MI
Navy - AS, MC, OS
Air Force - 17, 19, 99
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1397)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:20Z
Check the source to verify that this is the current version before use.