NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-26/3C
AMENDMENT 1
6 May 1983

PERFORMANCE SPECIFICATION

RESISTORS, FIXED, WIRE-WOUND (POWER TYPE), STYLES RW29, RW301/, RW31, RW321/, RW33, RW341/, RW35, RW361/,RW37, RW38, RW391/, AND RW47

This amendment forms a part of Military Specification MIL-R-26/3C, 1 June 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TABLE I, delete and substitute:

"TABLE I. Characteristics.

Symbol	Method of winding	Maximum continuous operating temperature	Minimum insulation resistance at end of moisture resistance	Resistance temperature characteristic PPM/°C
		°C	Megohms	0 ±260 20 ohms and above
				0 ±400 10 ohms up to but not including 20 ohms
V - - -	Inductive	350	100	+400 0 -200 1 ohm up to but not including 10 ohms
N - - -	Non-inductive			+500 0 -100 .499 ohm up to but not including 1 ohm
				+650 0 -100 .1 ohm up to but not including .499 ohm

1/ This temperature is also the maximum permissible hot-spot surface temperature."

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.

PAGE 4

TABLE III, delete and substitute:

"TABLE III. Minimum and maximum nominal resistance value.

Resistor style	Resistance value				
	Minimum	Maximum			
		Characteristic V	Characteristic N	Characteristic V	Characteristic K
	ohm	ohms 1/	ohms 1/	ohms 2/	ohms 2/
RW29	0.10	5,600	2,700	30,000	3,000
RW30 3/	0.10	2,700	---	- - -	- - -
RW31	0.10	6,800	3,300	27,000	3,000
RW32 3/	0.10	10,000	---	- - -	- - -
RW33	0.10	18,000	8,100	74,500	8,000
RW34 3/	0.10	30,000	---	- - -	- - -
RW35	0.10	43,000	20,000	172,000	19,000
RW36 3/	0.10	56,000	---	- - -	- - -
RW37	0.10	91,000	43,000	405,000	45,000
RW38	0.10	0.15 megohm	75,000	565,000	74,000
RW39 3/	0.10	.20 megohm	---	- - -	- - -
RW47	0.10	.18 megohm	81,000	760,000	85,000

1/ Based on the use of 0.00175-inch nominal diameter wire.
2/ Based on the use of 0.001-inch nominal diameter wire.
3/ Not to be used for new design. For replacement purposes only."

PAGE 6

Concluding material: Delete and substitute as printed in this amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI, AR
Navy - AS, OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5905-1008-3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.