NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-26/4D
AMENDMENT 1
6 May 1983

PERFORMANCE SPECIFICATION

RESISTORS, FIXED, WIRE-WOUND (POWER TYPE),
STYLES RW55, RW56, RW67, RW68, and RW69

This amendment forms a part of Military Specification MIL-R-26/4D, 6 May 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TABLE I, delete and substitute:

"TABLE I. Characteristics.

Symbol	Maximum continuous operating temperature 1/	Minimum insulation resistance at end of moisture resistance	Resistance temperature characteristic PPM/°C
	°C	Megohms	
V - - -	350	100	0 ±260 20 ohms and above
			0 ±400 10 ohms up to but not including 20 ohms
			+400 0 -200 1 ohm up to but not including 10 ohms
			+500 0 -100 .499 ohm up to but not including 1 ohm
			+650 0 -100 .1 ohm up to but not including .499 ohm

1/ This temperature is also the maximum permissible hot-spot surface temperature."

Concluding material: Delete and substitute as printed in this amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Preparing activity:
Army - ER

Review activities:
Army - MI, AR
Navy - AS, OS
Air Force - 11, 17, 99
DLA - ES

(Project 5905-1008-4

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Agent:
DLA - ES

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.