INCH-POUND
MIL-PRF-26/4F
w/Amendment 1
18 November 2010
SUPERSEDING
MIL-PRF-26/4F
15 September 2006

PERFORMANCE SPECIFICATION SHEET

RESISTOR, FIXED, WIRE-WOUND (POWER TYPE), STYLES RW55, RW56, RW67, RW68, and RW69

ALL STYLES, EXCEPT RW56, ARE INACTIVE FOR NEW DESIGN


This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-26.

1. SCOPE

1.1 Scope. This specification covers the associated requirements for styles RW55, RW56, RW67, RW68, and RW69, wirewound inductive resistors.

1.2 Part or Identifying Number (PIN). Resistors covered by this specification are identified by a PIN that consists of the style designation, characteristic, and coded resistive value. The PIN is derived in accordance with MIL-PRF-26 and is in the following form:



1.2.1 Style. The style is identified by the two-letter symbol "RW" followed by a two-digit number.

1.2.2 Characteristic. The characteristic is identified by a single letter that identifies the maximum continuous operating temperature (surface hot spot), the minimum insulation resistance value at the end of the moisture resistance test, and the resistance temperature characteristic in accordance with table I.

1.2.3 Resistance. The nominal resistance expressed in ohms is identified by a three-digit number: The first two digits represent significant figures and the last digit specifies the number of zeroes to follow. When resistance values less than 10 ohms are required, the letter "R" is substituted for one of the significant digits to represent the decimal point. When the letter "R" is used, succeeding digits of the group represent significant figures as shown in the following example.

R47 = 0.47 ohm
4R7 = 4.7 ohm

Comments, suggestions, or questions on this document should be addressed to: DLA Land and Maritime, ATTN: VAT, Post Office Box 3990, Columbus, Ohio 43218-3990 or by email Resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil/.

AMSC N/A FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.

Minimum and maximum resistance values are as specified herein. The standard values for every decade should follow the sequence demonstrated for the "10 to 100" decade in accordance with MIL-PRF-26.

TABLE I. Characteristic.

Symbol	Maximum continuous operation temperature 1/	Minimum insulation resistance at end of moisture resistance	Resistance temperature characteristic (ppm/^{O}C)
V 2/	350°C	100 Megohms	0 ±260 ≥20 ohms
			0 ±400 ≥10 ohms to <20 ohms
			0 +400, -200 ≥1 ohm to <10 ohms
			0 +500, -100 ≥0.499 ohm to <1 ohm
			0 +650, -100 ≥0.1 ohm to < 0.499 ohm

1/ This temperature is also the maximum permissible hot-spot surface temperature.
2/ Inductive wirewound.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract (see 6.2).

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-26 - Resistors, Fixed, Wire Wound (Power Type), General Specification for.

(Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094).


2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence unless otherwise noted. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-26.

3.2 Interface and physical dimension. The resistor shall meet the interface and physical dimensions specified on figure 1 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.



	RW55	RW56	RW67	RW68	RW69
A	1.375 ±.094	2.0 ±.094	1.0 ±.094	1.875 +.063, -.125	.500 ±.063
B	.469 ±.094	.469 ±.094	.313 ±.063	.344 ±.094	.188 ±.063

Inch	mm	Inch	mm	Inch	mm	Inch	mm
.006	.15	.125	3.18	.375	9.53	1.375	34.93
.036	.91	.188	4.78	.469	11.91	1.750	44.45
.063	1.60	.313	7.95	.500	12.70	1.875	47.63
.094	2.39	.344	8.74	1.000	25.40	2.000	50.80

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. These styles shall be untapped.
4. The end of the resistor body is the point where the diameter reduces to 0.06 inch.

FIGURE 1. Styles RW55, RW56, RW67, RW68, and RW69.

3.3 Power rating. The power rating shall be as specified in table II, based on full load operation at an ambient temperature of 25°C.

TABLE II. Power rating.

Resistor style	Power rating in watts Characteristic V
RW55	7
RW56	14
RW67	6.5

Resistor style	Power rating in watts Characteristic V
RW68	11
RW69	3

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.

3.4. Resistance. The minimum and maximum nominal resistance values shall be as specified in table III.

TABLE III. Minimum and maximum nominal resistance values.

Resistor style	Resistance value (kohms)	
	Minimum	Maximum
RW55	0.10	5.1
RW56		9.1
RW67		8.2
RW68		20.0
RW69		2.0

3.4.1 Standard resistance values. For standard resistance values see MIL-PRF-26.

3.5 Resistance tolerance. These resistors have a resistance range of 0.10 ohms to 20 kohms with the following resistance tolerances:

a. Resistors of less than 1 ohm in resistance value shall have a tolerance of ±10 percent of the nominal resistance value.

b. Resistors of 1 ohm and over in resistance value shall have a tolerance of ±5 percent of the nominal resistance value.

3.6 Thermal shock. The resistors shall not change in resistance in excess of ±(2 percent +0.05 ohm).

3.7 Short-time overload. The resistors shall not change in resistance in excess of ±(2 percent +0.05 ohm).

3.8 High-temperature exposure. The resistors shall not change in resistance in excess of ±(2 percent +0.05 ohm).

3.9 Moisture resistance. The resistors shall not change in resistance in excess of ±(2 percent +0.05 ohm).

3.10 Low-temperature storage. The resistors shall not change in resistance in excess of ±(2 percent +0.05 ohm).

3.11 Life. The resistors shall not change in resistance in excess of ±(3 percent +0.05 ohm).

3.12 Solderability. Solderability is applicable to this specification.

3.13 Terminal strength. The resistors shall not change in excess of ±(1 percent +.05 ohm).

3.14 Dielectric withstanding voltage (barometric pressure, reduced, not applicable). The resistors shall not change in resistance in excess of ±(.1 percent +0.05 ohm).

3.15 Shock (medium impact). The resistors shall not change in resistance in excess of ±(.2 percent +.05 ohm).

3.16 Vibration (high frequency). The resistors shall not change in resistance in excess of ±(.2 percent +.05 ohm).

3.17 Pure tin. The use of pure tin, as an underplate or final finish is prohibited both internally and externally. Tin content of resistor components and solder shall not exceed 97 percent, by mass. Tin shall be alloyed with a minimum of 3 percent lead, by mass (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.

4. VERIFICATION.

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-26.

4.2 Barometric pressure (reduced). The magnitude of test voltage shall be 300 volts rms at 100,000 feet for styles RW55, RW56, RW67, and RW68. For style RW69, the test voltage shall be 200 volts rms at 100,000 feet.

4.3 Short-time overload. The short time overload shall be 5 times rated wattage for 5 seconds for style RW69, and 10 times rated wattage for 5 seconds for styles RW55, RW56, RW67, and RW68.

5. PACKAGING.

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Service or Defense Agency, or within the military services system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity

6. NOTES.

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-PRF-26 are applicable to this specification.

6.2 Acquisition requirements. Acquisition requirements are as specified in MIL-PRF-26.

a. Title, number, and date of this specification, and the complete PIN (see 1.2).

b. Unless otherwise specified (see 2.1), the versions of the individual documents referenced will be those in effect on the date of release of the solicitation.

c. Packaging instructions (see 5.1).

6.3 Derating. Resistors shall be derated, when necessary, in accordance with figure 2.




FIGURE 2. Derating curve for high ambient temperatures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.

6.4 Tin whisker growth. The use of alloys with tin content greater than 97 percent, by mass, may exhibit tin whisker growth problems after manufacture. Tin whiskers may occur anytime from a day to years after manufacture and can develop under typical operating conditions, on products that use such materials. Conformal coatings applied over top of a whisker-prone surface will not prevent the formation of tin whiskers. Alloys of 3 percent lead, by mass, have shown to inhibit the growth of tin whiskers. For additional information on this matter, refer to ASTM-B545 (Standard Specification for Electrodeposited Coatings of Tin).

6.5 Amendment notations. The margins of this specification are marked with vertical lines to indicate modification generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5905-2011-004)

Review activities:
Army - MI
Navy - AS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:21Z
Check the source to verify that this is the current version before use.