INCH-POUND
MIL-R-26/6D
w/ Amendment 1
12 March 2008
SUPERSEDING
MIL-R-26/6D
15 September 2006

MILITARY SPECIFICATION

RESISTOR, FIXED, WIRE WOUND (POWER TYPE), STYLES RW80 and RW81

Inactive for new design after 11 May 1973.
For new design use MIL-PRF-39007. (See 6.4)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the associated requirements for styles RW80 and RW81, wirewound inductive resistors.

1.2 Part or Identifying Number (PIN). Resistors covered by this specification are identified by a PIN, which consists of the style designation, characteristic, and coded resistive value. The PIN is derived in accordance with MIL-PRF-26 and is in the following form:

RW80	U	49R9	F
Style (1.2.1)	Characteristic (1.2.2)	Resistance (1.2.3)	Resistance tolerance (1.2.4)

1.2.1 Style. The style is identified by the two-letter symbol "RW" followed by a two-digit number.

1.2.2 Characteristic. The characteristic is identified by a single letter that identifies the maximum continuous operating temperature (surface hot spot), the minimum insulation resistance value at the end of the moisture resistance test, and the resistance temperature characteristic in accordance with table I.

1.2.3 Resistance. The nominal resistance expressed in ohms is identified by a four-digit number; the first three digits represent significant figures and the last digit specifies the number of zeroes to follow. When resistance values less than 100 ohms are required, the letter "R" is substituted for one of the significant digits to represent the decimal point. When the letter "R" is used, succeeding digits of the group represent significant figures as shown in the following example.

R100 = 0.1 ohm
1R00 = 1.0 ohm
10R0 = 10.0 ohm

Comments, suggestions, or questions on this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC VAT, Post Office Box 3990, Columbus, Ohio 43218-3990 or by email Resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/ .

AMSC N/A FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.

Minimum and maximum resistance values are as specified herein. The standard values for every decade should follow the sequence demonstrated for the "10 to 100" decade in accordance with MIL-PRF-26.

* TABLE I. Characteristic.

Symbol	Maximum continuous operation temperature 1/	Minimum insulation resistance at end of moisture resistance	Resistance temperature characteristic (ppm/^{O}C)
U 2/	275°C	100 Megohms	0 ±30 ≥ 10 ohms
			0 ±50 ≥ 1 ohm to < 10 ohms
			0 +400, -100 ≥ 0.499 ohm to <1 ohm
			0 +650, -100 ≥ 0.1 ohm to < 0.499 ohm

1/ This temperature is also the maximum permissible hot-spot surface temperature.
2/ Inductive wirewound.

1.2.3.1 Replacement or maintenance (applicable to .1 and .5 percent tolerances). It is preferred that resistance values be selected as specified in MIL-PRF-26. However, if it is impracticable to do so, then any value (within specification limits) may be specified and these values shall be considered as conforming to the specification.

1.2.4 Resistance tolerance The resistance tolerance is identified by a single letter in accordance with table II.

* TABLE II. Resistance tolerance.

Symbol	Resistance tolerance percent (±%)
B	0.1
D	0.5
F	1.0

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract (see 6.2).

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-26 - Resistors, Fixed, Wire Wound (Power Type), General Specification for.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence, unless otherwise noted. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-26.

3.2 Interface and physical dimension. The resistor shall meet the interface and physical dimensions specified on figure 1 and as specified herein.

3.3 Power rating and maximum voltage. The power rating and maximum continuous voltage (dc or rms, ac) shall be in accordance with table III. The power rating shall be based on full-load operation at an ambient temperature of 25°C.

TABLE III. Power rating and maximum voltage.

Resistor style	Power rating in watts (Characteristic U)	Maximum continuous working voltage (volts)
RW80	2	80
RW81	1	33


3.4 Resistance. The minimum and maximum nominal resistance values shall be as specified in table IV.

3.4.1 Standard resistance values. For standard resistance values see MIL-PRF-26.

TABLE IV. Minimum and maximum nominal resistance values.

Resistor Style	Resistance value (ohms)	
	Minimum	Maximum
RW80	0.10	3,160
RW81	0.10	1,000

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.



	RW80	RW81
A	.406 ±.031	.250 ±.031
B	.094 ±.031	.085 ±.020
D	.020 ±.0015	.020 ±.0015

Inch	mm	Inch	mm	Inch	mm
.0015	.04	.085	2.16	.375	9.53
.020	.51	.094	2.39	.406	10.31
.031	.79	.250	6.35	1.750	44.45

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. These styles shall be untapped.
4. The end of the resistor body is the point where the diameter reduces to 0.06 inch.

FIGURE 1. Styles RW80 and RW81.

3.5 Thermal shock. The resistors shall not change in resistance in excess of ±(0.2 percent +0.05 ohm).

3.6 Short-time overload. The resistors shall not change in resistance in excess of ±(0.2 percent +0.05 ohm).

3.7 High-temperature exposure. The resistors shall not change in resistance in excess of ±(0.5 percent +0.05 ohm).

3.8 Moisture resistance. The resistors shall not change in resistance in excess of ±(0.2 percent +0.05 ohm).

3.9 Low-temperature storage. The resistors shall not change in resistance in excess of ±(0.2 percent +0.05 ohm).

3.10 Life. The resistors shall not change in resistance in excess of ±(0.5 percent +0.05 ohm).

3.11 Solderability. Solderability is applicable to this specification.

3.12 Shock (medium impact). The resistors shall not change in resistance in excess of ±(0.1 percent +.05 ohm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.

3.13 Vibration (high frequency). The resistors shall not change in resistance in excess of ±(0.1 percent +.05 ohm).

3.14 Terminal strength. The resistors shall not change in excess of ±(0.1 percent +.05 ohm).

3.15 Dielectric withstanding voltage (barometric pressure, reduced, not applicable). The resistors shall not change in resistance in excess of ±(0.1 percent +0.05 ohm).

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-26.

4.2 Short-time overload. The maximum voltages shall be 5 times rated wattage for 5 seconds; however, in no case shall the voltage exceed the values specified in table V.

TABLE V. Maximum voltages for short-time overload.

Resistor style	RW80	RW81
Voltage (volts maximum)	300	150

4.3 Barometric pressure (reduced). The magnitude of test voltage shall be 100 volts rms at 100,000 feet.

4.4 Terminal strength The applied force shall be 5 pounds.

5. PACKAGING.

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Service or Defense Agency, or within the military services system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-PRF-26 are applicable to this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition requirements are as specified in MIL-PRF-26.

a. Title, number, and date of this specification, and the complete PIN (see 1.2).

b. If not otherwise specified (see 2.1), the versions of the individual documents referenced will be those in effect on the date of release of the solicitation.

c. Packaging instructions (see 5.1).

6.3 Derating. Resistors shall be derated, when necessary, in accordance with figure 2.




FIGURE 2. Derating curve for high ambient temperatures.

6.4 Substitution data. The resistors specified herein are not for use in new design. They are authorized for use in design contracts effective prior to or on 11 May 1973 and to support existing military equipment. Resistors of MIL-PRF-39007 are preferred for new design and can be used as substitutes for the inactivated resistors as follows:

MIL-R-26/6 (style)	MIL-PRF-39007 Specification sheet	Substitute style	Resistance tolerance
RW80	MIL-PRF-39007/8	RWR80	B, D, and F
RW81	MIL-PRF-39007/9	RWR81	B, D, and F

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.

* 6.5 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5905-2007-067)

Review activities:
Army - MI
Navy - AS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:22Z
Check the source to verify that this is the current version before use.