MILITARY SPECIFICATION

RESISTORS, FIXED, WIRE-WOUND (POWER TYPE)
STYLES RW10, RW11, RW12, RW13, RW14, RW15, AND RW16

This amendment forms a part of Military Specification MIL-R-26/1A, 11 July 1967, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I, delete and substitute:

"TABLE I. Characteristic.

Symbol	Maximum continuous operating temperature 1/	Minimum insulation resistance at end of moisture resistance	Resistance temperature characteristic PPM/°C
	°C	Megohms	
V - - -	350	100	0 ±260 20 ohms and above
			0 ±400 10 ohms up to but not including 20 ohms
			+400 0 -200 1 ohm up to but not including 10 ohms
			+500 0 -100 .499 ohm up to but not including 1 ohm
			+650 0 -100 .1 ohm up to but not including .499 ohm

1/ This temperature is also the maximum permissible hot-spot surface temperature."

PAGE 7

Concluding material: Delete and substitute as printed in this amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI, AR
Navy - SH, AS, OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 14, 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5905-1008-1)

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:20Z
Check the source to verify that this is the current version before use.