MILITARY SPECIFICATION

TAPE, GLASS-SETTING: RUBBER, UNCUFED
(FOP SEALING GLASS WINDOWS)

This amendment forms a part of Military Specification MIL-T-46114B, dated 3 August 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Para 2.2, line 6: Add "Low-Voltage" before "Rubber".

Para 2.2, line 7: Delete document title and substitute: "Rubber Properties in Tension".

Para 2.2, line 9. Delete document title and substitute: "Rubber Property - Durometer Hardness".

After contents of para 2.2, add the following paragraph:

"2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence."

PAGE 3

Para 3.1, sentence 1: Delete from "uncured" to end of sentence and substitute "one of the following:

a. Uncured natural rubber and cotton fiber.
b. Synthetic rubber and cotton fiber.
c. Uncured natural and synthetic rubbers and cotton fiber."

PAGE 4

Para 3.8, sentence 1: Delete "(not to exceed 100°F)" and substitute: ", not to exceed 37.8°C (100°F),".

Custodians:
Army - MR
Navy - YD
Air Force - 99

Preparing activity:
Army - MR

Project No. 9320-0429

Review activities:
Army - MD
Air Force - 82
DLA - GS

User activities
Army - AT

/ FSC 9320 /

U S GOVERNMENT PRINTING OFFICE 1983 — 605 034/4058

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:54Z
Check the source to verify that this is the current version before use.