INCH-POUND
MIL-PRF-8805/65C
3 September 1999
SUPERSEDING
MIL-S-8805/65B
20 March 1992

PERFORMANCE SPECIFICATION SHEET

SWITCHES, SENSITIVE, DPDT, PLUNGER, 5 AMPERES, RESILIENT SEAL

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-8805.



FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:13Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.003	0.08	.375	9.53
.004	0.10	.470	11.94
.025	0.64	.650	16.51
.030	0.76	.750	19.05
.031	0.79	.812	20.62
.038	0.97	1.030	26.16
.047	1.19	1.125	28.58
.050	1.27	1.220	30.99
.072	1.83	1.380	35.05
.110	2.79	3.580	90.93
.150	3.81	3.700	93.38
.250	6.35		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.02 (0.51 mm) for two place decimals and ±.005 (0.13 mm) for three place decimals.
4. Switch configuration optional provided dimensions specified are not exceeded.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:13Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Enclosure design: Four (resilient). All entrances to the switch cavity except through the actuator bushing shall be sealed by fusion of glass-to-metal, metal-to-metal, or ceramic-to-metal.

Temperature characteristic: 1 (-55°C to +85°C).

Shock type: H (High-impact). There shall be no opening of closed contacts in excess of 8 milliseconds.

Vibration grade: 2(10 Hz to 2,000 Hz).

Weight: 0.60 pound maximum.

Operating characteristics:

Actuating force: 6 to 12 pounds.

Pretravel: 0.040 inch maximum.

Movement differential: 0.020 inch maximum.

Overtravel: 0.250 inch minimum.

Finish: Switch housing shall be processed to resist corrosion.

Contact resistance: 0.5 ohms maximum measured with a 5 ampere test current and a 28 V dc test voltage.

Dielectric withstanding voltage: Sea level (1,000 V rms).

Seal test: Only watertight test shall be performed in group A.

Mechanical endurance: 25,000 cycles.

Electrical endurance: 25,000 cycles.

Electrical ratings: See table I.

Marking: The circuit schematic shall be permanently and legibly marked on the switch case.

Part or Identifying Number (PIN): M8805/65-001.

TABLE I. Electrical ratings.

Load	Sea level 28 V dc
	amperes
Resistive	5
Inductive	3
Motor	4

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:13Z
Check the source to verify that this is the current version before use.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army – CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, AV, MI
Navy - AS,. MC, SH
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5930-1691-022)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:13Z
Check the source to verify that this is the current version before use.