INCH-POUND
MIL-PRF-8805/72J
31 May 2001
SUPERSEDING
MIL-S-8805/72H
12 May 1995

PERFORMANCE SPECIFICATION SHEET

SWITCHES, SENSITIVE, SPDT, PLUNGER, 4 AMPERES, HERMETICALLY SEALED CONTACTS, UNSEALED PLUNGER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-8805





FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:14Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm
.042	1.067	.265	6.731	.390	9.906
.052	1.321	.295	7.493	.410	10.414
.060	1.524	.300	7.620	.535	13.589
.188	4.775	.312	7.924	.565	14.351
.190	4.826	.350	8.890	1.15	29.21
.210	5.334	.370	9.398	71.00	1803.4
.213	5.410	.380	9.652	73.00	1854.2
.223	5.664	.385	9.779		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Mounting hardware not supplied on types C and F.
4. Body dimension on switches is .375 ±.005 (9.53 ± .13 mm) across the flats and the button diameter is .218 ±.005 (5.54 ± 13 mm).
5. Alternative base metals and protective finishes, as approved by the qualifying activity, may be utilized for lock washer material. Dimensions shall be in accordance with referenced hardware specifications.

FIGURE 1. Dimensions and configuration – continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:14Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

Enclosure design: 5 (hermetic). Basic switch shall be hermetically sealed M8805/68-022 listed on QPL-8805. Plunger is unsealed.

Temperature characteristic: 2 (- 65°C to + 125°C).

Shock type: M (100 g, test condition I, method 213 of MIL-STD-202).

Vibration grade: 3 (10 Hz to 3,000 Hz swept sinusoidal).

Operating characteristics:

Actuating force: 30 ounces maximum at standard temperature and pressure (21°C and 14.7 psia).

Releasing force: 4 ounces minimum at standard temperature and pressure (21°C and 14.7 psia).

Movement differential: .005 inch (0.13 mm) maximum.

Pretravel: .010 inch (0.25 mm) maximum

Overtravel:

Type A and E: .125 inch (3.18 mm) minimum.

Type C and F; .060 inch (1.52 mm) minimum.

Contact resistance: .040 ohm + 0.011 ohm per lead per foot.

Dielectric withstanding voltage:

Sea level and 70,000 feet: 1,050 V rms (terminal to case), 800 V rms (terminal to terminal).

Seal test: Not required.

Mechanical endurance: 50,000 cycles.

Electrical endurance: 4 amp load: 25,000 cycles

Intermediate current: 25,000 cycles.

Low level: 25,000 cycles.

Electrical ratings: see table I.

Short circuit: 20 times rated resistive load (SAE-AS33201; PIN MS3320-7 ½, or equivalent used for circuit protection).

Weight: 0.6 ounce +0.1 ounce per lead per foot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:14Z
Check the source to verify that this is the current version before use.

Qualification:

Group submission: See table II.

Military Part or Identifying Number (PIN): See tables III and IV.

Table I. Electrical ratings.

Load	Sea level and 70,000 feet (28 V dc) (Amperes)
Resistive	4
Inductive	1
Lamp	2

Table II. Qualification.

Inspection	Basic Switch	Other switch samples	Extent of approval
Qualification inspection table of MIL-PRF-8805, groups I through VI inclusive (seal test not required)	M8805/72-038 (all sample units)	M8805/72-033 through –037, -039, -040 (2 sample units each): Visual and mechanical inspection only	All

Table III. PIN's and configurations.

PIN 1/	Electrical Endurance Cycles @ Resistive Load Ratings	Circuit Diagram	Type of Actuating Mechanism	Terminals
M8805/72-033		1	A	Wire leads – bottom
M8805/72-034	4 Amp	1	B	Wire leads – bottom
M8805/72-035		1	A	Wire lead – side
M8805/72-036		1	B	Wire lead – side
M8805/72-037		2	A	Wire leads – bottom
M8805/72-038	25,000	2	B	Wire leads – bottom
M8805/72-039		2	A	Wire lead – side
M8805/72-040		2	B	Wire lead - side

1/ PIN's -001 through -032 have been canceled and are no longer procurable. Use PIN's -033 through -040.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:14Z
Check the source to verify that this is the current version before use.

Table V. Substitution information for canceled PIN's. 1/

Inactive for new design PIN's M8805/72-		Substitute PIN's M8805/72-
4 Amp	7 Amp	4 Amp
015	025	033
016	026	034
017	027	035
018	028	036
021	029	037
022	030	038
023	031	039
024	032	040

1/ The canceled PIN's are no longer procurable. Substitute, PIN configurations are interchangeable and are rated at 4 amperes for 25,000 cycles..

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army – AR, AV, MI
Navy – AS, MC, OS, SH
Air force – 19, 99

Preparing activity:
DLA - CC

(Project 5930-1671-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:14Z
Check the source to verify that this is the current version before use.