INCH-POUND
MIL-PRF-8805/76J
19 November 2018
SUPERSEDING
MIL-PRF-8805/76H
4 October 2004

PERFORMANCE SPECIFICATION SHEET

SWITCHES, SENSITIVE, 2 CIRCUIT (5 AMPERES) OR SPST (8 AMPERES), UNSEALED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this document and MIL-PRF-8805.





FIGURE 1. Dimensions and configuration.

AMSC N/A

FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:15Z
Check the source to verify that this is the current version before use.



CIRCUIT SCHEMATIC

2 CIRCUIT

Inches	mm	Inches	mm
.001	0.03	.096	2.44
.002	0.05	.119	3.02
.003	0.08	.124	3.15
.005	0.13	.125	3.18
.010	0.25	.147	3.73
.020	0.51	.200	5.08
.030	0.76	.281	7.14
.053	1.35	.320	8.13
.055	1.40	.350	9.02
.088	2.24	.355	9.03
.090	2.29	.510	12.95
.093	2.36		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.015 (0.38 mm).

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:15Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

Enclosure design: 1 (unsealed).

Temperature characteristic: 2 (-65°C to +125°C).

Shock type: M (100 g, test condition I, of MIL-STD-202-213).

Vibration grade: 2 (10 Hz to 2,000 Hz).

Weight: .003 pound maximum.

Operating characteristics:

Free position: .355 inch ±.015 (see figure 1).

Actuating force: 8 ounces maximum, ±20 percent variation from specified values acceptable after test.

Overtravel: .004 inch minimum, ±20 percent variation from specified values acceptable after test.

Movement differential: .010 inch minimum, ±20 percent variation from specified values acceptable after test.

Operating point: .320 inch ±.015 inch (see figure 1).

Strength of actuator: 10 pounds.

Terminal strength: 5 pounds, all directions.

Dielectric withstanding voltage:

Sea level: 1,000 V rms initial.

1,000 V rms between all terminals and mounting plate after endurance test.

Altitude: 70,000 feet - 400 V rms.

Mechanical endurance: 100,000 cycles.

Electrical endurance: 50,000 cycles.

Electrical ratings: See table I.

Part or Identifying Number (PIN): See table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:15Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Load	Sea level, 28 V dc		70,000 feet, 28 V dc	
	SPST (NO or NC)	2 circuit	SPST (NO or NC)	2 circuit
	(amperes)	(amperes)	(amperes)	(amperes)
Resistive	8	5	8	5
Inductive	5	3	3	2
Motor	5	---	---	---
Lamp	1	---	---	---

TABLE II. PIN and terminal configurations.

PIN	Terminal configuration
MS27257-1	Spade type
MS27257-2	Turret type

NOTE: MS27257 was superseded by MIL-PRF-8805/76; the MS27257 Part Numbers (PINS) were retained.

QUALIFICATION:

Group submission: See table III.

TABLE III. Group submission.

PIN	Examination or test	Extent of approval
MS27257-1	Qualification inspection table of MIL-PRF-8805	All
MS27257-2 (2 sample units)	Visual and mechanical examination Terminal strength Dielectric withstanding voltage Operating characteristics	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:15Z
Check the source to verify that this is the current version before use.

Reference documents:
MIL-PRF-8805 MIL-STD-202-213

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced Documents:
MIL-PRF-8805
MIL-STD-202-213

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2018-055)

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:15Z
Check the source to verify that this is the current version before use.