QUALIFICATIONS VALIDATED
EVERY TWO YEARS

QPL-3965-72
12-Jul-04
SUPERSEDING
QPL-3965-71
26-Jul-02

QUALIFIED PRODUCTS LIST
OF
PRODUCTS QUALIFIED UNDER DETAIL SPECIFICATION
MIL-DTL-3965
CAPACITOR, FIXED ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM,
GENERAL SPECIFICATION FOR

Effective 8 June 1972, MIL-DTL-3965 has been declared "Inactive for New Design" with no superseding specification. This is applicable on all acquisitons to which MIL-DTL-3965 is applied

This list has been prepared for use by or for the Government in the acquisition of products covered by subject specification and such listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE DEFENSE SUPPLY CENTER COLUMBUS (DSCC-VQ), COLUMBUS, OH 43218-3990.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
CL10				
Cap values 2 uf thru 140 uf; Tols. T; voltages (RATED) 8, 10, 20, 30, 60, 90, 180, 270, 360; seal type G	XTM	3965-321-64	/20	Mallory-North American Capacitor Company
CL13				
Cap values 2 uf thru 140 uf; Tols. T; voltages (RATED) 8, 10, 20, 30, 60, 90, 180, 270, 360; seal type G	XTMG	3965-321-64	/20	Mallory-North American Capacitor Company
CL14				
Cap values 3.5 uf thru 200 uf; Tols. U; voltages (RATED) 20, 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G	XTH	3965-1457-63	/1	Mallory-North American Capacitor Company
CL16				
Cap values 3.5 uf thru 200 uf; Tols. U; voltages (RATED) 20, 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G	XTHS	3965-1457-63	/1	Mallory-North American Capacitor Company
CL17				
Cap values 12 uf thru 1300 uf; Tols. M, T; voltages (RATED) 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G	XTV	3965-731-64	/19	Mallory-North American Capacitor Company
CL18				
Cap values 12 uf thru 1300 uf; Tols. M, T; voltages (RATED) 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G	TL	3965-731-64	/19	Mallory-North American Capacitor Company
CL050				
Brackets used with styles CL51, CL52, CL53, CL54,	CL050	3965-383-66	/21	Mallory-North American Capacitor Company
CL55				
Cap values 70 uf thru 2400 uf; Tols. M; voltages (RATED) 15, 30, 50, 75, 100, 150; seal type G	TLX	3965-732-64	/21	Mallory-North American Capacitor Company
CL66				
Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	TLX	39006-462-75	/24	Mallory-North American Capacitor Company
High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	TLX	396-462-75	/24	Mallory-North American Capacitor Company

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:04Z
Check the source to verify that this is the current version before use.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SPECIFI-CATION SHEET	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	WH	3965-1254-68	/24	Vishay-Tansitor Electronics, Inc.
High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	WH	3965-1254-68	/24	Vishay-Tansitor Electronics, Inc.
CL67				
Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	TLX	396-462-75	/24	Mallory-North American Capacitor Company
High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	TLX	396-462-75	/24	Mallory-North American Capacitor Company
Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	WH	3965-1254-68	/24	Vishay-Tansitor Electronics, Inc.
High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G	WH	3965-1254-68	/24	Vishay-Tansitor Electronics, Inc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:04Z
Check the source to verify that this is the current version before use.

Manufacturer and Supplier Location Information

Manufacturer: Mallory-North American Capacitor Company (CAGE Code: 37942)

Location: P.O. Box 1284, 7545 Rockville Road, Indianapolis, IN 46206-1284, United States

Plant Location: Mallory (Greencastle, IN), CAGE Code: 37942, North American Capacitor Company, 1701 Indianapolis Road, Greencastle, IN 46135, United States

Manufacturer: Vishay-Tansitor Electronics, Inc. (CAGE Code: 05079)

Location: P.O. Box 230, 2813 West Road, Bennington, VT 0520l-9714, US

Plant Location: Same Address as Manufacturer

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:04Z
Check the source to verify that this is the current version before use.