QUALIFICATIONS VALIDATED
EVERY TWO YEARS

QPL-3965-74
05-May-05
SUPERSEDING
QPL-3965-73
09-Sep-04

QUALIFIED PRODUCTS LIST
OF
PRODUCTS QUALIFIED UNDER DETAIL SPECIFICATION
MIL-DTL-3965
CAPACITOR, FIXED ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM,
GENERAL SPECIFICATION FOR

Effective 8 June 1972, MIL-DTL-3965 has been declared "Inactive for New Design" with no superseding specification. This is applicable on all acquisitons to which MIL-DTL-3965 is applied

This list has been prepared for use by or for the Government in the acquisition of products covered by subject specification and such listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE DEFENSE SUPPLY CENTER COLUMBUS (DSCC-VQ), COLUMBUS, OH 43218-3990.

| GOVERNMENT DESIGNATION | MANUFACTURER'S DESIGNATION OR TYPE NUMBER | TEST OR QUALIFICATION REFERENCE | SPECIFICATION SHEET | SUPPLIER'S NAME (ADDRESS ON LAST PAGE) |
|---|---|---|---|---|
| **CL10** | | | | |
| Cap values 2 uf thru 140 uf; Tols. T; voltages (RATED) 8, 10, 20, 30, 60, 90, 180, 270, 360; seal type G | XTM | 3965-321-64 | /20 | Vishay Mallory |
| **CL13** | | | | |
| Cap values 2 uf thru 140 uf; Tols. T; voltages (RATED) 8, 10, 20, 30, 60, 90, 180, 270, 360; seal type G | XTMG | 3965-321-64 | /20 | Vishay Mallory |
| **CL14** | | | | |
| Cap values 3.5 uf thru 200 uf; Tols. U; voltages (RATED) 20, 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G | XTH | 3965-1457-63 | /1 | Vishay Mallory |
| **CL16** | | | | |
| Cap values 3.5 uf thru 200 uf; Tols. U; voltages (RATED) 20, 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G | XTHS | 3965-1457-63 | /1 | Vishay Mallory |
| **CL17** | | | | |
| Cap values 12 uf thru 1300 uf; Tols. M, T; voltages (RATED) 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G | XTV | 3965-731-64 | /19 | Vishay Mallory |
| **CL18** | | | | |
| Cap values 12 uf thru 1300 uf; Tols. M, T; voltages (RATED) 30, 60, 90, 180, 270, 360, 450, 540, 630; seal type G | TL | 3965-731-64 | /19 | Vishay Mallory |
| **CL050** | | | | |
| Brackets used with styles CL51, CL52, CL53, CL54, | CL050 | 3965-383-66 | /21 | Vishay Mallory |
| **CL55** | | | | |
| Cap values 70 uf thru 2400 uf; Tols. M; voltages (RATED) 15, 30, 50, 75, 100, 150; seal type G | TLX | 3965-732-64 | /21 | Vishay Mallory |
| **CL66** | | | | |
| Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | TLX | 39006-462-75 | /24 | Vishay Tansitor |
| Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | WH | 3965-1254-68 | /24 | Vishay Tansitor |
| High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | TLX | 396-462-75 | /24 | Vishay Tansitor |
| High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | WH | 3965-1254-68 | /24 | Vishay Tansitor |



**DISTRIBUTION STATEMENT A.** Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T13:04Z
Check the source to verify that this is the current version before use.

| GOVERNMENT DESIGNATION | MANUFACTURER'S DESIGNATION OR TYPE NUMBER | TEST OR QUALIFICATION REFERENCE | SPECIFI-CATION SHEET | SUPPLIER'S NAME (ADDRESS ON LAST PAGE) |
|---|---|---|---|---|
| **CL67** | | | | |
| Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | WH | 3965-1254-68 | /24 | Vishay Tansitor |
| Low-Capacitance series; Cap values 1.7 uf thru 330 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | TLX | 396-462-75 | /24 | Vishay Tansitor |
| High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | WH | 3965-1254-68 | /24 | Vishay Tansitor |
| High-Capacitance series; Cap values 3.6 uf thru 560 uf; Tols. J, K, M; voltages (RATED) 6, 8, 10, 15, 25, 30, 50, 60, 75, 100, 125; seal type G | TLX | 396-462-75 | /24 | Vishay Tansitor |


Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:04Z
Check the source to verify that this is the current version before use.

**Manufacturer and Supplier Location Information**

**Manufacturer: Vishay Mallory (CAGE Code: 37942)**
Location: 1701 Indianapolis Road, State Route 240, Greencastle, IN 46135, United States

Plant Location: Same Address as Manufacturer

**Manufacturer: Vishay Tansitor (CAGE Code: 05079)**
Location: P.O. Box 230, 2813 West Road, Bennington, VT 0520l-9714, US

Plant Location: Same Address as Manufacturer


Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:04Z
Check the source to verify that this is the current version before use.