NOT MEASUREMENT SENSITIVE

MIL-DTL-2/65
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

HYDROGEN SULFIDE, OUTLET 330

Pressures through 500 PSIG (3,450 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION: V65-330-2

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
III	30	A	6	330	Required	2 or 4

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:45Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: HYDROGEN SULFIDE.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).

INTENDED USE:

The valves covered by this specification sheet are intended for use with hydrogen sulfide cylinders.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing activity:
Air Force - 68

(Project 8120-1025-50)

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:45Z
Check the source to verify that this is the current version before use.