NOT MEASUREMENT SENSITIVE

MIL-DTL-2/69
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

CORROSIVE (ACIDIC) MIXTURES, OUTLET 330

Pressures through 3000 PSIG (20,680 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION: V69-330-0

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
IV	30	A	6	330	Required	0

DISTRIBUTION STATEMENT A. Approved for public release; distribution in unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. When specified, valve outlet threads shall be 1/2 NPT.
2. When specified, a dip tube shall be supplied in a radius to conform to the cylinder diameter specified.
3. Diaphragms shall be made of metal.
4. Mark the valve body: CORROSIVE (ACIDIC) MIXTURE.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Dip tube assembled to valve (required) (not required).
3. Diameter of cylinder (inches).

INTENDED USE:

The valves covered by this specification sheet are intended for use with cylinders containing corrosive (acidic) mixtures.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-54)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.