NOT MEASUREMENT SENSITIVE

MIL-DTL-2/71
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

HIGH PRESSURE, TOXIC AND OXIDIZING MIXTURES, OUTLET 660

Pressures through 3000 PSIG (20,680 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE PSI	TYPE SAFETY DEVICE
V71-660-3	1800	1
V71-660-4	2015	1

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
III	30	A	6	660	Required	1

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: HIGH PRESSURE, TOXIC AND OXIDIZING MIXTURE.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. When the cylinder service pressure is specified, the appropriate frangible disk safety device (type 1) shall be supplied.

INTENDED USE:

The valves covered by this specification sheet are intended for use with cylinders containing high pressure, toxic and oxidizing mixtures.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-56)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.