NOT MEASUREMENT SENSITIVE

MIL-DTL-2/71A
25 September 2002
SUPERSEDING
MIL-DTL-2/71
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS: HIGH PRESSURE, TOXIC AND OXIDIZING MIXTURES, OUTLET 660 (PRESSURES THROUGH 3000 psig (20680 kPa) AT 120 ºF (48.9 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-2 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE psig	TYPE PRESSURE RELIEF DEVICE (PRD)
V71-660-2	1800 through 2400	5
V71-660-3	1800	1
V71-660-4	2015	1
V71-660-5	2265	1
V71-660-6	2400	1

TABLE I. Valve requirements.

Style	Class	Composition	Inlet size	Outlet application	Handwheel	PRD[1]
III	30	A	6	660	Yes	1 or 5
IV	30	A	6	660	Yes	1 or 5

[1] See intended use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS:

1. Mark the valve body: H.P., TOXIC AND OXIDIZING MIXT.
2. When the cylinder service pressure is specified, the appropriate rupture PRD (type 1) shall be supplied.
3. When the cylinder service pressure is not specified, a combination PRD (type 5) shall be supplied with a rupture disk with a burst range between 2700 and 3000 psig. This device shall be utilized only for cylinders of 1800 to 2400 psig rating.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. PRD (required) (not required).

INTENDED USE: The valves covered by this specification sheet are intended for use with cylinders containing high pressure, toxic and oxidizing mixtures. If the LC50 of the mixture is equal to or less than 200 ppm, a PRD is prohibited. If the LC50 is greater than 200 ppm and contains a hazard zone A component, then no PRD is required; but if a PRD is used, it shall be a type 4.

NOTES:

1. Type designation will include any style valve from table I.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing Activity:
DLA - GS3

(Project 8120-1047-71)

Review Activities:
Army - AV
Navy - AS, MC, YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.