NOT MEASUREMENT SENSITIVE

MIL-DTL-2/71A
w/Amendment 1
29 September 2006
SUPERSEDING
MIL-DTL-2/71A
25 September 2002

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS: HIGH PRESSURE, TOXIC AND OXIDIZING MIXTURES, OUTLET 660 (PRESSURES THROUGH 3000 psig (20680 kPa) AT 120 ºF (48.9 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet, MIL-DTL-2, and QPL-2.

REQUIREMENTS:

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE psig	TYPE PRESSURE RELIEF DEVICE (PRD)
V71-660-2	1800 through 2400	5
V71-660-3	1800	1
V71-660-4	2015	1
V71-660-5	2265	1
V71-660-6	2400	1

TABLE I. Valve requirements.

Style	Class	Composition	Inlet size	Outlet application	Handwheel	PRD[1]
IIB	30	A	6	660	Yes	1 or 5
III	30	A	6	660	Yes	1 or 5
IV	30	A	6	660	Yes	1 or 5

[1] See intended use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS:

1. Mark the valve body: H.P., TOXIC AND OXIDIZING MIXT.
2. When the cylinder service pressure is specified, the appropriate rupture PRD (type 1) shall be supplied.
3. When the cylinder service pressure is not specified, a combination PRD (type 5) shall be supplied with a rupture disk with a burst range between 2700 and 3000 psig. This device shall be utilized only for cylinders of 1800 to 2400 psig rating.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. PRD (required) (not required).

INTENDED USE: The valves covered by this specification sheet are intended for use with cylinders containing high pressure, toxic and oxidizing mixtures. If the LC50 of the mixture is equal to or less than 200 ppm, a PRD is prohibited. If the LC50 is greater than 200 ppm and contains a hazard zone A component, then no PRD is required; but if a PRD is used, it shall be a type 4.

NOTES:

1. Type designation will include any style valve from table I.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

AMENDMENT NOTATIONS: The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review Activities:
Army - AV
Navy - AS, MC

Preparing Activity:
DLA - GS7

(Project 8120-2006-050)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:46Z
Check the source to verify that this is the current version before use.