NOT MEASUREMENT SENSITIVE

MIL-DTL-2/73
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

CORROSIVE (BASIC) MIXTURES, OUTLET 705

Pressures through 500 PSIG (3450 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION: V73-705-0

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
I	05	B	6	705	Required	0

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: CORROSIVE (BASIC) MIXTURES.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Cylinder service pressure (psi) (unknown).

INTENDED USE:

The valves covered by this specification sheet are intended for use with cylinders containing corrosive (basic) mixtures.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-58)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.