NOT MEASUREMET SENSITIVE

MIL-DTL-2/76
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

OXIDIZING MIXTURES, OUTLET 296

Pressures through 3000 PSIG (20,680 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE PSI	TYPE SAFETY DEVICE
V76-296-2	1800 through 2400	5
V76-296-3	1800	1
V76-296-4	2015	1
V76-296-5	2265	1
V76-296-6-	2400	1

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
III	30	A	6	296	Required	1 or 5

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: OXIDIZING MIXTURE

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Cylinder service pressure (psi) (unknown).

INTENDED USE:

The valves covered by this specification sheet are intended for use with cylinders containing oxidizing mixtures.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-61)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.