NOT MEASUREMENT SENSITIVE

MIL-DTL-2/76A
25 September 2002
SUPERSEDING
MIL-DTL-2/76
9 June 1995

DETAIL SPECIFICATION SHEET

# VALVE, CYLINDER, GAS: OXIDIZING MIXTURES, OUTLET 296 (PRESSURES THROUGH 3000 psig (20680 kPa) AT 120 ºF (48.9 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-2 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

| TYPE DESIGNATION | CYLINDER SERVICE PRESSURE psig | TYPE PRESSURE RELIEF DEVICE (PRD) |
|---|---|---|
| V76-296-2 | 1800 through 2400 | 5 |
| V76-296-3 | 1800 | 1 |
| V76-296-4 | 2015 | 1 |
| V76-296-5 | 2265 | 1 |
| V76-296-6 | 2400 | 1 |

TABLE I. Valve requirements.

| Style | Class | Composition | Inlet size | Outlet application | Handwheel | PRD |
|---|---|---|---|---|---|---|
| III | 30 | A | 6 | 296 | Yes | 1 or 5 |



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS:

1. Mark the valve body: OXIDIZING MIXT.
2. When the cylinder service pressure is specified, the appropriate rupture PRD (type 1) shall be supplied.
3. When the cylinder service pressure is not specified, a combination PRD (type 5) shall be supplied with a rupture disk with a burst range between 2700 and 3000 psig. This device shall be utilized only for cylinders of 1800 to 2400 psig rating.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Cylinder service pressure (psig) (unknown).

INTENDED USE: The valves covered by this specification sheet are intended for use with cylinders containing oxidizing mixtures.

NOTES:

1. Special requirements will be mandatory for all valve procurements.
2. Optional requirements will be specified for each valve procurement.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing Activity:
DLA - GS3

(Project 8120-1047-76)

Review Activities:
Army - AV
Navy - AS, MC, YD



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.