NOT MEASUREMENT SENSITIVE

MIL-DTL-2/77
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

METHYL CHLORIDE, OUTLET 660

Pressures through 500 PSIG (3,450 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE PSI	TYPE SAFETY DEVICE
V77-660-1-225	225	7
V77-660-1-240	240	7
V77-660-1-300	300	7

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
I	05	A	6	660	No	7

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. For type designations V77-660-1-225, V77-660-1-240, and V77-660-1-300 mark the valve body: METHYL CHLORIDE.
2. Type designation V77-660-1-225, V77-660-1-240, and V77-660-1-300 shall be only be used with methyl chloride.

OPTIONAL REQUIREMENTS:

1. Strainer (required) (not required).
2. Outlet cap or plug (required) (not required).
3. Wrench or key for style 1 valve (required) (not required).

INTENDED USE:

The valves covered by this specification sheet are intended for use with methyl chloride cylinders.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-65)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:47Z
Check the source to verify that this is the current version before use.