| NOT MEASUREMENT |
| SENSITIVE |

MIL-T-29182B(YD)
25 June 1990
SUPERSEDING
MIL-T-29182A(YD)
18 June 1984

MILITARY SPECIFICATION

TRAILER, CARGO; 4,000 POUNDS PAYLOAD, TANDEM AXLE, COMMERCIAL

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.2 Scope. This specification covers a commercial, tandem axle, cargo type trailer having a minimum payload capacity of 4,000 pounds (lb).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-V-62038 - Vehicle, Wheeled, Preparation for Shipment and Storage of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing, Commercial (Nontactical) Vehicles.
FED-STD-595 - Colors (Requirements for Individual Color Chips).

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plate Standards.
MS51336 - Lunette-Coupler, Drawbar, Ring.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government document. The following other Government document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Vehicle Safety Standards and Regulations.
Federal Motor Carrier Safety Regulations.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which are current on the date of the solicitation (see 6.2).

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

SAE J534 - Lubrication Fittings.
SAE J560 - Seven Conductor Electrical Conductor for Truck Trailer Jumper Cable.
SAE J588 - Turn Signal Switch.
SAE J682 - Rear Wheel Splash Throw Protection.
SAE J684 - Trailer Couplings, Hitches & Safety Chains-Automotive type.
SAE J1067 - Seven Conductor Jacked Cable for Truck Trailer connections.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard commercial product. The trailer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the trailer being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.2 First production vehicle. When specified (see 6.2), the contractor shall furnish a trailer for first production vehicle inspection (see 4.2.1 and 6.4).

3.3 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.4 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

3.5 Federal Motor Vehicle Safety Standards. The trailer and furnished accessories shall comply with all DoT Federal Motor Vehicle Safety Standards and Regulations in effect at time of manufacture.

3.6 Weights and dimensions.

3.6.1 Net weight. The net weight of the trailer shall include the weight of the chassis and the body with all accessories.

3.6.2 Gross weight. The gross weight shall consist of the net weight and a payload of not less than 4,000 lbs.

3.6.3 Weight distribution. The distribution of the gross weight for the purpose of establishing suspension, axle, and tire capacities shall be determined with the payload uniformly distributed over the load space.

3.6.4 Dimensions and clearances. The trailer, without payload, uncoupled from the towing vehicle, resting level on landing leg on level ground, shall conform to the dimensions and clearances specified in table I.

TABLE I. Dimensions and clearances.

Overall length, inches (not more than)	168
Overall width, inches (not more than)	96
Body length, inches (not more than)	120
Body height, inches +/-3 inches	81
Platform height, inches +/-1 inch	21
Axle ground clearance, inches from lowest point (not less than)	9

3.7 Performance. Trailer performance as specified in 3.7.1 through 3.7.3 shall be demonstrated by the trailer when fully equipped with all attachments and accessories, with payload uniformly distributed over trailer load area, completely serviced and towed by a towing vehicle over improved and unimproved hard, uneven terrain (see 6.5). The trailer, components, attachments, and accessories shall show no evidence of failure or malfunction.

3.7.1 Towing speed and trailing ability. When transporting the rated payload (see 3.6), while being towed over dry, level, smooth, improved, and prepared hard-surfaced roads at sustained speeds to 55 miles per hour (mph), and over dry unimproved and gravel roads at speeds to 10 mph the trailer shall follow the towing vehicle without exceeding the tracking deviations as specified in DoT Federal Motor Carrier Safety Regulations, section 393.70.

3.7.2 Braking ability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

3.7.2.1 Service brakes. The service brakes of the trailer in conjunction with towing vehicle (truck trailer combination) shall control, decelerate, and stop the vehicle combination in accordance with DoT Federal Motor Carrier Safety Regulations, section 393.52, when loaded as specified herein.

3.7.2.2 Parking brake. The hand parking (mechanical) brakes shall hold the loaded trailer on a dry hard surface road, on a grade not less than 30 percent, when uncoupled from the towing vehicle and resting on its landing leg, either headed up or down the incline.

3.7.3 Turning ability. When coupled to a towing vehicle operating in its minimum turning circle, the trailer shall follow without cramping. The trailer shall be capable of assuming an angle of 60 degrees (°) with the towing vehicle without damage to either, or interference between vehicles. The angle shall be measured between the longitudinal axis of the trailer and longitudinal axis of the towing vehicle at the ball hitch or lunette.

3.8 Trailer components.

3.8.1 Frame. Frame shall be all steel construction and shall be designed to transport the weight of the trailer body with all equipment and imposed load. All parts of the frame shall be completely electric arc welded. The frame main member shall be of one piece construction, without splices or joints, extended to form an "A" frame to which the coupling device shall be attached. A sufficient number of full width cross members shall be provided to assure structural capacity to resist bending and twisting when subjected to required performance (see 3.7 and 3.7.1).

3.8.2 Suspension. Trailer shall be equipped with a spring suspension system, with each component having a rated capacity at least equal to the load imposed, measured at the wheels at the ground, when the trailer is loaded as specified in 3.6. Springs shall have a rated capacity at least 15 percent greater than the respective imposed loads. Clearances between the springs and spring stops shall be sufficient to prevent bottoming. A sufficient number of alinement clips shall be provided to preclude lateral shifting.

3.8.3 Axles. The trailer shall be equipped with two axles mounted in tandem. Axle ratings shall be at least equal to the load imposed on each axle, measured between the wheels and the ground, when the trailer is loaded as specified in 3.6. The axles shall be so designed as to have no less than 3 inches ground clearance with the tires deflated.

3.8.4 Wheels, rims, tires, and inner tubes. The trailer shall be equipped with single wheels on each axle. Trailer wheels shall be manufacturer's standard. Rims and tire ratings shall conform to TRA recommendations, for the type and size of tires furnished. Tire and rim sizes shall be the same for all wheels on each axle.

3.8.4.1 Tires. Tires shall be tube or tubeless type with highway tread. Tires shall be truck type with a minimum of 8-ply rating and have the rated capacity at least equal to the load imposed on each tire, measured between each wheel and the ground, with the trailer loaded as specified in 3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

3.8.4.2 Inner tubes. When tube-type tires are furnished, inner tubes shall be heavy-duty type, and shall be of proper size for tires furnished. Tire flaps shall be provided for tube-type tires in accordance with TRA recommendations.

3.8.4.3 Spare wheel carrier. A spare wheel carrier shall be furnished and mounted on the trailer. The carrier shall be mounted in a readily accessible location on the curb side of the trailer body just forward of the fender, on the front of the trailer body (curb side), or centered on the A-frame accessible from the front curb side of trailer. Carrier shall permit ready removal or installation of spare tire assembly.

3.8.4.4 Spare tire. An inflated spare tire, mounted on a rim shall be furnished. The spare tire shall be of the same size, tread design, and ply rating as the tires in use on the trailer.

3.8.4.5 Tools. A wheel nut wrench shall be provided for exchanging the mounted tire assembly with the spare assembly. When specified (see 6.2), a hydraulic jack with jack handle shall be furnished and secured inside the trailer body. The closed height of the jack shall permit locating it under a satisfactory lift point at any wheel with a flat tire. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly.

3.8.5 Brakes. The trailer braking system shall comply with DoT Federal Motor Carrier Safety Regulations, sections 393.40 through 393.43, 393.45 through 393.47, and as specified herein.

3.8.5.1 Service brakes. The service brakes shall be hydraulic, internal expanding type, conforming to DoT Federal Motor Carrier Safety Regulations, section 393.40, and independent of the towing vehicle. The brake actuator shall be of the surge type, tongue mounted. The trailer shall be equipped with brakes at each of the four wheels.

3.8.5.2 Breakaway and emergency braking. A mechanical device conforming to DoT Federal Motor Carrier Safety Regulations, section 393.43, shall be furnished and shall apply and maintain application of the trailer service brakes for not less than 15 minutes upon breakaway from towing vehicle.

3.8.5.3 Parking brake. Parking brake shall be furnished and shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.41. Parking brake shall be of the internal expanding type. Parking brake lever shall have sufficient movement arm to require not more than 35 lb of effort for application and release. Provisions shall be made for slack adjustment. When brake cables are used, they shall be corrosion resistant.

3.8.6 Lighting. The electrical lighting system shall be 12 volts potential. All trailer lights, reflectors, and wiring shall be as specified herein and shall conform to DoT Federal Motor Carrier Safety Regulations, sections 393.15, 393.19, 393.20, 393.22, 393.23, 393.25 through 393.29, 393.32, and 393.33. Trailer wiring shall be routed through a conduit or tubing which is secured to the trailer chassis. Lights and reflectors shall not be mounted on

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

rub rails or trailer bumper. Two interior high intensity dome lights, suitably located, shall be furnished. Each light bulb shall be 15 candlepower minimum. A light switch shall be furnished in a convenient place at or near the rear door opening. The dome lights shall be connected to the auxiliary lighting cable circuit.

3.8.6.1 Clearance-marker lights. Side marker lights shall be furnished and mounted on the trailer body sides. Two amber colored marker lights (one on each side of trailer) shall be mounted at the highest and most forward point on the flat portion on the side of the trailer body. Two red colored marker lights (one on each side of trailer) shall be mounted at the highest and most rear point on the flat portion on the side of the trailer body. Marker lights shall be connected to the taillight circuit of the trailer.

3.8.6.2 Lighting cable. A seven-conductor lighting cable in accordance with SAE J1067 shall be furnished. One end of the lighting cable shall be connected to the trailer lighting circuit and wired to the uniform wiring pattern as specified in SAE J560. The auxiliary circuit shall be connected to the dome lights and the roof vent fan. The connector end of the cable shall be equipped with a round 7-conductor connector plug in accordance with SAE J560. The plug shall be equipped with a grip for withdrawing from connector socket. A 7-conductor connector socket shall be furnished with the lighting cable which is compatible with the connector plug. The lighting cable shall be coiled and shall be not less than 3 feet longer than the distance from the trailer receptacle to the lunette or ball hitch, when the cable is fully extended.

3.8.6.3 Turn signals. Turn signals conforming to SAE J588 shall be furnished.

3.8.7 Landing leg. Trailer shall have a retractable landing leg with a caster type landing wheel, with cranking handle (rigid or swivel type) permanently installed. The landing leg and related parts shall withstand without permanent deformation, the combined static and dynamic forces due to the proportionate weight of the gross weight, and impacts during coupling and uncoupling operations. Landing leg shall operate freely, and shall be protected from malfunctioning by foreign matter. When placed into travel position, the landing leg shall remain positively locked to provide ground clearance in the course of normal towing operations. The caster wheel shall be fitted with a bushing or antifriction bearing. Means shall be provided to lubricate the landing leg assembly and wheel.

3.8.8 Coupling device and tow bar. The trailer shall be furnished with a class 4 ball type (flanged), and a flange type lunette ring hitch (Holland Model 1250-15 or equal). Both the ball type and the lunette ring hitch shall be interchangeable with provisions made on the trailer for storing the hitch when not in use. The ball hitch, with a 2-5/16 inch diameter ball, shall conform to SAE J684 and the lunette ring shall conform to MS51336. Each type hitch shall be compatible with the surge type service brake actuator (see 3.8.5.1). Provisions shall be made to adjust the height of the coupling device, with the trailer in the horizontal position on level ground. The coupler shall be adjustable to a minimum height of 18 inches to a maximum of 24 inches. The coupler shall have not less than three adjustment positions. The tow bar shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

comply to DoT Federal Motor Carrier Safety Regulations, section 393.71. The coupling device "A" frame shall be designed to accept any commercially available load equalizing bars.

3.8.8.1 Safety chains. Safety chains conforming to DoT Federal Motor Carrier Safety Regulations, section 393.70 shall be furnished and so installed and arranged to permit connection to the towing vehicle from the towed trailer and shall be in accordance with SAE J684.

3.8.8.2 Center of gravity. The center of gravity with the payload evenly distributed shall be forward of the center line of the axles and shall be located so that 10 percent of the gross trailer weight is on the coupling device. The load on the coupling device with the trailer empty shall not be less than 150 lb.

3.8.9 Rear end protection. Trailer rear end protection shall conform to DoT Federal Motor Carrier Safety Regulations, section 393.86.

3.8.10 Lifting and tiedown attachments. The trailer shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the trailer. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tie down of the trailer on the carrier when shipped.

3.9 Body. The trailer shall be furnished with a fully enclosed body and provided with double rear doors. The exterior body dimensions shall be as specified in table I, and as specified herein. The width of the body shall be not less than 72 inches and fenders shall be provided as specified in 3.9.5. When specified (see 6.2), the width of the body shall be not less than 94 inches and wheel housings provided to prevent mud and water from splashing on the frame and body. The exterior, consisting of roof, sides, and end sheets utilized in body construction shall be aluminum alloy or stainless steel. When used, aluminum alloy sheets shall be not less than 0.032 inch, and stainless steel, shall be type 304 of not less than 16 gage. All panels shall be fastened by using the best commercial practices. All roof, body seams, and joints shall be sealed and weatherproofed. Effective means shall be taken to preclude electrolytic action between dissimilar metals.

3.9.1 Sidewall and roof framing. Sidewall and roof framing shall be manufacturer's standard steel or aluminum channel or hat section shaped aluminum extrusions. The vertical posts and roof framing shall be on not more than 24-inch centers. Roof framing shall be so constructed to insure drainage. Roof framing shall have no less than two longitudinal beams. Each side shall have no less than one longitudinal beam. Front end framing shall have no less than one transverse beam. Framing at rear door opening shall be constructed and braced to support the two rear doors. All parts of the frame shall be electric arc welded, riveted, or combination of both.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

3.9.2 Doors. Double rear doors shall be provided. The clear opening shall be not less than 70 inches in height. The clear opening shall be not less than 60 inches in width for the minimum 72-inch wide body and shall be not less than 82 inches for the minimum 94-inch wide body. Doors shall be hung with two pin strap hinges on each door. Hinges shall have a teflon bearing or equal material. Doors shall swing open no less than 180 ° from the closed position and shall be provided with a means for holding in the full open position. Doors shall be provided with gaskets and be tightly fitted to insure a seal against the entrance of water and dust. The door on traffic side (left) shall be provided with a latch at the top and bottom and be operated from inside the trailer. The door opposite traffic side (right) shall be provided with double cam latch with operating handle and have provisions for a locking type padlock. A rain gutter or drip rail shall be mounted outside, above the doors.

3.9.3 Flooring. The floor shall be not less than 1-inch exterior grade plywood. Not less than four nonferrous longitudinal hat shaped sections shall be installed in the flooring, flush with the floor surface. Floor fasteners shall be countersunk type and corrosion resistant type.

3.9.4 Air intake fan. An air intake fan shall be provided. The intake fan shall be mounted on the forward wall, centered, and as near the roof line as practical. The fan shall have not less than 200 cubic feet minimum air capacity delivery at atmospheric pressure. The fan shall be powered by a 12 volt direct current electric motor. A switch shall be conveniently located near or in the area of the dome light switch(s) (see 3.8.6). The fan shall be connected to the auxiliary lighting circuit cable. The opening for the fan shall be not less than 14 x 14 inches and no larger than 17 x 17 inches diameter. The fan mounting shall be reinforced on all sides. The fan opening shall have a hinged cover which when closed provides a weatherproof closure. The cover shall be operated from the outside and when in the closed position, shall be provided with an outside locking device.

3.9.4.1 Side vents. A vent shall be provided on each side of the body near the roofline at or near the center of the side panel. The minimum size of the opening shall be 12-inches wide x 18-inches long. The side panel opening shall be reinforced all around. The vent shall have hinged metal louvers which when closed provide a weatherproof closure. The louvers shall be operated from the outside and be provided with an outside locking device.

3.9.5 Fenders. The trailer furnished with the minimum 72-inch wide body shall be provided with fenders that cover each wheel and tire. The fenders shall be constructed with sufficient crown to prevent mud and water from splashing on the frame and body, and shall be capable of supporting personnel weight up to 200 lb. The fenders shall be rigidly attached to the chassis frame. Mud flaps shall be furnished and installed to the rear of the rear wheels in accordance with SAE J682.

3.10 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pound-force per square inch or higher, will damage grease seals or other parts,

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with type of lubricant specified in the operator's manual and grade of lubricant recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

3.11 Treatment and painting. Treatment, painting, identification marking, and data plates shall be in accordance with MIL-STD-1223, as specified for the Navy. Finish coat shall be an acrylic based enamel, color chip number 14064 green of FED-STD-595.

3.12 Rustproofing. The trailer shall be rustproofed in accordance with FED-STD-297.

3.13 Servicing and adjusting. Prior to acceptance of the trailer by the Government, the contractor shall service and adjust the trailer for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Adjustment of brakes.
c. Proper functioning of all lighting and electrical systems.
d. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.

The trailer shall be conspicuously tagged to identify the lubricants and their temperature range.

3.14 Workmanship.

3.14.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.14.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.14.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface or the member.

3.14.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subject to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production vehicle inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. This inspection shall include the examination of 4.3 and the tests of 4.4. The purpose of the inspection shall be to determine vehicle conformity with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its right under the provisions of the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.5, and the packaging inspection of 4.6.

4.3 Examination. Each trailer shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 First production vehicle tests. The first production vehicle shall be subjected to the tests specified in 4.4.1 through 4.4.4. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all trailers until corrective action has been taken.

4.4.1 Vehicle weight. The trailer shall be weighed to determine net weight and distribution of net weight on axles. The imposed loading on the axles shall be computed using the net weight and the specified payload (see 3.6.2 and 3.6.3). Calculated imposed loads on the axles shall be utilized to ascertain that the suspension, axles, and tires are of adequate capacity to meet specification requirements of 3.8.2, 3.8.3, and 3.8.4.1.

4.4.2 Road test. The trailer, loaded with payload and coupled to a truck, shall be towed for a distance of not less than 20 miles, to verify the performance requirements of 3.7. At least 20 percent of this distance shall be over unimproved roads at speeds as great as 10 mph. The other 80 percent of this distance shall be over improved roads at speeds as great as 55 mph. After test, the trailer shall be examined for evidence of misalignment, binding, or other malfunction.

4.4.3 Turning and tracking ability tests. The loaded trailer shall be tested for turning and tracking ability to verify compliance with the requirements of 3.7.1 and 3.7.3.

4.4.4 Brake performance tests. Service and parking brakes of the trailer, loaded with payload, shall be tested to verify conformance to 3.7.2.1 and 3.7.2.2.

4.4.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and be the last trailer shipped on the contract. The contractor shall maintain the trailer in a serviceable condition for the duration of the contract.

4.5 Production trailer tests. The contractor's testing system shall, as a minimum, assure that the trailer is capable of meeting the performance requirements specified herein.

4.6 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packed in accordance with the contractor's standard practice. When specified (see 6.2),

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

equipment shall be preserved, packed, and marked in accordance with the mobile requirements of MIL-V-62038 with the level of preservation and packing as specified (see 6.2).

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The trailer covered by this specification are commercial units intended for general purpose cargo handling.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When first production is required for inspection and approval (see 3.2).
d. When hydraulic jack is required (see 3.8.4.5).
e. When 94-inch minimum body width is required (see 3.9).
f. When preservation is in accordance with MIL-V-62038, it is required and the level of preservation is required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.475-1 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data should be delivered by the contractor in accordance with the contract of purchase order requirements.

6.4 First production vehicle. When a first production vehicle inspection is required, the vehicle shall be tested and should be a first production vehicle or a standard vehicle from the contractor's current inventory. The contracting officer should include specific instructions in the contract regarding arrangements for examination, test, and approval of the first production vehicle (see 3.2 and 4.2.1).

6.5 Definitions.

6.5.1 Improved road. An improved road is a smooth, hard, surfaced road, such as concrete or asphalt paved highway.

6.5.2 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) Listing.

Axle
Cargo
Trailer

Custodian:
Navy - YD

Preparing activity:
Navy - YD

(Project 2330-N011)

☆U.S. GOVERNMENT PRINTING OFFICE: 1990 - 704-034/30592

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-29182B(YD)	2. DOCUMENT DATE (YYMMDD) 1990 June 25

3. DOCUMENT TITLE
TRAILER, CARGO; 4,000 POUNDS PAYLOAD, TANDEM AXLE, COMMERCIAL

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME C. R. LEDERER, Director Equipment Criteria Development Division	b. TELEPHONE (Include Area Code) (1) Commercial (805) 982-5801 x452	(2) AUTOVON 551-5801 x452
c. ADDRESS (Include Zip Code) Commanding Officer (156) Naval Construction Battalion Center Port Hueneme, CA 93043-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:55Z
Check the source to verify that this is the current version before use.