MILITARY SPECIFICATION

MICROCIRCUITS, LINEAR, VOLTAGE REGULATOR, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/102B, dated 24 April 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

1.5, last column: Delete "θ_{JC}" and substitute "θ_{JA}".

PAGE 3

TABLE I, first load regulation characteristic, conditions column: Add "3/" to the right of T_A = +125°C.

PAGE 4

TABLE I, average temperature coefficient of output voltage characteristics, conditions column: Delete "-55°C $\leq T_A \leq$ -55°C" and substitute "-55°C $\leq T_A \leq$ +25°C".

TABLE I, add the following note: "3/ The test time is less than 50 ms. For sustained operation, the maximum power dissipation must be taken into account."

PAGE 6

TABLE III, test number 3, conditions column: Delete "V_{IN} = 12 to 15 V" and substitute "V_{IN} = 12 V to 40 V".

TABLE III, test number 12, conditions column: Add "4/".

PAGE 7

TABLE III, add the following note: "4/ Test time is less than 50 ms. For sustained operation, the maximum power dissipation shall be taken into account."

PAGE 17

FIGURE 5, test number 3, V_{IN}(volts) column: Delete "15" and substitute "40".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:16Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG
Air Force - 80

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1167-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:16Z
Check the source to verify that this is the current version before use.