MILITARY SPECIFICATION

MICROCIRCUITS, LINEAR LINE
DRIVERS AND RECEIVERS
MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/104B, dated 29 May 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2.3, case outlines: Delete "2 C-2 (20-terminal, .350" x . 350") square chip carrier package" and substitute "2 C-2 (20-terminal, SQ. LCC, .358" x .100", maximum)".

PAGE 9

TABLE I, I_{O2} and I_{O3}, delete and substitute the following:

Inhibited-state output leakage current (sink tied to pull up)	I_{O2}	V_{CC} = 5.5 V; V_O = 0.0 V	T_A = -55°C, +25°C		-120	µA
			T_A = +125°C		-175	µA
	I_{O3}	V_{CC} = 5.5 V; V_O = 0.4 V	T_A = -55°C, +25°C		±80	µA
			T_A = +125°C		±125	µA

"

PAGE 35

TABLE III, test numbers 58 through 63, terminal conditions column 16: Delete '"' and substitute "4.5 V".

PAGE 40

TABLE III, test numbers 125 through 132, maximum limits column: Delete "-120" and substitute "-175".

TABLE III, test numbers 133 through 140, maximum limits column: Delete "±80" and substitute "±125".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI
Navy - OS, SH
Air Force - 11, 19, 85, 99
DLA -ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1143)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:18Z
Check the source to verify that this is the current version before use.