[METRIC]
A-A-1608B
February 18, 1994
SUPERSEDING
A-A-1608A
December 31, 1992

COMMERCIAL ITEM DESCRIPTION

VIEWER, STILL PICTURE
(READER, MICROFICHE, DESK TOP)

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers desk top readers that will accommodate microfiche formats of 1:24 source document and COM format, 1:42 format and 1:48 COM format. The readers shall be of the following groups, types and styles, as specified:

Group 1 - 25 - 40 watts, energy savings/low energy consumption, light weight materials.
Group 2 - 40 - 50 watts , energy savings/low energy consumption, light weight materials, weight less than 9.1 kg (20 lbs).
Group 3 - 40 - 50 watts, up to 28 x 35.5 cm (11 x 14 inches) screen, and weighing between 9.5 - 15.9 kgs (21 -35 lbs).
Group 4 - up to 50 watts, weighing between 10.9 - 22.7 kgs (24 - 50lbs), Over-size screen which enables double page viewing of 1:24 source document and COM format (original typically a vertical A size drawing) and full size viewing of 1:42 and 1:48 COM formats.

Type I - 3/4 size, 20.5 x 25.5 cm (8 x 10 in) min. screen size, 1:42 COM format, single lens holder with 32x lens.

Type II - 3/4 size, 20.5 x 25.5 cm (8 x 10 in) min. screen size, 1:48 COM format, single lens holder with 36x lens.

Type III - Full size, 28 x 35.5 cm (11 x 14 in) min. screen size 1:24 source document and COM format, full size 1:48 COM format, dual lens holder with 24x and 48x lenses.

Type IV - 3/4 size, 28 x 28 cm (11 x 11 in) min. screen size, 1:48 COM format, full size 1:24 COM format, dual lens holder with 24x and 48x lenses.

Type V - Full size, 28 x 35.5 cm (11 x 14 in) min. screen size 1:24 source document and COM format, full size 1:42 COM format, dual lens holder with 24x and 42x lenses.

Type VI - 3/4 size, 28 x 28 cm (11 x 11 in) min. screen size, 1:24 COM format, full size 1:24 COM format, dual lens holder with 24x and 32x lenses.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 6730

Source: https://assist.dla.mil -- Downloaded: 20260410-26T08:15Z
Check the source to verify that this is the current version before use.

Shall be of the following styles, as specified:

Style A - Front screen projection.
Style B - Rear screen projection.

Salient characteristics.

General. Shall be designed specifically for desk top or table use.

Unacceptable features. Portable readers characterized by features such as light weight, handles for transporting, battery operation, collapsible design, integral or separate carrying case, etc.

Lens interchangeability. Lens shall be operator interchangeable and easily installed.

Replacement lamp. Lamp shall be easily accessible and replaceable without the use of special tools.

Electrical characteristics. Machine shall operate on 120 volts, 60 Hz.

Lamp. Rated average life of the lamp shall be not less than 500 hours.

Power cord. The power cord shall be at least 1.8 meters (6 feet) long.

Frame format.
Lens magnification of 24X, the reader shall display no less than one frame of 98 frame format, with no cropped images.
Lens magnification of 30.5X, 31X, 31.5X, 32X, 33X; 35X, 36X, 37X are all acceptable provided the projected image is confined within available screen area and 48X; the reader shall display no less than one frame of 208/270 frame format.
Lens magnification of 42X, the reader shall display no less than one frame of 210 frame format.

Image rotation. 360 degree image rotation shall be available, as specified:

1) by carrier on single lens unit.
2) by carrier on dual lens unit.
3) on low magnification lens.
4) on high magnification lens.
5) on both high and low magnification lenses of the same unit.

Light shield. Front screen readers shall have light-absorbing black on all non-optical surfaces surrounding the screen. Rear screen shall have a fixed or detachable ambient light shield.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.

Glass flats. Automatic separating glass flats that accept either a standard 105mm x 148mm microfiche for a single fiche or two standard 105mm x 148mm microfiches will be supplied, as specified.

Indexing. Readers shall have a separate indexing system for 1:24 source document and COM fiche, 1:42 COM fiche, and 1:48 COM fiche as applicable

Warning. Conspicuous warning signs shall be placed on or adjacent to areas or parts that may be of high voltage or other hazardous conditions

Instruction. An instruction manual or card shall be furnished.

Accessories. A cleaning kit and appropriate dust cover shall be furnished with each unit.

Workmanship. The machine, including all parts and accessories shall be fabricated and finished in accordance with good workmanship standards and the machine shall be free from any defect which affects the appearance, durability or serviceability or which might cause personal injury.

Conformance. Shall provide acceptable proof of conformance with the requirements of the applicable safety standard(s) for the product by an organization approved by the Occupational Safety and Health Administration (OSHA) as a "Nationally Recognized Testing Laboratory" (NRTL). Acceptable proof of conformance includes a labeling, listing or certification of the product by an NRTL.

Quality Assurance Provisions

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection and test requirements specified herein. Failure to meet all provisions of the requirements as specified, shall provide reason for rejection.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this Commercial Description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking. The preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

Notes: Purchaser should specify NSN, Group, Type and Style when ordering.

6730-01-235-3516	Group 1,	Type I,	Style B
6730-01-236-3836	Group 1,	Type II,	Style B
6730-01-236-2829	Group 1,	Type III,	Style B
6730-01-235-5533	Group 1,	Type IV,	Style B
6730-01-236-2830	Group 1,	Type V,	Style B
6730-01-235-5534	Group 1,	Type VI,	Style B
6730-01-235-5539	Group 2,	Type III,	Style B
6730-01-236-0819	Group 2,	Type V,	Style B
6730-01-236-1397	Group 2,	Type III,	Style A

Copies of FED-STD-376 may be obtained from the General Services Administration, Specifications Section (3 FBP-W), Suite 8100, 490 L'Enfant Plaza, SW, Washington, DC 20407.

PREPARING ACTIVITY

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.