[INCH-POUND]
A-A-3018
June 15, 1996
SUPERSEDING
GGG-R-180
January 21, 1992

COMMERCIAL ITEM DESCRIPTION

PILOT, REAMER

The General Services Administration has authorized the use of this Commercial Item Description for procurement of the Type IV pilots specified in GGG-R-180 for all federal agencies.

1. SCOPE

This Commercial Item Description covers reamer pilots for adjustable reamers covered by A-A-2937. The pilot is used for applications where alignment between reamed holes is necessary. The reamer pilot screws onto the adjustable reamer.

2. CLASSIFICATION

Not applicable

3. SALIENT CHARACTERISTICS

3.1 Design. The pilot shall consist of a pilot body, pilot bushing, and retaining collar. The pilot hole and tapers of the bushing shall be concentric within 0.0005 inch T.I.R. The bushing shall be double tapered and both ends shall take the full adjustment of the reamer. The bushing shall provide a sliding fit on the pilot body with a 0.0003 to 0.0005 inch clearance. pilots shall be similar to Figure 1 and conform to table I.




Figure 1. Pilot, Reamer

3.2 Material. The reamer shall be made of carbon tool steel.

3.3 Hardness. The pilot bushing shall be hardened and tempered to a Rockwell hardness value of soft to C45. When required to be tested, the pilot bushing shall be tested for hardness in accordance with ASTM E18.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Washington, DC 20406

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

Size	Pilot diameter (nominal) inch	Overall length min. (in)	max.(in)	Used with reamer size	Thread sizes	NSN 5110-00
A	13/32	4 7/8	5 1/8	A	5/16-24	049-8016
B	15/32	4 7/8	5 1/8	B	3/8-24	049-8017
C	17/32	5	5 1/4	C	7/16-20	049-8018
D	19/32	5 5/8	6	D	1/2-20	049-8019
E	21/32	5 5/8	6	E	9/16-18	049-8020
F	23/32	5 5/8	6	F	5/8-18	049-8021
G	25/32	5 5/8	6	G	11/16-16	049-8022
H	27/32	5 5/8	6	H	3/4-16	049-8023
I	31/32	5 5/8	6	I	7/8-14	049-8024
J	31/32	5 5/8	6	J	7/8-14	049-8025
K	1 3/32	5 5/8	6	K	1-14	049-8026

Table I

3.5 Workmanship. Details of workmanship shall be in accordance with the best commercial standards and practices. Paints, coatings, platings, and finishes shall be smooth adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g. sharp or rough external edges, corners or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety or appearance.

3.6 Identification marking. The reamer shall be marked with the manufacture's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the Contracting Officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product provided commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any of the inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING

6.1 Packaging. Requirements for preservation, packing and marking shall be as specified in the contract or order.

7. NOTES

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of reference documents.

Federal Specifications and standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC, 20407.

Federal Acquisition Regulations (FAR): Government Printing Office Superintendent of Documents, Washington, DC 20401-9371.

ANSI/ASQC Z1.4: American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 43201-4606.

ASTM E-18. American Society for Testing and Materials, 100 Burr Harbor Dr., West Conshohcken, PA 19428-2959.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and shall include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN.
(c) If bid samples are required and the number of samples required.
(d) If first article samples are required and the number of samples required.
(e) If lot sampling inspections are required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Examinations. Each sample tool shall be examined for all salient characteristics. The Inspection Level shall be S-3 with an Acceptable quality level (AQL) of 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

Testing. Each sample tool shall be tested for all salient characteristics. The Inspection Level for the hardness test shall be S-2 with an Acceptable quality level (AQL) of 2.5 percent defective. The Inspection Level for the performance test shall be S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective.

(f) What preservation, packaging, and marking are required.

7.3 National Stock Numbers (NSNs). NSNs shown may not be indicative of all possible NSNs associated with this CID:

See table I.

Military Interests:
None: DoD has no registered interest in revisions and notices to this Commercial Item Description until further notice.

Preparing Activity:
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.