A-A-50052
May 25, 1983

COMMERCIAL ITEM DESCRIPTION

RINSER-SANITIZER, CAN

The General Services Administration has authorized the use of this commercial item description in preference to Military Specification MIL-R-19038.

Salient characteristics:

Description. The rinser-sanitizer shall be a pedestal mounted unit consisting of a bowl, nozzle, floor mounting base, pedal operated hot and cold water valves, vacuum breaker, check valves, piping, and seals. The rinser-sanitizer shall be designed to clean garbage cans up to 25 inches outside diameter and 27 inches high. When bolted to the floor and connected to a cold water supply line and a 180°F water supply line, each capable of delivering at a pressure of 30 psig, the nozzle shall spray at a rate of 10 GPM with either pedal fully depressed. The unit shall be capable of withstanding a pressure of 180 psig for 1 minute without any leaks. This shall be determined by replacing the nozzle with a suitable pressure gage. The unit shall be designed to provide easy access to all pipes, valves, connections, etc., and not require the use of special tools for servicing.

Specific. Specific component item requirements are as follows:

a. Bowl. The bowl shall be dish shaped to a minimum depth of 4 inches and shall have an inside diameter sufficient to accommodate the garbage can. The top of the bowl shall be located at a maximum height of 25 inches from the floor. The bowl shall have not less than 4 stainless steel spokes firmly attached to support the cans above the contaminated water within the bowl. The bowl shall have a 1-1/2 inch I.P.S. drain pipe extending 1-1/2 inches to 6 inches below the bottom of the bowl. The top of the drain pipe shall have a removable stainless steel screen.

b. Nozzle. A rotary type nozzle shall be located in the center of the bowl. The nozzle shall be fabricated from stainless steel, brass, bronze, or aluminum or any combination thereof. The top of the nozzle shall be located at a maximum height of 33 inches from the floor. The nozzle spray pattern shall be effective in all inside areas of the can.

c. Pedestal. The pedestal shall have a base with holes for floor mounting bolts and shall be designed to support the bowl, pedals, and piping.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

d. Pedals. Each of the two pedals shall operate a quick-opening, self-closing, spring-loaded valve which is in a closed position until the pedal is depressed. Both pedals shall have automatic safety locks to prevent accidental opening. Both the safety lock and pedal must be depressed by foot, at the same time, to actuate either the hot or cold water valves.

e. Check valves. A check valve shall be installed in the cold and hot water inlet pipes before the pedal operated valves.

f. Brush. Each rinser-sanitizer shall be supplied with a brush attachment to clean the outside surface of the can. The brush attachment shall consist of a stiff and durable brush, insulated handle, hand valve, hose, and attachment fitting, all properly assembled.

g. Finish. Exposed surfaces of all components shall resist corrosion, cracking, chipping and peeling.

h. Instruction plate. An instruction plate, if necessary, shall be affixed to the unit to include warnings and cautions for safe operation and servicing of the unit.

i. Identification plate. The rinser-sanitizer shall have an identification plate which shall include, as a minimum, the manufacturer's name, model number, serial number, contract number and stock number.

Certification. The contractor shall certify that the product offered meets the salient characteristics of the description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices, and is the same as the product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packaging.

Commercial packaging. Each rinser-sanitizer shall be packaged in accordance with commercial practice.

Commercial packing. Each rinser-sanitizer shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:38Z
Check the source to verify that this is the current version before use.

Export packaging. The rotary nozzle, vacuum breaker and drain screen shall be packaged together in a fiberboard box. The box shall be secured to the unit with pressure-sensitive tape. The technical manual shall be placed in a plastic bag and the bag closed with tape. The bagged manual should be placed in the bowl of the unit. The rinser-sanitizer shall be cleaned, preserved and cushioned to afford protection against corrosion, deterioration, and physical damage during shipment and storage. Each rinser-sanitizer shall be packaged in a snug-fitting fiberboard box constructed and closed in accordance with style optional, class domestic, grade 275 of PPP-B-636 or class nonweather resistant, style optional of PPP-B-640.

Export packing. One rinser-sanitizer, export packaged or commercially packed as specified, shall be overpacked in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

Marking of shipping containers (commercial and export). Commercial marking for shipping containers is acceptable provided the following information is included:

National Stock Number
Item Description
Quantity, Unit of Issue
Date of Packaging (month/year)
Contract Number
Name, Address and Zip Code of Contractor

Source of information for nongovernment association documents:

National Motor Freight Traffic Association, Inc., Agent
National Motor Freight Classification
American Trucking Associations, Inc., Traffic Department
1616 P Street, N.W., Washington, DC 20036

Uniform Classification Committee, Agent
Uniform Freight Classification
Uniform Classification Committee, Suite 1106
222 South Riverside Plaza, Chicago, IL 60606

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD
Navy - MC
Air Force - 84

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0729

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:38Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:38Z
Check the source to verify that this is the current version before use.

PROCUREMENT USE:

DESCRIPTION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN