A-A-50653
September 11, 1981

COMMERCIAL ITEM DESCRIPTION

MAINTENANCE STAND, SELF-PROPELLED, SCISSORS LIFT

The General Service Administration has authorized the use of this commercial item description.

Scope. This commerical item description covers a self-propelled, scissors lift maintenance stand, consisting of a work platform and base, for use with large aircraft. Both electric-powered and diesel-driven stands are described herein.

Applicable documents. The following documents are referenced in this commercial item description:

MIL-H-5606 Hydraulic Fluid, Petroleum Base, Aircraft, Missile and Ordnance

(Copies of this military specification can be obtained from the procuring activity or as directed by the contracting officer.)

FED-STD-595 Color

(Copies of this federal standard can be obtained from the procuring activity or as directed by the contracting officer.)

National Electric Code

(Application for copies should be addressed to National Electrical Manufacturers Association, 2101 L Street, NW, Washington DC 20037.)

Tire and Rim Association Yearbook

(Application for copies should be addressed to Tire and Rim Association, Inc., 3200 W. Market Street, Akron OH 44313.)

Salient characteristics

a. size

(1) The stand shall be at least 37 feet high as measured from the ground to the underside of the platform when fully elevated and in a mobile configuration. The maximum height of the stand with platform lowered and guardrails removed shall be 8 feet 4 inches.

(2) The platform shall be at least 6 feet wide and 13 feet long, with a front overreach of at least 5 feet.

(3) The base shall be at least 6 feet wide and 8 feet long.

FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

b. Design

(1) The floor of the platform shall be steel plate with a non-skid surface. The platform shall have a guard rail, midrail, and kickplate around its upper periphery. The guardrail shall be at least 39 inches high and the kickplate shall be at least 4 inches high.

(2) The front and rear of the platform shall have access points. At the access openings, chains may be substituted for the guardrail and midrail, and the kickplate may be omitted.

(3) Means shall be provided for ascending the platform, If access ladders are provided as part of the platform, they shall be retractable.

(4) The front of the platform shall have two tie-down points for safety lanyards. The tie-downs shall withstand a 1500-pound dynamic shock load.

(5) The platform forward surfaces shall have wear-resistant bumpers to prevent damage when contacting an aircraft.

(6) A spotlight, adjustable through 360 degrees horizontally and ±60 degrees from the horizontal, shall be located at each corner of the platform.

(7) The base shall have four tie-down points. The tie-down points shall withstand the stress of air shipment, including the following loads; 3.0g fore and aft, 2.0g up, 4.5g down, and 1.5g laterally.

(8)- The stand shall have a drawbar ring capable of towing the stand up to 15 mph. The drawbar ring shall be formed of material with a diameter of 1-5/8 ±1/32 inch. The opening of the ring shall be 3 ±1/32 inch.

(9) The stand shall be equipped with both hydraulic brakes and a mechanical parking brake that will hold the stand, without load, on a 17-degree slope.

(10) The stand shall have pneumatic tires selected from the Tire and Rim Association Yearbook.

(11) The stand shall use hydraulic fluid in accordance with MIL-H-5606.

c. Function

(1) The platform shall have a sensing device to stop the motion of the stand when contact is made with an aircraft, The maximum force required to actuate the sensor shall be 10 pounds.

(2) Movement stabilizers shall be mounted on the base and shall be controlled from the platform. The stand shall be capable of speeds up to 0.8 mph with the platform elevated and the stabilizers extended.

(3) Operating controls shall be provided on the platform. The control boxes shall be weatherproof and illuminated with non-glare lighting. All controls, handles, et cetera shall be operable by personnel wearing heavy gloves, mittens, and bulky clothing or chemical defense ensembles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

(4) The platform elevating mechanism shall have a failsafe system to prevent platform descent due to malfunction or power loss. An emergency override system operable from both the platform and ground level shall allow the platform to be manually lowered in an emergency. A warning signal shall sound when the platform is lowered or the stand is moved under its own power in reverse.

(5) The stand shall be capable of raising, stopping, and holding 750 pounds located anywhere on the main platform up to the fully elevated position.

(6) The stand shall be capable of negotiating a 17-degree ramp for aircraft loading; no part of the stand other than the wheels shall contact the surface while being rolled into the aircraft.

(7) The stand shall be operable over a temperature range of -23°C to +55°C.

(8) The stand shall withstand winds of 43 mph with gusts to 65 mph with the platform fully elevated.

Models

a. Electric, An electrically powered stand shall comply with class 1, division 1, group D of the National Electric Code. A battery charger, operable on 115V/220V, 50/60 Hz, shall be provided, as a non-integral part, with each stand. A fully charged stand shall be capable of 8 hours operation with a 25-percent duty cycle, or 2 hours continuous operation.

b. Diesel. The diesel engine shall operate on standard diesel fuel, JP-4, JP-5, and JP-8.

c. The electric and diesel stand designs shall incorporate parts interchangeability to the maximum extent possible.

Color and finish. The stand shall be Forest Green, color 24052 in accordance with FED-STD-595. The stand shall be painted, and exposed surfaces shall be coated or finished, using the manufacturers best materials and standard practices.

Display information. All information specified herein shall be legible, visible, and accessible and shall be permanently displayed on the work platform. Reflectors shall not be required.

a. Plates. The following information shall be identified on plates:

(1) Warnings, cautions, or restrictions for safe operation -- to be identified in red.

(2) Make, model, serial number, manufacturer's name and address, rated load, and gross weight.

(3) Rated load and maximum platform height visible at platform access points.

(4) Alternate configuration statement near access points -- (Only required if rated load changes in alternate configurations).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

(5) An instruction placard at each control panel.

b. Stencils. The following information may be stenciled in flat black:

(1) Fuel and fluid types near fill points.

(2) Tire pressure near air fill points.

(3) Maximum towing speed on the front of the stand.

(4) Nominal voltage rating of batteries near terminals of battery-powered stands.

(5) Center of gravity at the CG of the base.

Workmanship The stands shall be free from imperfections that may affect appearance, serviceability, or durability. All parts shall be cleaned and free of extraneous materials. Burrs and sharp edges shall be removed.

Manuals Each stand shall be delivered with a complete set of parts manuals, maintenance manuals, and operating instructions.

Certification The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producers own drawings, specifications, standards, and quality assurance practices; and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packaging Each stand shall be packaged for shipment in accordance with normal commercial practices that shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage. Marking for shipment shall be as specified in the contract or order.

Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this commercial item description.

b. Marking for shipment.

Custodian:
Air Force - 11

Preparing activity:
Air Force - 11

Project No. 1730-F253

GSA DC-01201749

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.