INCH-POUND
A-A-50681A
06 MAY 2015
SUPERSEDING
A-A-50681
30 MAY 1989

COMMERCIAL ITEM DESCRIPTION

TRAILER, MAINTENANCE POWER

The General Services Administration has authorized the use of this Commercial Item Description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers a mobile power unit used to supply electric power, ventilation, compressed air, and water removal for telecommunication and utility installation and maintenance crews in cable vaults and manhours at locations distant from commercial sources of power.

2. SALIENT CHARACTERISTICS. The structural pumper truck shall be in accordance with the applicable requirements of the following chapters of NFPA 1901, Standard for Automotive Fire Apparatus (Current Edition).

2.1 General. The mobile power utility trailer shall be suitable for its intended use. Structural elements shall be rigid and possess the requisite strength. Individual components shall be durable reliable and suited for their intended purposes. The engine generator set, compressors and pump shall be standard commercial products. Service and parts shall be readily available for all components. The unit shall be towable at 60 MPH along paved highways. It shall have the following approximate minimum/maximum dimensions listed in Table I:

Table I. Dimensions

DIMENSION	MIN measurement	MAX measurement
Length	124 inches	136 inches
Width	68 inches	68 inches
Height	50 inches	58 inches

Comments, suggestions, or questions on this document should be sent to: WR-ALC / 404th SCMS/GUEEA, 295 Byron Street, Robins AFB, GA 31098-1611 or emailed to SPECC99@us.af.mil . Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/ .

AMSC N/A FSC 4940

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

2.2 Trailer. The trailer shall be a low profile unit, properly balanced to be handled by one person. The frame shall be all steel construction with minimum 10 gauge formed channel steel capable of supporting all equipment and accessories. The trailer shall have a spring steel suspension. It shall travel on two F78x15, minimum size, tires, and have a 36 inch adjustable front landing gear with pneumatic tire. It shall have mechanical type parking brakes and hydraulic, fully self-contained, surge type service brakes. A towbar with lunette conforming to A-A-52464 (3 inch dia. eye and 1 5/8 dia. ring) and safety chains shall be provided. The trailer shall have fenders, recessed tail lights, stop and turn signals. A seven conductor electrical connector shall comply with SAE J560. An intervehicle jumper cable with plugs conforming to SAE J560 shall be provided.

2.3 Equipment and storage area. Equipment and accessory storage areas shall be provided. Winged doors on each side of the storage cabinet shall be securable in the open position. All doors shall be lockable with a common key. The storage cabinet shall have a minimum of 20 cubic feet designated storage space with access from either side. The equipment area shall be sufficient to provide for ease of access for full servicing of all equipment and the rear of the control panel. There shall also be storage areas for hoses, platform supports, and extension boards. The floor shall have a sufficient number of drain holes. The storage compartment shall have a DC light.

2.4 Control panel. The control panel shall be easily accessible and located at the rear of the unit. It shall be incorporated in the shell of the equipment storage cabinet. It shall have a DC light. It shall have a door that covers all switches, outlets, gauges and meters. It shall be lockable with the common key. It shall include three 120 VAC, GFI protected duplex receptacles; one 240 VAC, GFI protected receptacle; one DC ammeter, two AC ammeteres, one AC voltmeter, and electric hour meter, and circuit breaker on/off switched for each circuit. The rear of the control panel shall provide for easy removal and re-connection of individual components.

2.5 Engine generator set. A minimum 7.5 KW, continuous duty, 120/240 VAC, 60 cycle, single phase, AC/DC generator directly connected to a four cycle gasoline engine rated 14 HP at 1800 RPM, water cooled, oil lubricated, electrically started, and designed in accordance with NEMA, IEEE and ASA standards shall be provided. Fuel will be ASTM-D4814 automotive gasoline. The engine shall have a low oil pressure and high water temperature safety shut-offs. It shall have a replaceable oil filter and a 12 VDC starting battery, 36 month maintenance free. The set shall be of sufficient quality to average a minimum of 2500 hours of operation between major overhauls. The exhaust system shall have a silencer assembly. An electric engine block heater shall be provided. Two 12 gallon, minimum, fuel tanks with fuel gages shall be secured at the front of the trailer.

2.6 Compressors. Dual 3/4 HP air compressors, oilless type, single stage, drip proof, ball bearing design, shall provide 5 CFM at 100 PSI. They shall be activated by a combination switch-circuit breaker on the control panel. An air pressure switch shall automatically start the primary compressor when pressure in the receiver drops to 80 PSI and stop it when pressure reaches 100 PSI. The secondary compressor shall automatically start when the pressure drops to 75 PSI and stop when pressure reached 95 PSI. A high pressure line shall have a gauge and regulator assembly adjustable to furnish air from 0 to 100 PSI. A low pressure, dry air line shall contain an air filter and heatless desiccant type dryer. It shall have a gauge and regulator assembly which shall be adjustable to furnish air from o to 40 PSI for communications cable pressurization and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

flash testing. A 12 gallon, minimum, ASTM stamped air tank with automatic drain and 1/4 inch by 25 foot air hose assembly with quick connector shall be provided.

2.7 Pump. A two inch submersible pump, 120 VAC, shall provide 110 GPM pumping rate. It shall be activated by a combination switch-circuit breaker on the control panel. A 2 inch by 25 foot discharge hose with quick connector shall be provided.

2.8 Ventilation equipment. A two speed blower shall deliver 1000 CFM free air a high speed for purging and 640 CFM free air at low speed for ventilating. The blower speed switch shall be on the control panel. The blower intake shall be located on the right side of the trailer and away from engine exhaust. The blower outlet shall be located at the rear of the trailer. The blower outlet shall allow and eight inch flexible blower hose to be attached. An 8 inch by 20 foot blower hose, with storage provision on the trailer, shall be provided. A heat exchanger, incorporated into the blower assembly, shall transfer heat from the engine cooling water to the blower air. It shall be capable of raising the temperature of the air leaving the blower 100 degrees F over the ambient temperature. A electric water pre-heater shall facilitate a supply of warm air prior to the engine reaching sufficient temperature to warm its cooling system. The pre-heater shall work in conjunction with the engine to provide increased capability in cold weather. The heater control switches shall be mounted on the control panel.

2.9 Accessories. Accessories to be included are:

a. Light standard adjustable to nine feet. A amber strobe light and two 300 watt (minimum) floodlight assemblies. A bracket shall be mounted inside the cabinet for storing the strobe and floodlight assemblies.

b. A 12 inch deep manhole rim with air inflatable bladder for sealing and seating with mounting bracket or holder.

c. A manhole guard rail with holder.

2.10 Spare Parts. Spare parts to be included are:

a. Oil, fuel and air filters, spark plugs, condenser, rotor, and distributor cap.

b. Two replacement lamps for the flood lights.

c. One replacement lamps for the strobe light.

d. One each bulb for the control panel and storage compartment lights.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

3. REGULATORY REQUIREMENTS.

3.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or refurbished items shall not be provided.

3.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

4.2 Regulatory Requirements. The mobile power utility trailer shall comply with all applicable Federal Motor Carrier Safety Regulations and OSHA Regulations.

5. PACKAGING.

5.1 Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 Military Specifications, Standards and Handbooks referenced herein may be obtained at https://assist.dla.mil or available from the Standardization Documents Order Desk, 700 Robbins Ave, Bldg. 4, Section D, Philadelphia, PA 19111-5094.

6.1.2 The Code of Federal Regulations (CFR) may be obtained at http://www.gpoaccess.gov/cfr/ or from the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

6.1.3 SAE documents may be obtained http://www.sae.org/servlets/index or from SAE, Inc., 400 Commonwealth Drive, Warrendale PA 15096

6.1.4 National Electrical Manufacturers Association (NEMA) standards may be obtained from National Electrical Manufacturers Association, 1300 North 17th Street, Suite 1752, Rosslyn, Virginia 22209. Electronic copies of NEMA standards may be obtained from http://www.nema.org/stds/ .

6.1.5 FAR. FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh PA 15250-7954. Electronic copies of the FAR may be obtained from https://www.acquisition.gov/far/.

6.1.6 Occupational Safety and Health Association (OSHA) copies may be obtained online at http://www.osha.gov/ or from OSHA, 200 Constitution Ave., Washington, D.C. 20210.

6.1.7 ASTM standards may be obtained from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959. Electronic copies of ASTM standards may be obtained from http://www.astm.org.

6.1.8 NFPA documents. NFPA copies can be obtained online at http://www.nfpa.org/ or at NFPA, 1 Batterymarch Park, Quincy, MA 02169-7471 – phone 617-770-0700.

6.2 National Stock Number(NSN). The following is a list of NSNs assigned that correspond to this CID. The list may not be indicative of all possible NSNs associated with this CID.

NSN
4940-01-239-0270

6.3 Key Words.

Mobile
Telecommunication
Utility Installation

6.4 Changes from previous issue. Marginal notations are not used in this in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AR
Air Force - 84

Preparing Activity:
Air Force - 84

Reviewers:
Air Force - 99

Agent:
Air Force - 99

(Project 4940-2014-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.