A-A-50686
13 Nov 89

COMMERCIAL ITEM DESCRIPTION

AIR CONDITIONER, TRAILER MOUNTED, ELECTRIC MOTOR, DRIVEN

The General Services Administration has authorized the use of this Commercial Item Description.

Abstract. The Commercial Item Description describes an electric motor driven trailer, mounted air conditioner for delivering conditioned air (cooling and heating) to the E-3A and other military aircraft.

Salient characteristics.

1. Physical characteristics.

   a. Dimensions. The overall dimensions of the air conditioner shall not exceed 230 inches in length, 94 inches in width, and 94 inches in height.

   b. Weight. The maximum overall weight of the air conditioner when equipped with ducts, connectors, fluids, and one half tank of fuel shall not exceed 20,000 pounds. The weight of the air conditioner shall not exceed 6,500 pounds per wheel or 13,000 pounds per axle.

   c. Cleaning, treatment and painting. Cleaning, treatment, and painting shall be in accordance with MIL-STD-808 in conjunction with Table I of Air Force Drawing 7545352. The color finish shall be dark green (FED-STD-595, Color No. 24052).

   d. Markings. Warnings, cautions, or restrictions shall be identified. An instruction panel shall be located near the control panel. An identification plate of the air conditioner (model no., serial no., etc.) shall be provided. Doors or panels that must be open before operation shall be clearly marked.

2. Design characteristics.

   a. Trailer assembly. The air conditioner shall be mounted on a trailer with wheels at both front and rear. The air conditioner shall provide for two-wheel front end steering and have a tow bar with a lunette eye (with a minimum inside diameter of 3 inches). Positive stops shall be provided to limit the maximum cramp angle. The trailer shall be equipped with pneumatic tires.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Support Division, SA-ALC/MMDEMM, Kelly AFB TX 78241-5000.

AMSC N/A FSC 4120

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:45Z
Check the source to verify that this is the currentversion before use.

b. Electric motors. The air conditioner components shall be electrically motor driven. The air conditioner shall operate when supplied with a 480V/60Hz/3 phase power source. A flexible, insulated power cable shall be provided and shall be adequately rated for the application.

c. Tie down rings. Tie down rings shall be provided to secure the unit in shipment and for lifting.

d. Conditioned air outlets. The air conditioner shall have a minimum of three separate, individually controlled (for flow) 12 inch outlet ducts. The air conditioner shall have 12 inch diameter air duct hose male connectors in accordance with Air Force Drawing 64C1004 for attaching a 12 inch diameter flexible air duct.

e. Control panel. A control pannel shall be provided with the following minimum controls and gages:

1. Ammeter - indicates power supply amperage.

2. Voltmeter - indicates power supply voltgage.

3. Start switch - switch to start the air conditioner.

4. Discharge pressure gage - indicates refrigerant compressor discharge pressure.

5. Suction pressure gage - indicates refrigerant compressor suction pressure.

6. Oil pressure gage - indicates refrigerant compressor oil pressure.

7. Blower discharge pressure - indicates blower discharge pressure.

8. Airflow indicator gages - indicates flow rate of conditioned air into each individual air duct.

9. Airflow controls - adjusts flow rate of conditioned air into each individual air duct.

10. Temperature gage - indicates temperature of conditioned air into the duct assemblies.

11. Temperature control - controls temperature of conditioned air into the duct assemblies.

3. Performance characteristics.

a. Conditioned air. The air conditioner shall be capable of delivering 450 pounds per minute (ppm) of 50°F air against a maximum static pressure of 1.0 psig into three separate, individually controlled 12 inch outlet ducts. Each individual outlet shall be capable of providing 200 ppm of conditioned air.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:45Z
Check the source to verify that this is the current version before use.

b. Ambient conditions. The air conditioner shall operate in ambient conditions ranging from 0°F to 125°F.

c. Mobility. The air conditioner shall be capable of being towed at speeds up to 20 mph on an aircraft taxiway and flight line type surface.

d. Parking brakes. The air conditioner shall have mechanically actuated parking brakes.

4. Manuals. The air conditioner shall be delivered with a complete set of parts manuals, maintenance manuals and operating instructions.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The Government reserves the rights to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements of exposing the supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Custodian:
Air Force - 99

Preparing activity:
Air Force - 82

(Project 4120-F324)

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:45Z
Check the source to verify that this is the currentversion before use.