MILITARY SPECIFICATION SHEET

FIXTURES, LIGHTING; FLUORESCENT, GENERAL LIGHTING,
DIRECTIONAL 32 WATTS, 120 VOLTS, 60 HERTZ, WATERTIGHT,
SYMBOLS 145.4 AND 145.5

This amendment forms a part of MIL-F-16377/10A, dated 30 November 1970, and is approved for use within the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Under "NOTES", delete 7 and 8, and substitute:

"7. For replacement parts only, one type VI modified label shall be applied on the inside surface of curved area of window. Type VI label shall be in accordance with 3.7.4.3 of MIL-F-16377 except add "THIS SIDE FACES AREA TO BE LIGHTED".

PAGE 6

Under "DESIGN:" "Designation and marking:", delete (d) and substitute:

"(d) One type IV applied as shown on figure 2, bearing the legend "THIS SIDE OF FIXTURE AND CLEAR, CURVED PORTION OF WINDOW ASSEMBLY SHALL FACE AREA TO BE LIGHTED".

Preparing activity:
Navy - SH
(Project 6210-N621)

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.