
MILITARY SPECIFICATION SHEET

FIXTURES, LIGHTING; FLUORESCENT, GENERAL LIGHTING

24 WATTS, 120 VOLTS, 60 HERTZ, WATERTIGHT, SYMBOLS 73.3, 73.4, 346.2 AND 346.3

This specification sheet is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the fixtures described herein shall consist of this document and the latest issue of MIL-F-16377(SH).



SH8605

FIGURE 1. Typical view of Symbols 73.3 and 346.2.

All dimensions in inches.
For tolerances, other than specified herein, see paragraph 3.5.2 of MIL-F-16377.

FSC 6210

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.




FIGURE 2. Typical section for Symbols 73.3 and 346.2.





FIGURE 3. Typical section for Symbols 73.4 and 346.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.



ANGLE	CANDLEPOWER SYMBOL NUMBER	
	73.3, 73.4	346.2, 346.3
0	212	265
5	212	265
10	210	265
15	208	260
20	202	260
25	195	251
30	190	242
35	180	232
40	165	218
45	155	200
50	138	175
55	122	147
60	112	125

ANGLE	CANDLEPOWER SYMBOL NUMBER	
	73.3, 73.4	346.2, 346.3
65	95	97
70	85	75
75	70	57
80	55	40
85	45	30
90	32	20
95	22	15
100	15	10
105	10	11
110	5	6
115	5	0
120	5	0
125	0	0

SH8609

Photometric test data:

Distance: 10 feet.
Plane: At right angles to long axis of fixture through geometric center of lamp.
Voltage: 115 volts, 60 Hz.
Ambient temperature: 76°F.
Lamps: Use lamps furnished with fixtures seasoned for at least 100 hours.
Ballast: Use ballast furnished with fixture.
Lamp correction: Distribution curves based on 380 lumens per lamp.

FIGURE 4. Candlepower distribution curves.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

CLASSIFICATION:
Type: I
Class: 2

SYMBOL NUMBERS:
73.3: Complete lighting fixture assembly, standard mounting, with three 8-watt cool white fluorescent lamps and white diffusing window assembly.
73.4: Complete lighting fixture assembly, flush mounting with three 8-watt cool white fluorescent lamps and white diffusing window assembly.
346.2: Complete lighting fixture assembly, standard mounting with three 8-watt cool white fluorescent lamps and clear and white prismatic window assembly.
346.3: Complete lighting fixture assembly, flush mounting, with three 8-watt cool white fluorescent lamps and clear and white prismatic window assembly.

DESIGN:
Electrical rating: 24 watts, 120 volts, 60 Hertz.
Dimension and configurations: See figures 1, 2 and 3 and figure 10 of MIL-F-16377.
Photometric data: see figure 4.
Lampholder spacing: see figure 21 of MIL-F-16377
Wiring diagram: see figure 24 of MIL-F-16377.
Mounting dimensions:
Symbols 73.3 and 346.2: see figure 25 of MIL-F-16377.
Symbols 73.4 and 346.3: see figure 26 of MIL-F-16377.
Window assembly:
Symbols 73.3 and 73.4 : Military Part Number M16377/9-001, figure 27 of MIL-F-16377.
Symbols 346.2 and 346.3: Military Part Number M16377/9-003, figure 27 of MIL-F-16377.
Enclosure: Watertight. See 3.5.11 of MIL-F-16377.
Cable: 10 feet of type SJO or SJT, construction in accordance with J-C-580 except AWG size 16, three conductor (white, black, and red).
Weight:
Symbols 73.3 and 346.2: 7 lbs. 7 oz. maximum.
Symbols 73.4 and 346.3: 8 lbs. 11 oz. maximum.
Designation and marking: The following labels shall be furnished in accordance with MIL-F-16377 applied as shown in figures 1 and 3:

(a) Two type I
(b) One type II for Symbols 73.4 and 346.3 only.
(c) One type IV. The information to be shown on the type IV label shall be "USE THE FOLLOWING REPAIR PARTS ONLY." List all standard parts shown in table I and window assemblies of table IV by name and stock number only.

Standard Parts: The standard parts shown in table I shall be used in the construction of the fixtures specified herein.

TABLE I. Standard parts.

Name	Specification or Military part number	National Stock Number (NSN)	Remarks
Lamp	W-L-116/3	6240-00-299-5546	Industry Number F8T5/CW
Lock lamp	M16377/40-001	6250-00-399-7039	
Lampholder	MIL-L-970/10	6250-00-377-8590	
Startersocket	MIL-L-970/13	6250-00-295-2738	
Starter	8W, Type III of W-S-755	6250-00-299-5962	Commercial Designation: FS5
Ballast	M16377/45-001	6250-00-295-2735	
Shockmount	M16377/41-009 or M16377/41-010	6210-00-973-1747 6210-00-973-1748	See 3.5.16 of MIL-F-16377
Red filter tube	M16377/42-001	6210-00-399-6297	Not furnished See 3.7.7 of MIL-F-16377

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.

QUALITY ASSURANCE:

First article inspection:
Complete fixtures: See table II
Window assemblies: See table III
Quality conformance:
Comparison inspection: Same as the first article inspection.
Inspection of product for delivery:
Examination: See MIL-F-16377
Examination for preparation of delivery: MIL-F-16377
Quality conformance tests: See MIL-F-16377

GENERAL INFORMATION:

Assignment of Military part numbers and general information is shown in table IV.

TABLE II. First article and comparison inspection for complete fixtures.

Tests	Requirement paragraph	Test paragraph	Remarks
Examination	3.13	4.5	
Operation	3.13	4.8.1	
Dielectric	3.6.15	4.8.2	
Insulation resistance	3.6.16	4.8.3	
Enclosure effectiveness	3.5.11	4.8.14.4	Watertight
Shock	3.5.12	4.8.7	
Vibration	3.5.13	4.8.8	
Enclosure effectiveness	3.5.11	4.8.14.4	Watertight
Dielectric	3.6.15	4.8.2	
Insulation resistance	3.6.16	4.8.3	
Noise	3.5.14	4.8.9	
Continuity of grounding	3.6.13.4	4.8.12	
Optical uniformity	3.7.4.1.1	4.8.4	
Stress relief	3.8.5.3	4.8.5	
Light output	3.7.1	4.8.6.1	Candlepower
Magnetic permeability	3.4.8	4.8.18	

TABLE III. First article and comparison inspection for window assemblies.

Tests	Requirement paragraph	Test paragraph	Remarks
Examination	3.13	4.5	
Optical uniformity	3.7.4.1.1	4.8.4	
Stress relief	3.8.5.3	4.8.5	
Shock	3.5.12	4.8.7	
Vibration	3.5.13	4.8.8	
Enclosure effectiveness	3.5.11	4.8.14.4	Watertight
Light output	3.7.1	4.8.6.1	Candlepower

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.

TABLE IV. Part number and general information.

Military part 1/ number M16377/9-	Item name	National Stock Number (NSN)	Remarks
73.3	Complete fixture, Symbol 73.3	6210-00-295-2880	2/
73.4	Complete fixture, Symbol 73.4		2/
346.2	Complete fixture, Symbol 346.2		New
346.3	Complete fixture, Symbol 346.3		New
001	Window, white diffusing	6210-00-548-0214	3/
003	Window, clear and white prismatic		New

1/ Military part numbers M16377/9-346, 346.1 and 002 have been superseded by Military part numbers M16377/9-346.2, 346.3 and M16377/67-002 respectively.

2/ Formerly covered on NAVSHIPS Drawing 9000-S6401-74461 and MS17150

3/ Formerly covered on MS1689.38.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 6210-N557)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 3112)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:41Z
Check the source to verify that this is the current version before use.