MIL-C-19219D(YD)
17 November 1987
SUPERSEDING
MIL-C-19219C(YD)
9 November 1981

MILITARY SPECIFICATION

CURTAIN, DOORWAY, DARKROOM

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for materials and fabrication of materials into light-proof curtains to be used in photographic darkrooms and adjoining areas in advanced base components. The curtains shall be of one type and size only.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-276 - Thread, Cotton.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-T-3530 - Thread and Twine: Mildew Resistant or Water Repellent Treated.
MIL-G-16491 - Grommet, Metallic.
MIL-C-20696 - Cloth, Coated, Nylon, Waterproof.

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D3951 - Packaging, Commercial.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Description. The finished curtains shall be 52 inches ± 0.5 inch wide by 84 inches ± 0.5 inch long, finished measurements. The curtains shall have a 3-inch ± 0.25 inch, single turn hem at top and bottom with raw edges turned under and a 1-inch ± 0.25 inch single turn hem along the sides with raw edges turned under. The hems shall be sewn straight and smooth without pleats or puckers. The curtains shall be sewn with black cotton thread conforming to type IA, 3 ply, number 60 ticket of V-T-276. The cotton thread shall be treated for mildew resistance in accordance with MIL-T-3530. Stitching shall be stitch type 301 in accordance with FED-STD-751, with an average of 6 to 8 stitches per inch. All stitching shall be backedstitched 0.5 inch at the beginning and end of the hems to prevent thread pulling. In case of thread break, the area at the break shall be backedstitched at least 1 inch for each break. Nylon thread that will meet the same requirements may be used in lieu of cotton thread specified herein. Whichever thread is used, the thread tension shall be properly maintained so as to prevent loose or irregular stitching.

3.2 Standard commercial product. The curtains shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the curtain being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.3 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.

3.3.1 Cloth. The cloth used in the fabrication of the curtains shall be coated nylon conforming to type II, class 3 of MIL-C-20696. Unless otherwise specified (see 6.2.1), the color shall be black.

* 3.3.2 Grommets. The finished curtain shall be equipped with brass grommets conforming to type II, class 1, size number 5 of MIL-G-16491. Grommets shall be equally spaced along the top edge of the curtains, on 4-inch ± 0.25 inch center. Grommets shall be located 2 inches ± 0.25 inch from the top of finished curtain to center of grommets. End grommets shall be located 2 inches ± 0.25 inch from sides of finished curtains to center of end grommets.

3.4 Interchangeability. All curtains of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability.

3.5 Identification marking. Unless otherwise specified (see 6.2.1), curtains shall be marked for identification in accordance with manufacturer's standard practice. Identification shall include the manufacturer's model and serial number, name and trademark to be readily identifiable to the manufacturer.

3.6 Workmanship. Workmanship shall be of a high grade throughout and in accordance with the best standard practice for this type of item. All surfaces shall be smooth and free from any irregularities which would affect the appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of product shall be one curtain. All curtains offered for delivery at one time shall be considered a lot for the purpose of inspection. The inspection level shall be level II and the Acceptable Quality Level shall be 4.0 percent defective for major defects and 6.5 percent defective for minor defects. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separated from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each curtain shall be examined for defects listed in table I. Each attribute within each classification of multiple defects shall constitute one defect.

TABLE I. Classification of defects.

Classification	Defects	Requirement paragraph
Major:		
101	Curtains not constructed as specified.	3.1
102	Dimensions of curtains not as specified.	3.1
103	Cloth cut, torn or stained.	3.3
104	Type, size, alignment, and location of grommets not as specified.	3.3.2
105	Defective grommets affecting serviceability.	3.3.2
106	Hems not sewn.	3.1
107	Dimensions and alignment of hems not as specified.	3.1
108	Loose stitching.	3.1
109	Open seams.	3.1
Minor:		
201	Fabric or threads in grommet holes.	3.3.2
202	Small pleats and puckers in cloth.	3.6
203	Hems not sewn straight and smooth.	3.1
204	Raw edges of hems exposed.	3.1

4.5 Packaging inspection. The preservation, packing, and marking of the item shall be inspected to verify conformance to the requirements of section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2.1).

5.1.1 Level A.

5.1.1.1 Cleaning and drying. The curtains shall be cleaned and dried by any suitable process listed in, and in conformance with MIL-P-116.

5.1.1.2 Method of preservation. Each individual curtain shall be preserved by any suitable submethod of IC in accordance with MIL-P-116.

5.1.2 Commercial. Commercial requirements shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2.1).

5.2.1 Levels A and B. Curtains shall be packed in accordance with MIL-STD-794 in containers selected from table II of MIL-STD-794 for the appropriate level of protection.

5.2.2 Commercial. Curtains shall be packed in accordance with ASTM D3951.

5.3 Palletization. Material shall be palletized (see 6.2.1), in accordance with MIL-STD-147 when the following criteria are met:

a. Load to consist of four or more unskidded containers; and,
b. Load shall utilize a minimum of 80 percent of the pallet base.

5.4 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The curtains are intended for use as door closures for photographic darkrooms and adjoining areas.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Color, if different (see 3.3.1).
c. Identification marking other than contractor's standard practice and marking required (see 3.5).
d. Level of preservation and level of packing required (see 5.1 and 5.2).
e. When palletization is required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.

* 6.3 Subject term (key word listing).

Nylon, coated
Grommets
Curtain, darkroom

6.4 Change from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing Activity:
Navy - YD

(Project 7230-0049)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-19219D(YD)	CURTAIN, DOORWAY, DARKROOM

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2020-10-18T12:36Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Code 156
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:36Z
Check the source to verify that this is the current version before use.