INCH-POND
A-A-55588A
7 October 2025
SUPERSEDING
A-A-55588
31 October 1994

COMMERCIAL ITEM DESCRIPTION

HINGE STRAP (OFFSET)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This Commercial Item Description (CID) covers commercial and industrial quality, non-template butt hinges suitable for use on wood and hollow core doors.

2. Salient Characteristics.




Figure I. Hinge strap

Beneficial comments, recommendations, additions, deletions, clarifications, and any other data that may improve this document should be sent to: DLA Land and Maritime, ATTN: VAI, P.O. Box 3990, Columbus OH 43218–3990, or email fluidflow@.dla.mil. Since contact information can change you may want to verify the currency of the address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:55Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number and dimensions.

DASH NUMBER		2	4	6	8
A NONMINAL SIZE	± 0.06	1.50	1.50	1.50	1.50
B OFFSET	± 0.03	0.50	0.62	0.75	0.87
C LENGTH	± 0.06	1.50	1.37	1.25	1.12
D LENGTH	± 0.06	2.19	2.19	2.19	2.19
T THICKNESS	± 0.05	0.075	0.075	0.075	0.075
NUMBER OF SCREW HOLES	MIN	7	7	8	8
SIZE OF SCREWS 1/	(REF)	#7 X 1/2	#7 X 5/8	#7 X 5/8	#7 X 3/4
DASH NUMBER		12	14	16	18
A NONMINAL SIZE	± 0.06	2.00	2.00	2.00	2.00
B OFFSET	± 0.03	0.50	0.62	0.75	0.87
C LENGTH	± 0.06	2.00	1.87	1.75	1.62
D LENGTH	± 0.06	2.69	2.69	2.69	2.69
T THICKNESS	± 0.005	0.077	0.077	0.077	0.077
NUMBER OF SCREW HOLES	MIN	7	7	8	8
SIZE OF SCREWS 1/	(REF)	#8 X 1/2	#8 X 5/8	#8 X 5/8	#8 X 3/4

1/ SEE SAL. CHAR. 3

2.1 Material. Body: Steel, in accordance with ASTM A506, low carbon, cold rolled.
Pin: Brass in accordance with ASTM B36/B36M, UNS numbers C26000, C26800, C27200, C28000 all H04 hard temper or ASTM B121/B121M all specified UNS numbers with H04 hard temper or corrosion-resistant steel, in accordance with ASTM A666.

2.2 Protective coating. Zinc plated in accordance with ASTM B633, Type II, class Fe/Zn13.

2.3 Hardware. Hinges are furnished with wood screws. The sizes specified are those normally finished by the supplier.

2.4 All dimensions are in inches unless otherwise specified

2.5 Workmanship. The hinges furnished shall be free from imperfections which may impair durability or serviceability.

3. REGULATORY REQUIREMENTS.

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

5. PACKAGING.

5.1 Preservation, packing and marking shall be as specified in the contract or order.


6. NOTES

6.1 Packaging shall be in accordance with ASTM D3951.

6.2 CID based part identification number The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:55Z
Check the source to verify that this is the current version before use.

Example



6.3 Source of documents.

FEDERAL REGULATIONS

FAR	-	Federal Acquisition Regulations (FAR)

(Copies of these documents are available online at www.acquisition.gov.comp/far/index.html.)

Other Publications

ASTM INTERNATIONAL

ASTM B36/B36M	-	Standard Specification for Brass Plate, Sheet, Strip, And Rolled Bar
ASTM A506	-	Alloy and Structural Alloy Steel, Sheet and Strip, Hot-Rolled and Cold Rolled
ASTM A666	-	Steel, Sheet, Strip, Plate, and Flat Bar, Austenitic Stainless, Annealed or Cold-Worked
ASTM B121/B121M	-	Plate, Leaded Brass, Sheet, Strip, and Rolled Bar
ASTM B633	-	Zinc on Iron and Steel, Electrodeposited Coatings of
ASTM D3951	-	Standard Practice for Commercial Packaging

(Copies of these documents are available at https://www.astm.org.)

6.4 Ordering data. Acquisition documents must specify the following.

1. Title, number, and date of this CID.
2. Arrangement for first article inspection or whether first article is not required
3. Applicable level and packaging requirements

6.5 Cross-reference data. Butt hinges conforming to this CID are interchangeable/substitute with butt hinges conforming to MS27973B dated 21 dec 1987.

TABLE II. CROSS-REFERENCE TABLE.

Cancelled MS PIN	Replacement CID PIN
MS27968 - * 2/	AA55587 - * 2/

2/ *represents the same designation codes for both MS and CID PINS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:55Z
Check the source to verify that this is the current version before use.

6.6 Key words.

Pin
Door
Swaged

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army – AR
Navy – YD
Air Force – 71
DLA - CC

Preparing activity:
DLA - CC

(Project 5340-2025-021)

Review activities:
Army – AV, CR4
Navy – MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:55Z
Check the source to verify that this is the current version before use.