INCH-POUND
A-A-55618A
31 December 1997
SUPERSEDING
A-A-55618
29 September 1995

COMMERCIAL ITEM DESCRIPTION

CASTER, SWIVEL, KINGPINLESS INDUSTRIAL, HEAVY DUTY WITH TOWING APPLICATION

This General Services Administration has authorized the use of this *Commercial Item Description* for all federal agencies..

1. SCOPE: This Commercial Item Description (CID) covers industrial heavy duty kingpinless swivel casters for non-powered material transport and maintenance equipment with towing application for no more than five (5) miles per hour (mph).

2. SALIENT CHARACTERISTICS:

2.1 Casters furnished under this CID shall be flat mounted plate type kingpinless ball bearing swivel design. Swivel casters shall conform to the dimensions and load rating as specified in Table I and figures below.




FIG 1. SWIVEL CASTER




FIG. 2. MOUNTING PLATE




FIG. 3. MOUNTING PLATE




FIG. 4. MOUNTING PLATE

BENEFICIAL COMMENTS, RECOMMENDATIONS, ADDITIONS, DELETIONS, CLARIFICATIONS, ETC., AND DATA WHICH MAY IMPROVE THIS DOCUMENT SHOULD BE SENT TO: DEFENSE INDUSTRIAL SUPPLY CENTER, ATTN: DISC-EED, 700 ROBBINS AVENUE, PHILADELPHIA, PA 19111-5096.

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:56Z
Check the source to verify that this is the current version before use.

TABLE I. DASH NUMBERS AND DIMENSIONS.

DASH NO.	ØA	WHEEL WIDTH	WHEEL MATERIAL	MIN. LOAD CAPACITY (LBS)	OVERALL HEIGHT B	MOUNTING BOLT DIAMETER	SWIVEL OFFSET C	MOUNTING PLATE
8	8.00	2.50	RUBBER	670	10.50	.500	2.56	SEE FIGURE 2
			POLYURETHANE	1800				
8H	8.00	2.50	RUBBER	670	11.00	.500	2.56	SEE FIGURE 3
			POLYURETHANE	1800				
12	12.00	3.00	RUBBER	1140	14.75	.500	3.62	SEE FIGURE 4
			POLYURETHANE	3400				

2.1.1 Swivel caster. Swivel caster has a swivel horn and wheel assembly that will rotate freely through 360°.

2.2 Mounting plate and horn assembly. The mounting plate and horn assembly shall be made of steel plate, cast or forged steel. The horn legs shall be either an integral part of the horn plate or welded thereto.

2.2.1 Finish. Exposed metal surfaces of the caster assemblies shall be zinc plated per ASTM B633, Type II or III, SC2.

2.2.2 Kingpinless raceway. Raceway shall be three (3) inches minimum diameter which measured from center of ball bearing to center of ball bearing at 180° apart.

2.2.3 Swivel assembly. The kingpinless swivel assembly shall be ball bearing assembly type with a smooth non-binding operation. The raceways shall be case hardened to a depth of .020 to .030 inch and shall be filled to capacity with commercial quality steel ball bearings. The case hardness shall be within the range of 83 to 91 on the 15N scale with a minimum average of 86 when checked on four (4) places approximately 90 degrees apart.

2.2.4 Wheel bearing. Wheel bearing shall be precision tapered roller or precision ball journal bearings having a minimum life rating of 2500 hours at rated loads and rated speed and shall be manufactured in accordance with high-grade bearing manufacturing practice.

2.2.5 Axle. The axle shall be constructed of steel and shall secure the wheel by means of a lockout or slotted nut and pin. During operation, the axle shall not rotate loose or bind the wheel.

2.2.6 Wheel hardness. The hardness of treads shall be 70 ±5 points for rubber, and 92 ±5 points for polyurethane, measured on the face of the treads by type A Shore durometer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:56Z
Check the source to verify that this is the current version before use.

2.2.7 Swivel lock. When specified, four position lever operated plunger type swivel lock shall be furnished. When engaged, the swivel lock shall prevent the caster from swiveling while rolling or shall prevent rolling while at right angles to the normal path of the equipment. When disengaged, the swivel lock shall permit full 360° free swiveling.

2.2.8 Brake. When specified, a manually operated with side or front mounted control lever parking brake shall be provided. The brake shall be tread contact type with, using a combination of pressure and friction to prevent wheel rotation. The control lever shall be readily accessible for operation, permitting quick and easy brake application and release. The control lever shall not require a physical force in excess of 50 pounds to set the brake. When disengaged, the brake lever shall be capable of ensuring brake contact surface has a clearance of at least .062 inch off the wheel tread surface.

2.2.9 Lubrication fitting. The swivel assembly and wheel assembly shall have pressure lubrication fittings and shall be prelubricated with water repellent grease having a -32° C to +71° C (-10° F to +160° F) operating temperature range.

2.3 Casters as a minimum, shall be able to withstand the following tests:

2.3.1 Static load test. The caster shall be able to withstand four (4) times its rated capacity for one (1) minute minimum without damage.

2.3.2 Endurance test. The casters shall be loaded to rated capacity and shall be run continuously (see 4.3) at eight (8) mph minimum on an endless belt or drum type testing machine with a smooth, uninterrupted running surface for a period of forty (40) hours. At the completion of the test, there shall be no indication of excess wear on the bearing races, looseness of bearings, scuffing of tires, looseness of tire tread, or permanently deformed members.

2.3.3 Obstacle test. The caster shall be loaded to rated capacity and shall be run continuously (see 4.3) at five (5) mph minimum on an endless belt or drum type testing machine for a minimum duration of two (2) hours. There shall be an obstacle (see 2.3.3.1) at every 6 feet of travel of the machine. At the completion of the test, there shall be no indication of excess wear to the bearing races, looseness of bearings, scuffing of tires, or looseness of tire tread, or permanently deformed members.

2.3.3.1 Obstacles shall consists of a rectangular cross-sectioned steel bar .250 inch in thickness, so mounted that the longitudinal axis of the obstacles perpendicularly across the path of the casters.

2.3.4 Brake Test. For casters furnished with a brake, the brake must prevent wheel rotation from a horizontal pulling force equal to 103 percent (%) of the force required to initiate movement of the equipment under rated load with brakes disengaged. The test shall be conducted on a level concrete floor by applying a horizontal pulling force on a rated load evenly distributed over four (4) casters, two of which will have the brakes engaged. The test should be repeated a minimum of four (4) times.

3. QUALITY CONFORMANCE PROVISIONS.

3.1 Product conformance. The product provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and the quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:56Z
Check the source to verify that this is the currentversion before use..

4. NOTES.


4.1 Unless otherwise specified, all dimensions are in inches.

4.2 Unless otherwise specified in the contract or purchase order, packaging shall be in accordance with ASTM D3951.

4.3 "Continuously" shall mean 45 minutes of rolling operation for each hour of work. The cycling of the stop and go periods shall be at the option of the manufacturer.

4.4 Unless otherwise specified, tolerances: .xx ± .12, .xxx ± .031.

4.5 The part identification number (PIN) shall consist of the basic commercial item description number followed by a dash number from Table I, a code letter for wheel material. Add "B" for Brake (optional) and/or "L" for swivel lock (optional) after PIN number.



Military Interests:

Custodians:
Navy – AS
Air Force - 99

Review Activity:
Air Force 82

Civil Agency Coordination Activity:
GSA-FSS

Preparing Activity:
DLA-IS
(Project 5340-2443)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:56Z
Check the source to verify that this is the current version before use.